# **Permatex.**

# SAFETY DATA SHEET

Revision Date 09-Jan-2017 Version 2

# 1. IDENTIFICATION

**Product identifier** 

Product Name PC PIT CREW'S CHOICE GAS TANK AND RADIATOR REPAIR 28GR.

Other means of identification

Product Code 12020 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use (Epoxy resin)

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufactured and Distributed by:May Also Be Distributed by:ITW PermatexITW Permatex Canada6875 Parkland Blvd.35 Brownridge Road, Unit 1Solon, OH 44139 USAHalton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

# Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

# Label elements

# **Emergency Overview**

#### Warning

Causes skin irritation Causes serious eye irritation May cause an allergic skin reaction



Appearance Gray Physical state Solid Odor Amine

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Not applicable

# Other Information

- This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product

Unknown acute toxicity 69 % of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
BISPHENOL A/EPICHLOROHYDRIN BASED	25068-38-6	10 - 30	*
EPOXY RESIN			
3,6-DIAZAOCTANETHYLENEDIAMIN	112-24-3	0.1 - 1	*
SILICA, QUARTZ	14808-60-7	0.1 - 1	*

# 4. FIRST AID MEASURES

# **Description of first aid measures**

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

\_\_\_\_\_

# 12020 - PC PIT CREW'S CHOICE GAS TANK AND RADIATOR REPAIR 28GR.

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

**Environmental precautions**Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Ensure adequate ventilation. Take up mechanically, placing in appropriate containers for

disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials Strong oxidizing agents

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
SILICA, QUARTZ	TWA: 0.025 mg/m <sup>3</sup> respirable	(vacated) TWA: 0.1 mg/m <sup>3</sup>	IDLH: 50 mg/m3 respirable dust
14808-60-7	fraction	respirable dust	TWA: 0.05 mg/m³ respirable dust
		: (30)/(%SiO2 + 2) mg/m <sup>3</sup> TWA	
		total dust	
		: (250)/(%SiO2 + 5) mppcf TWA	
		respirable fraction	
		: (10)/(%SiO2 + 2) mg/m <sup>3</sup> TWA	
		respirable fraction	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Physical state Solid Appearance Gray Odor Amine

Odor threshold No information available

# 12020 - PC PIT CREW'S CHOICE GAS TANK AND **RADIATOR REPAIR 28GR.**

Setaflash Closed Cup

**Property** Values Remarks • Method

pН No information available No information available Melting point / freezing point

Not Applicable

Boiling point / boiling range Flash point > 93 °C / > 200 °F **Evaporation rate** No information available

Flammability (solid, gas) No information available Flammability Limit in Air

**Upper flammability limit:** No information available Lower flammability limit: No information available Vapor pressure No information available Vapor density No information available

Relative density 1.665

Water solubility No information available Solubility in other solvents No information available **Partition coefficient** No information available **Autoignition temperature** No information available >200°C (>392°F) **Decomposition temperature** 

Kinematic viscosity No information available No information available Dynamic viscosity No information available **Explosive properties Oxidizing properties** No information available

Other Information

Softening point No information available Molecular weight No information available

**VOC Content (%)** O

**Density** No information available No information available **Bulk density** 

#### 10. STABILITY AND REACTIVITY

# Reactivity

No data available

# **Chemical stability**

Stable under recommended storage conditions

# Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Excessive heat.

# Incompatible materials

Strong oxidizing agents

#### **Hazardous Decomposition Products**

Carbon oxides Nitrogen oxides (NOx) Halogenated compounds Metal oxides

# 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

May cause irritation of respiratory tract. Inhalation

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

# 12020 - PC PIT CREW'S CHOICE GAS TANK AND RADIATOR REPAIR 28GR.

**Skin contact** May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN 25068-38-6	= 11400 mg/kg(Rat)	•	-
3,6-DIAZAOCTANETHYLENEDIAM IN 112-24-3	= 2500 mg/kg ( Rat )	= 550 mg/kg(Rabbit)	-
SILICA, QUARTZ 14808-60-7	= 500 mg/kg(Rat)	-	-

#### Information on toxicological effects

**Symptoms** No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization**No information available. **Germ cell mutagenicity**No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
SILICA, QUARTZ 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans Not classifiable as a human carcinogen NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central Vascular System (CVS), Eyes, Respiratory system.

# The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 16755 mg/kg **ATEmix (dermal)** 54699 mg/kg

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

32 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

#### **Mobility**

No information available.

Chemical Name	Partition coefficient
3,6-DIAZAOCTANETHYLENEDIAMIN	-1.4
112-24-3	

#### Other adverse effects

# 12020 - PC PIT CREW'S CHOICE GAS TANK AND RADIATOR REPAIR 28GR.

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

# 14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

<u>IATA</u>

Proper shipping name: Not regulated

MDG

Proper shipping name: Not regulated

# 15. REGULATORY INFORMATION

International Inventories

**TSCA** Complies Complies **DSL/NDSL** Not determined **EINECS/ELINCS** Not determined **ENCS** Not determined **IECSC** Not determined **KECL** Complies **PICCS AICS** Not determined

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No

**Reactive Hazard** 

No

#### CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

# **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
CHLORINATED PARAFFIN - 63449-39-8	Carcinogen	
SILICA, QUARTZ - 14808-60-7	*Carcinogen (airborne particles of respirable size only)	

<sup>• \*</sup>The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product **U.S. State Right-to-Know Regulations** 

Chemical Name	New Jersey	Massachusetts	Pennsylvania
MAGNESIUM SILICATE	X	X	X
14807-96-6			
FERROSILICON	X	=	-
8049-17-0			
CHLORINATED PARAFFIN	-	X	-
63449-39-8			
3,6-DIAZAOCTANETHYLENEDIAM	X	X	X
IN			
112-24-3			
SILICA, QUARTZ	X	X	X
14808-60-7			

#### **U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

#### **WHMIS Hazard Class**

D2B - Toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 1 Instability 0

HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

**Revision Date** 09-Jan-2017

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**