SAFETY DATA SHEET

1. Identification

Product identifier Rain-X Anti Fog

Other means of identification

Synonyms 36235

Recommended use Anti Fog Treatment
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Permatex Canada

Address 35 Brownridge Road, Unit 1
Halton Hills, ON L7G 0C6

Canada

Telephone 1-905-693-8900

e-mail literature.canada@permatex.com

Emergency phone number 1-877-504-9352
Supplier See above.

2. Hazard identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSerious eye damage/eye irritationCategory 2A

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapour.
Causes serious eye irritation.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Ground and bond container and receiving equipment. Take action to prevent

static discharges.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Response In case of fire: Use appropriate media to extinguish.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical nameCommon name and synonymsCAS number%Isopropanol67-63-013

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

#28725 Page: 1 of 7 Issue date 16-November-2017

Skin contact Eye contact IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious, or is convulsing.

Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

General information

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Take off all contaminated clothing immediately. Wash contaminated clothing before reuse. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Hazardous combustion products

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods
General fire hazards

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Sand.

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed. Vapours may form explosive mixtures with

May include and are not limited to:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Do not discharge into lakes, streams, ponds or public waters.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight.

All equipment used when handling the product must be grounded.

Take precautionary measures against static discharges.

Avoid contact with eyes.

Wear appropriate personal protective equipment.

Observe good industrial hygiene practices.

Wash thoroughly after handling.

When handling, do not eat, drink or smoke.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame.

Prevent electrostatic charge build-up by using common bonding and grounding techniques.

Store in a cool, dry place out of direct sunlight.

Store in original tightly closed container.

Store in a well-ventilated place.

Store away from incompatible materials (see Section 10 of the SDS).

Keep out of reach of children.

#28725 Page: 2 of 7 Issue date 16-November-2017

Secretarion		8. Expo	sure controls/Pers	onal protec	tion	
Sopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm 200 ppm TWA 200 ppm	•					
Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Components Type Value Isopropanol (CAS 67-63-0) STEL 984 mg/m3 400 ppm TWA 492 mg/m3 200 ppm Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm TWA Acetone Urine *-For sampling details, please see the source document. proportate engineering Introls dividual protection Matural or butyl rubber, nitrile or neoprene gloves. Confirm with a reputable supplier first. As required by employer code. Wear safety glasses with side shields (or goggles). Skin protection Hand protection Hand protection Natural or butyl rubber, nitrile or neoprene gloves. Confirm with a reputable supplier first. As required by employer code. Were exposure found in Surviva response and safety practices. Wash hands before president properties Other Posicial and Chemical properties Popearance Clear		t Values	Turne	v	alus.	
Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Components Type Isopropanol (CAS 67-63-0) STEL A00 ppm TWA A492 mg/m3 A00 ppm TWA A92 mg/m3 A00 ppm TWA A92 mg/m3 A00 ppm TWA Components Type Value Isopropanol (CAS 67-63-0) STEL Components Type Value Sopponents Type Value Sopponents Type Value Sopponents STEL Sopponents Sopponents STEL Sopponents Sopponents Sopponents Type Value Sopponents						
Canada. Alborta OELs (Occupational Health & Safety Code, Schodule 1, Table 2) Components Type Value Isopropanol (CAS 67-63-0) STEL 984 mg/m3 400 ppm TWA 482 mg/m3 200 ppm Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm Ological limit values ACGH Biological Exposure Indices Components Value Determinant Specime	isopropanoi (CAS 67-63-0)					
Sopropanol (CAS 67-63-0) STEL 984 mg/m3 400 ppm TWA 492 mg/m3 200 ppm TWA 492 mg/m3 400 ppm 492 mg/m3					• •	
Isopropanol (CAS 67-63-0) STEL 17WA 18WA 20W ppm 20WA 20W		cupational Heal	_			
TWA 492 mg/m3 200 ppm Canada, British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada, Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada, Ontario OELs, (Control of Exposure to Biological or Chemical Agents) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada, Outario OELs, (Control of Exposure to Biological or Chemical Agents) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada, Quebec OELs, (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm ological limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling time Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine * * For sampling details, please see the source document. propropriate engineering Ensure adequate ventilation. Skin protection Hand protection measures, such as personal protective equipment Eye/face protected Wear safety glasses with side shields (or goggles). Skin protection Hand protection As required by employer code. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trainent health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134); CANICSA-2944 and ANSI's standard for respiratory protection (288.2). Thermal hazards Popearance Clear						
Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm Isopropanol (CAS 67-63-0) Acetone Value Isopropanol (CAS 67-63-0) 40 mg/L Acetone Value * * - For sampling details, please see the source document. Propropriate engineering Introls Components Value Ensure adequate ventilation. Skin protection Hand protection Other As required by employer code. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trainen health and safety professional following requirements found in OSHA's respirator at andard (29 CFR 1910.134). CAN/CSA-2944 and ANSI's standard for respiratory protection (28.8.2). Not applicable. Papearance Clear	isopropunor (crite or oc c)		0122		<u> </u>	
Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Components Type Isopropanol (CAS 67-63-0) STEL COMPONENTS Type Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Isopropanol (CAS 67-63-0) STEL SUBJECT STEL SUBJECT			TWA	4	92 mg/m3	
Safety Regulation 296/97, as amended) Components Type Value Sopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm				2	00 ppm	
Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm			ional Exposure Limits	or Chemical S	ubstances, Occupational Health and	
Isopropanol (CAS 67-63-0) STEL TWA 200 ppm Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Isopropanol (CAS 67-63-0) STEL JOD ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Typa Value Isopropanol (CAS 67-63-0) STEL JOD ppm TWA 200 ppm Canada. Outerol Of Exposure to Biological or Chemical Agents) Components Typa Value Isopropanol (CAS 67-63-0) STEL JOD ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Typa STEL JOD ppm TWA JOD ppm TWA JOD ppm TWA JOD ppm TWA JOD ppm TWA JOD ppm TWA JOD ppm TWA JOD ppm		as amended)	Turno	v	'alua	
TWA 200 ppm Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm Sological limit values ACGIH Biological Exposure Indices Components Value Determinant Specime Sampling time Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine * * - For sampling details, please see the source document. proporpirate engineering Ensure adequate ventilation. Skin protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Natural or butyl rubber, nitrile or neoprene gloves. Confirm with a reputable supplier first. As required by employer code. Respiratory protection Respiratory should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirators reportant (2RS 2). Thermal hazards Not applicable. Universe respiratory protection of a trained health and safety professional following requirements found in OSHA's respiratory protection (ZRS 2). Not applicable. Universe value and protective equipment supplier first. As required by employer code. Respiratory protection Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke.	· · · · · · · · · · · · · · · · · · ·					
Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 2000 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm TWA Palue Components Value Determinant Specimen Sampling time Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine * * - For sampling details, please see the source document. " - For sampling details, please see the source document. Specimen Sampling time Ensure adequate ventilation. Stin protection Measures, such as personal protective equipment Eyerface protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Other As required by employer code. Respiratory protection Respiratory should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator. Respiratory should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134). CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (288.2). Thermal hazards Not applicable. 9. Physical and chemical properties	isoproparior (CAS 07-03-0)				• •	
Sopropanel (CAS 67-63-0) STEL 400 ppm					оо ррш	
Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm TWA 200 ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm TWA Palue Determinant Specimen Sampling time Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine * * - For sampling details, please see the source document. Proprofiate engineering Introls Idividual protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Hand protection Hand protection Cher As required by employer code. Respiratory protection Respiratory protection Respiratory protection Thermal hazards Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator and safety professional following requirements found in OSHA's respirator and safety professional following requirements found in OSHA's respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator shandard (29 CFR 1910.134). CANICSA-294.4 and ANSI's standard for respiratory protection (288.2). Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke.		keg. 217/2006, T	-		alue	
TWA 200 ppm Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Isopropanol (CAS 67-63-0) STEL 400 ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 5000 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm Ological limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling time Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine * * - For sampling details, please see the source document. propriate engineering Introlection Mearures, such as personal protective equipment Eye/face protection Hand protection Hand protection As required by employer code. Respiratory protection Cher As required by employer code. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respiratory should be selected by and used under the direction of a trained health and safety professional following requirements found in OSTHA's respirator and are fell professional following requirements found in OSTHA's respirator shandard (29 CFR 1910.134). CANICSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Not applicable. 1 Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke.						
Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Components Type Value Isopropanol (CAS 67-63-0) STEL TWA 200 ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm Ological limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Specimen Specimen Specimen Specimen Specimen Specimen Twa Specimen Specimen Sampling time Isopropriate engineering Incrols dividual protection measures, such as personal protective equipment Eyerface protection Hand protection Hand protection Hand protection Hand protection Respiratory protection Respiratory protection Respiratory protection Respiratory protection Hand protection Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. Properties Properties Properties Department Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not ea	isopropanor (eric or oo o)				• •	
Sopropanel (CAS 67-63-0) STEL 400 ppm	Canada Ontario OELa (Ca	natural of Evensor			90 pp	
Isopropanol (CAS 67-63-0) STEL TWA 200 ppm 200 ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm Ological limit values ACGIH Biological Exposure Indices Components Value Determinant Specime Specime Specime Supropriate engineering Introls dividual protection measures, such as personal protective equipment Eye/face protection Hand protection Hand protection Other Respiratory protection Respiratory protection Respiratory protection Thermal hazards Not applicable. Not applicable Handle in accordance with good industrial hygiene and safety product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Opearance Clear	•	ontroi oi Expost	_	• .	alue	
TWA 200 ppm Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm Ological limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling time Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine * * - For sampling details, please see the source document. Propropriate engineering Ensure adequate ventilation. Skin protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Watural or butyl rubber, nitrile or neoprene gloves. Confirm with a reputable supplier first. Other As required by employer code. Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-294.4 and ANSI's standard for respiratory protection (Z88.2). Thermal hazards Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties				4	00 pm	
Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Type Value Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm TWA 983 mg/m3 400 ppm Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine * *- For sampling details, please see the source document. *- For sampling details, please see see the source document. *- For sampling details, please see seen source document. *- For sampling details, please see seen seen seen seen seen seen s	, , ,				• •	
STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm Sampling time Sampling	Canada Quebec OELs (M	inistry of Labou			• •	
Isopropanol (CAS 67-63-0) STEL 1230 mg/m3 500 ppm TWA 983 mg/m3 400 ppm Ological limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling time Sopropanol (CAS 67-63-0) 40 mg/L Acetone Urine * - For sampling details, please see the source document. Suppropriate engineering Introls dividual protection measures, such as personal protective equipment Eyelface protection Hand protection Hand protection Other As required by employer code. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Thermal hazards Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties		illistry of Labou	_	-		
TWA 983 mg/m3 400 ppm cological limit values ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling time Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine *	Isopropanol (CAS 67-63-0)			1.	230 mg/m3	
ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling time Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine *				5	00 ppm	
ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling time Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine *			TWA		•	
ACGIH Biological Exposure Indices Components Value Determinant Specimen Sampling time Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine * * - For sampling details, please see the source document. * - For sampling details, please see the source documents such sets of sampling time seeds of sampling time seeds of sampling time seeds of sampling time seeds of sampling time see				4	ou ppm	
Components Value Determinant Specime Sampling time	_					
Isopropanol (CAS 67-63-0) 40 mg/L Acetone Urine * * - For sampling details, please see the source document. propropriate engineering Ensure adequate ventilation. Wear safety glasses with side shields (or goggles). Skin protection Wear safety glasses with side shields (or goggles). Skin protection Natural or butyl rubber, nitrile or neoprene gloves. Confirm with a reputable supplier first. As required by employer code. Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Thermal hazards Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Depearance Clear			Determinant	Specimen	Sampling time	
* - For sampling details, please see the source document. propriate engineering introls dividual protection measures, such as personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Natural or butyl rubber, nitrile or neoprene gloves. Confirm with a reputable supplier first. Other As required by employer code. Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Thermal hazards Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Depearance Clear	- <u>-</u>				*	
Insure adequate ventilation. Ensure adequate ventilation. Eye/face protection measures, such as personal protective equipment Eye/face protection Bair Potection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Other As required by employer code. Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Thermal hazards Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties pearance Clear	,	· ·		Office		
dividual protection measures, such as personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Other Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Thermal hazards Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Opearance Clear	. •					
dividual protection measures, such as personal protective equipment Eye/face protection Skin protection Hand protection Other Respiratory protection Respiratory should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Thermal hazards Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Clear		Ensure adequ	uate ventilation.			
Eye/face protectionWear safety glasses with side shields (or goggles).Skin protectionNatural or butyl rubber, nitrile or neoprene gloves. Confirm with a reputable supplier first.OtherAs required by employer code.Respiratory protectionWhere exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).Thermal hazardsNot applicable.Peneral hygiene onsiderationsHandle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke.9. Physical and chemical properties		e euch ae norec	anal protective equipme	ınt		
Skin protection Hand protection Other Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Clear		-				
Natural or butyl rubber, nitrile or neoprene gloves. Confirm with a reputable supplier first. As required by employer code. Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Clear	•	, ,	,	(0 00 /		
Other Respiratory protection Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Clear	_	Natural or butyl rubber, nitrile or neoprene gloves. Confirm with a reputable supplier first				
Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Clear						
professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Clear	Respiratory protection					
CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Not applicable. Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Clear						
Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties Clear						
breaks and immediately after handling the product. When using, do not eat, drink or smoke. 9. Physical and chemical properties ppearance Clear	Thermal hazards					
ppearance Clear						
ppearance Clear		9. PI	hysical and chemic	al propertie	 S	
	nnoaranco		,	p po. 00	-	
	•	_				

Form Liquid.

Not available. Colour Odour Alcohol

Odour threshold Not available.

Melting point/freezing point Not available. Not available. Initial boiling point and boiling

range

Flash point 35.0 °C (95.0 °F) **Evaporation rate** Not available. Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper

(%)

Not available. Vapour pressure Vapour density Not available.

Relative density 0.99

Solubility(ies)

Not available. Solubility (Water) Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Density 8.25

Explosive properties Not explosive. Oxidising properties Not oxidising

VOC (Weight %) 15 %

10. Stability and reactivity

May react with incompatible materials. Reactivity **Chemical stability** Material is stable under normal conditions. Hazardous polymerisation does not occur. Possibility of hazardous

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Do not mix with other chemicals.

Acids. Strong oxidising agents. Incompatible materials

Hazardous decomposition

products

11. Toxicological information

May include and are not limited to: Oxides of carbon.

Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation

No adverse effects due to skin contact are expected. Skin contact

Eye contact Causes serious eye irritation.

May cause stomach distress, nausea or vomiting. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity

#28725 Page: 4 of 7 Issue date 16-November-2017

Species Test results Components Isopropanol (CAS 67-63-0) **Acute** Dermai LD50 Rabbit 12800 mg/kg, HSDB 16.4 ml/kg, 24 Hours, ECHA Inhalation LC50 Rat > 10000 ppm, 6 Hours, ECHA 16970 mg/l/4h, HMIRA Oral LD50 Dog 4797 mg/kg, HSDB 3600 mg/kg, HSDB Mouse Rabbit 5030 mg/kg, HSDB 5 g/kg, HSDB Rat 5.8 g/kg, ECHA Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Not available. **Exposure minutes** Not available. Erythema value Not available. Oedema value Serious eye damage/eye Causes serious eye irritation. irritation Not available. Corneal opacity value Iris lesion value Not available. Conjunctival reddening Not available. value Not available. Conjunctival oedema value Recover days Not available. Respiratory or skin sensitisation Respiratory sensitisation Not a respiratory sensitizer. Skin sensitisation This product is not expected to cause skin sensitisation. Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. Carcinogenicity See below. **ACGIH Carcinogens** Isopropanol (CAS 67-63-0) A4 Not classifiable as a human carcinogen. Canada - Manitoba OELs: carcinogenicity 2-Propanol (CAS 67-63-0) Not classifiable as a human carcinogen. Reproductive toxicity This product is not expected to cause reproductive or developmental effects. Specific target organ toxicity -Not classified. single exposure Not classified. Specific target organ toxicity repeated exposure **Aspiration hazard** Not an aspiration hazard. **Chronic effects** Prolonged inhalation may be harmful. **Further information** Not available. 12. Ecological information **Ecotoxicity** See below

Ecotoxicological data Components		Species	Test results
Isopropanol (CAS 67-63-0))		
Algae	IC50	Algae	1000 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours

Components **Species Test results**

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) > 1400 mg/L, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Mobility in soil No data available. Mobility in general Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Empty containers or liners may retain some product residues. This material and its container must

be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

General

Canada: TDG Proof of Classification: In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue. If applicable, the technical name and the classification of the product will appear below.

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number UN1993

FLAMMABLE LIQUID, N.O.S. Proper shipping name

Technical name Isopropanol

Hazard class 3 Ш Packing group 16, 150 Special provisions

TDG



15. Regulatory information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Isopropanol (CAS 67-63-0)

1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS status Controlled

International regulations

#28725 Page: 6 of 7 Issue date 16-November-2017 **Inventory status**

Country(s) or region Inventory Name On Inventory (Yes/No)*

Canada Domestic Substances List (DSL)


Canada Non-Domestic Substances List (NDSL) No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information



HEALTH / 2
FLAMMABILITY 3
PHYSICAL HAZARD 0
PERSONAL PROTECTION X



Issue date Revision date 16-November-2017 16-November-2017

Version No.

01

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Prepared by

Dell Tech Laboratories Ltd. Phone: (519) 858-5021