HALL CHEM MFG. INC.

1270 rue Nobel Tel. : (450) 645-0296 Boucherville Qc J4B 5H1 Fax : (450) 645-0444

MATERIAL SAFETY DATA SHEET

EMERGENCY: CANUTEC (613) 996-6666

MSDS: 700-2

PRODUCT IDENTIFICATION AND USE

NAME OF PRODUCT: Chain oil –light-medium-heavy-USE OF PRODUCT: used for the lubrication of chainsaw chains

TRANSPORTATION OF DANGEROUS GOODS

SHIPPING NAME: Chain oil WHMIS: Non controlled product

P.N.I.: PRIMARY CLASS: PACKING GROUP: SUBSIDIARY CLASS:

COMPONENTS

COMPOSITION	% V/V	CASE #	LD ₅₀ mg/kg Oral/rat	LC_{50}	TLV ppm 8h
			Oral/rat		
Lubricating oils recycled	40-95%	64742-58-1	>15 000	Not available	5mg/m³
(petroleum)					
Residual oils not parafinic	0-50	64742-62-7	Not available	Not available	5mg/m³
Lubricating oils recycled neutral	0-25	72623-86-0	Not available	Not available	5mg/m³

PHYSICAL CARACTERISTICS

PHYSICAL STATE:	APPEARANCE:	ODOR:	ODORTRESHOLD:			
Liquid	Red, viscous	Petroleum	Not available			
VAPOR TENSION:	VAPOR DENSITY:	EVAPORATING RATE:				
Not available	Not available	Not available				
BOILING RANGE : 260°C (500°F)	FREEZING POINT:	pH : Not applicable				
DENSITY (g/mL):	DISTRIBUTION FACTOR	SOLUBILITY IN WATER (25°C):				
Approx. 0,85 to 0,88 at 15,5°C (60°F)	WATER/OIL: Not available	Insoluble				
REACTIVITY DATA						



MSDS: 700-2 Page 1 of 3

HALL CHEM MFG. INC.

1270 rue Nobel Tel. : (450) 645-0296 Boucherville Qc J4B 5H1 Fax : (450) 645-0444

MATERIAL SAFETY DATA SHEET

EMERGENCY: CANUTEC (613) 996-6666

CHEMICAL STABILITY: Stable

INCOMPATIBILITY WITH OTHER PRODUCTS: Avoid strong oxidizing agents (ex: chlorates, peroxides,

strong acids)

REACTIVITY CONDITIONS: No hazardous polymerization. Avoid excessive heat and formation of vapours

or mists.

EXPLOSION AND FIRE RISKS

FLAMMABILITY: ND

EXTINGUISHING METHODS: Carbon dioxide, foam, dry chemical, water spray. Use water jet to cool fire

exposed containers.

FLASH POINT: 171°C (340°F), Cleveland open cup

AUTO-IGNITION TEMPS.: Not available

FLAMMABILITY (% per volume)
SUPERIOR LIMIT: Not available
LOWER LIMIT: Not available

HAZARDOUS COMBUSTION PRODUCT: Thermal decomposition and burning may produce carbon

monoxide, carbon dioxide, and dense smoke.

EXPLOSIBILITY DATA: Not available

TOXICOLOGICAL PROPERTIES

ABSORPTION V	VAYS	CONTACT		
SKIN √	INHALATION √	INGESTION √	WITH SKIN √	EYES √

EFFECTS OF EXPOSURE TO PRODUCT: Inhalation of oil mist or vapours from hot oil may cause irritation of the upper respiratory tract. Prolonged or repeated contact may cause various forms of dermatitis including folliculitis and oil acne. Long term intensive exposure to oil mist may cause benign fibrosis.

PREVENTIVE MEASURES

PROTECTIVE EQUIPMENT: Gloves, security glasses and protective apron.

GLOVES: Viton, nitrile, neoprene, PVC

RESPIRATORY SYSTEM: Respirator approved by NIOSH / MSHA

OCULAR INSTRUMENT: Chemical safety goggles



MSDS: 700-2 Page 2 of 3

HALL CHEM MFG. INC.

1270 rue Nobel Boucherville Qc J4B 5H1

MATERIAL SAFETY DATA SHEET

Tel.: (450) 645-0296

Fax: (450) 645-0444

EMERGENCY: CANUTEC (613) 996-6666

CLOTHING: Resistant to product

TECHNICAL CONTROL: Mechanical or local ventilation

PROCEDURE IN CASE OF LEAKS/SPILLS: Eliminate all ignition sources. Isolate hazard area and restrict access. Wear appropriate breathing apparatus and protective clothing. Try to work upwind of spill. Dike and contain land spills; contain water spills by booming. For large spills remove by mechanical means and place in containers. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Flush area with water to remove trace residue.

HANDLING: Avoid excessive heat, formation of oil mist, breathing of vapours and mist of hot oil and prolonged or repeated contact with skin. Launder contaminated clothing prior to reuse. Properly dispose of

contaminated leather articles, including shoes, that cannot be decontaminated.

WASTE DISPOSAL: Dispose in accordance with federal, provincial and local regulations.

STORAGE: Store in cool, dry well-ventilated area. Keep away from ignition sources (open flame, sparks and electricity).

FIRST AID

SKIN: Remove contaminated clothing. Wash exposed area with soap and water for at least 15 minutes. **EYES:** Flush eyes with water for 15 minutes while holding eyelids apart. Get medical attention.

INHALATION: Remove to fresh air. Administer artificial respiration if breathing is stopped. Get medical

attention.

INGESTION: Do not induce vomiting. Get medical attention immediately.

NOTE TO PHYSICIAN: In general, lubricating oils have low oral toxicity. High pressure injection under the skin

may have serious consequences and may require urgent treatment.

INFORMATION ON THE M.S.D.S. PREPARATION

PREPARED BY: TELEPHONE: (450) 645-0296 REVISED January, 2015

Hall Chem Mfg. Inc.

NOTE:

The information in this detailed M.S.D.S. is available on request, for the customer service. It must not be used for any other purpose and its reproduction and/or publication is forbidden without the consent of HALL CHEM MFG. INC. Even though this information is based on reliable sources, HALL CHEM MFG. INC. cannot guarantee its accuracy and formally excludes all explicit guarantee relative to the exactitude of this information or of the results following its application.



MSDS: 700-2 Page 3 of 3