



GB

1 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 01-01-2015 Replaces the version of: 01-03-2014 PDF date: 01-01-2015
Trade name: 01 001734 AUTOSOL® Stainless Steel Polish (75 ml Tube)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Identification of the substance or mixture / Product identifier

Autosol® Stainless Steel Polish

Use of the substance/mixture

Cleans and polishes stainless steel.

Company/undertaking identification / Details of the supplier of the safety data sheet

Autosol LLC, P.O. Box 340358 Austin, Texas 78734
Telephone +1-512-804-9337, Fax +1-512-266-6518
email: info@autosol.com
Internet: www.autosol.com

E-mail address of the competent person: msds@autosol.com

Emergency telephone

+1-512-804-9337

Telephone number of the company in case of emergencies:

Tel. 1-800-314-5545

SECTION 2: Hazards identification

To people

See point 11 and 15.

The mixture is classified as dangerous in the terms of the directive 1999/45/EC.

Irritation of the skin.

Vapours may cause drowsiness and dizziness.

To the environment

See point 12.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

REGULATION (EC) No 648/2004

15 % or over but less than 30 %

aliphatic hydrocarbons

5 % or over but less than 15 %

soap

less than 5 %

aromatic hydrocarbons

SECTION 3: Composition/information on ingredients

Kerosine (petroleum)	
Registration number (ECHA)	-
Index	649-404-00-4



(GB)

2 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 01-01-2014 Replaces the version of: 01-03-2013 PDF date: 01-01-2014
Trade name: 01 001734 AUTOSOL® Stainless Steel Polish (75 ml Tube)

EINECS, ELINCS	232-366-4
CAS	CAS 8008-20-6
content %	10 - 20
Symbol	Xn
R-phrases	65-66
Classification categories / Indications of danger	Harmful

2-diethylaminoethanol	
Registration number (ECHA)	-
Index	603-048-00-6
EINECS, ELINCS	202-845-2
CAS	CAS 100-37-8
content %	1 -< 5
Symbol	Xn/C
R-phrases	10-20/21/22-34
Classification categories / Indications of danger	Corrosive, Flammable, Harmful

Naphtha (petroleum), hydrotreated light	
Registration number (ECHA)	-
Index	649-328-00-1
EINECS, ELINCS	265-151-9
CAS	CAS 64742-49-0
content %	15 -< 20
Symbol	F/Xn/Xi/N
R-phrases	11-38-51-53-65-67
Classification categories / Indications of danger	Dangerous for the environment, Harmful, Highly flammable, Irritant

For complete wording of the R-phrases / H-phrases (GHS/CLP), refer to point 16.

SECTION 4: First aid measures

4.1 Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.

4.2 Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

4.4 Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting. Consult doctor immediately.

4.5 Special resources necessary for first aid

n.c.

SECTION 5: Firefighting measures

5.1 Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

5.2 Extinguishing media which shall not be used for safety reasons

High volume water jet

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:



GB

3 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 01-01-2014 Replaces the version of: 01-03-2013 PDF date: 01-01-2014
Trade name: 01 001734 AUTOSOL® Stainless Steel Polish (75 ml Tube)

Oxides of carbon
Oxides of nitrogen
Toxic pyrolysis products.

5.4 Special protective equipment for fire-fighters

Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary

5.5 Further information

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

Refer to point 13. and for personal protection refer to point 8.

6.1 Personal precautions

Ensure sufficient supply of air.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.
Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent from entering drainage system.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods for cleaning up

Collect mechanically and dispose of according to point 13.

SECTION 7: Handling and storage

7.1 Handling

Tips for safe handling:

See point 6.1
Ensure good ventilation.
Avoid build up of dust.
Keep away from sources of ignition - Do not smoke.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Wash hands before breaks and at end of work.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.2. Storage

Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.
Store product closed and only in original packing.

Special storage conditions:

See point 10
Store at room temperature.

SECTION 8: Exposure controls/personal protection

8.1 Exposure limit values

GB	Chemical Name	Kerosine (petroleum)	Content %:10 - 20
	WEL-TWA:	500 mg/m ³ , 100 mg/m ³ (AGW)	WEL-STEL: 2(II) (AGW) ---
	BMGV:	---	Other information: ---

GB



GB

4 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 01-01-2014 Replaces the version of: 01-03-2013 PDF date: 01-01-2014
Trade name: 01 001734 AUTOSOL® Stainless Steel Polish (75 ml Tube)

Chemical Name	Naphtha (petroleum), hydrotreated light		Content %:15 - < 20
WEL-TWA: 1200 mg/m3 (> C7 normal and branched chain alkanes) (WEL), 1500 mg/m3 (AGW)	WEL-STEL: 2(II) (AGW)	---	
BMGV: ---	Other information: ---		
Chemical Name	Aluminium oxide		Content %:
WEL-TWA: 10 mg/m3 (total inhal. dust), 4 mg/m3 (resp. dust) (aluminium oxides)	WEL-STEL: ---	---	
BMGV: ---	Other information: ---		
Chemical Name	Ethanol		Content %:
WEL-TWA: 1000 ppm (1920 mg/m3)	WEL-STEL: ---	---	
BMGV: ---	Other information: ---		
Chemical Name	general dust limit		Content %:
WEL-TWA: 10 mg/m3 (inhal. dust), 4 mg/m3 (respir. dust)	WEL-STEL: ---	---	
BMGV: ---	Other information: ---		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Occupational exposure controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

On dust formation:

If the general dust-limit is exceeded, breathing masks with fine-dust filters are necessary (EN 143), code colour white.

Hand protection:

Recommended

With long-term contact:

If applicable

Protective Neopren gloves (EN 374).

Protective nitrile gloves (EN 374)

Protective hand cream recommended.

Eye protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.

Selection made for preparations according to the best available knowledge and information on the ingredients.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.



(GB)

5 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 01-01-2014 Replaces the version of: 01-03-2013 PDF date: 01-01-2014
Trade name: 01 001734 AUTOSOL® Stainless Steel Polish (75 ml Tube)

In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.2 Environmental exposure controls

n.av.

SECTION 9: Physical and chemical properties

9.1 General information

Physical state: Pastelike
Colour: White
Odour: Characteristic

9.2. Important health, safety and environmental information

pH-value undiluted: 8,5
10 % pH-value: 9,0
Boiling point/boiling range (°C): >= 100
Melting point/melting range (°C): n.av.
Flash point (°C): > 100
Flammability (solid, gas): No
Oxidising properties: No
Minimum limit of explosion: n.a.
Maximum limit of explosion: n.a.
Product is not explosive.
Density (g/ml): 1,045
Water solubility: Mixable
Viscosity: 1500 - 2000 mPas (DIN 53211)

SECTION 10: Stability and reactivity

Conditions to avoid

See point 7
Stable when handled and stored correctly.

Materials to avoid

See point 7
No dangerous reactions are known.

Hazardous decomposition products

See point 5.3
No decomposition when used as directed.

SECTION 11: Toxicological information

Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg): n.av.
Inhalation, LC50 rat inhal.(mg/l/4h): n.av.
Skin contact, LD50 rat dermal (mg/kg): See point 15.
Eye contact: n.av.

Delayed and chronic effects

Sensitization: n.c.
Carcinogenicity: n.c.
Mutagenicity: n.c.
Reproductive toxicity: n.c.
Narcosis: n.c.

Further information



(GB)

6 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 01-01-2014 Replaces the version of: 01-03-2013 PDF date: 01-01-2014
Trade name: 01 001734 AUTOSOL® Stainless Steel Polish (75 ml Tube)

Classification according to calculation procedure.

The following may occur:

Irritation of the eyes

With long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

SECTION 12: Ecological information

Persistence and degradability:

Completely biologically degradable *

> 70% DOC (OECD 302B) **

The surfactant(s) contained in this mixture complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Behaviour in sewage plants:

According to the recipe, contains no AOX.

Aquatic toxicity:

See point 2.

Ecological toxicity:

n.av.

Mobility:

n.av.

Accumulation:

n.av.

* Naphtha (petroleum), hydrotreated light

** 2-diethylaminoethanol

Results of PBT assessment

n.av.

Other adverse effects:

n.av.

SECTION 13: Disposal considerations

13.1. for the material / preparation / residue

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

07 06 99 wastes not otherwise specified

12 01 14 machining sludges containing dangerous substances

Recommendation:

Pay attention to local and national official regulations

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

UN-Number:

n.a.

Road/Rail-transport (ADR/RID)

Class/packing group:

n.a.

Classification code:

n.a.

LQ:

n.a.



(GB)

7 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision: 01-01-2014 Replaces the version of: 01-03-2013 PDF date: 01-01-2014
Trade name: 01 001734 AUTOSOL® Stainless Steel Polish (75 ml Tube)

Tunnel restriction code:

Transport by sea

IMDG-code: n.a. (class/packing group)
Marine Pollutant: n.a.

Transport by air

IATA: n.a. (class/secondary danger/packing group)

Additional information:

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

Classification according to Dangerous Product Regulations incl. EC Directives (67/548/EEC and 1999/45/EC)



Symbols: Xi

Indications of danger:

Irritant

R-phrases:

38 Irritating to skin.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

S-phrases:

2 Keep out of the reach of children.

24/25 Avoid contact with skin and eyes.

35 This material and its container must be disposed of in a safe way.

46 If swallowed, seek medical advice immediately and show this container or label.

Additions: n.a.

Observe restrictions: Yes

Observe youth employment law (German regulation).

Regulation (EC) No 1907/2006, Annex XVII.

SECTION 16: Other information

These details refer to the product as it is delivered.

Revised points: 1 - 16 (REACH)

The following phrases represent the prescribed R-phrases / H-phrases (GHS/CLP) for the ingredients (designated in point 3).

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

10 Flammable.

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

34 Causes burns.

11 Highly flammable.

38 Irritating to skin.

51 Toxic to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked

WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40

AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)

VbF = Regulations for flammable liquids (Austria)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water



GB

8 / 8

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision: 01-01-2014 Replaces the version of: 01-03-2013 PDF date: 01-01-2014

Trade name: 01 001734 AUTOSOL® Stainless Steel Polish (75 ml Tube)

VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.