

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Brakleen® Brake Parts Cleaner - 411 g

Other means of identification

Product Code Item# 1752253

Recommended use Brake parts cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Canada Co.

Address 83 Galaxy Blvd
Unit 35 - 37

Toronto, ON M9W 5X6

Canada

Telephone

**General Information** 416-847-7750

24-Hour Emergency

800-424-9300 (Canada)

(CHEMTREC)

Website www.crc-canada.ca

E-mail Support.CA@crcindustries.com

#### 2. Hazard identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Compressed gas

Health hazardsSkin corrosion/irritationCategory 2

Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1
Hazardous to the aquatic environment, acute Category 2

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause

drowsiness or dizziness.

Precautionary statement

**Prevention** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection. Wear protective gloves.

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON Response

SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated

place. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards Static accumulating flammable liquid can become electrostatically charged even in bonded and

grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
naphtha (petroleum), hydrotreated light		64742-49-0	30 - 60
heptane, branched, cyclic and linear		426260-76-6	10 - 30
isopropyl alcohol		67-63-0	5 - 10
n-heptane		142-82-5	5 - 10
solvent naphtha (petroleum), light aliph.		64742-89-8	5 - 10
carbon dioxide		124-38-9	1 - 5

The exact percentage (concentration) of composition has been withheld as a trade secret.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison Inhalation

center or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache, Nausea, vomiting, Severe eye irritation, Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

be formed.

Fire fighting equipment/instructions
Specific methods

risk. Containers should be cooled with water to prevent vapor pressure build up.

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

#### 7. Handling and storage

Precautions for safe handling

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

**US. ACGIH Threshold Limit Values** 

Components	Туре	Value
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm

Canada. Alberta OELs	(Occupational Health & Safety Cod	le, Schedule 1, Table 2)

Components	Туре	Value	
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
isopropyl alcohol (CAS 67-63-0)	STEL	984 mg/m3	
		400 ppm	
	TWA	492 mg/m3	
		200 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m3	
,		400 ppm	
n-heptane (CAS 142-82-5)	STEL	2050 mg/m3	
		500 ppm	
	TWA	1640 mg/m3	
		400 ppm	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	1590 mg/m3	
,		400 nnm	

400 ppm

# Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	
carbon dioxide (CAS 124-38-9)	STEL	15000 ppm	
	TWA	5000 ppm	
isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
n-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	

# Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	туре	value	
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
n-heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	

# Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm	

		Туре	Va	lue
		TWA	20	0 ppm
n-heptane (CAS 142-82-5)	)	STEL	50	0 ppm
		TWA	40	0 ppm
Canada. Quebec OELs. ( Components	Ministry of Labor	- Regulation respecting Type		nealth and safety) lue
carbon dioxide (CAS 124-38-9)		STEL	54	000 mg/m3
			30	000 ppm
		TWA	90	00 mg/m3
			50	00 ppm
isopropyl alcohol (CAS 67-63-0)		STEL	12	30 mg/m3
			50	0 ррт
		TWA	98	3 mg/m3
			40	0 ррт
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		TWA	15	90 mg/m3
04742-49-0)			40	0 ppm
n-heptane (CAS 142-82-5)	)	STEL		50 mg/m3
······································	,			0 ppm
		TWA		40 mg/m3
				0 ppm
solvent naphtha (petroleum), light aliph.		TWA		90 mg/m3
(CAS 64742-89-8)			40	0 ppm
(CAS 64742-89-8)  Canada. Saskatchewan (	DELs (Occupation	-	egulations, 1996	6, Table 21)
(CAS 64742-89-8)	DELs (Occupation	al Health and Safety Ro Type	egulations, 1996	• •
(CAS 64742-89-8)  Canada. Saskatchewan (Components  carbon dioxide (CAS	OELs (Occupation	-	egulations, 1996 Va	6, Table 21)
(CAS 64742-89-8)  Canada. Saskatchewan ( Components  carbon dioxide (CAS 124-38-9)	DELs (Occupation	Type 15 minute 8 hour	egulations, 1996 Va 30	5, Table 21) lue
CAS 64742-89-8)  Canada. Saskatchewan ( Components  carbon dioxide (CAS 124-38-9)  isopropyl alcohol (CAS	OELs (Occupation	Type 15 minute 8 hour 15 minute	egulations, 1996 Va 30 50 40	5, Table 21) llue 000 ppm 00 ppm 0 ppm
Canada. Saskatchewan (Components  carbon dioxide (CAS 124-38-9)  isopropyl alcohol (CAS 67-63-0)	OELs (Occupation	Type 15 minute 8 hour 15 minute 8 hour	egulations, 1996 Va 30 50 40	5, Table 21) Ilue 000 ppm 00 ppm 0 ppm 0 ppm
Canada. Saskatchewan (Components  carbon dioxide (CAS 124-38-9)  isopropyl alcohol (CAS 67-63-0)  naphtha (petroleum), hydrotreated light (CAS	OELs (Occupation	Type 15 minute 8 hour 15 minute	egulations, 1996 Va 30 50 40	5, Table 21) llue 000 ppm 00 ppm 0 ppm
CAS 64742-89-8)  Canada. Saskatchewan ( Components  carbon dioxide (CAS 124-38-9)  isopropyl alcohol (CAS	DELs (Occupation	Type 15 minute 8 hour 15 minute 8 hour	990 Va 30 50 40 50 50	5, Table 21) Ilue 000 ppm 00 ppm 0 ppm 0 ppm
Canada. Saskatchewan (Components) carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		Type 15 minute 8 hour 15 minute 8 hour 15 minute	egulations, 1996 Va 30 50 40 20 50	5, Table 21) llue 000 ppm 00 ppm 0 ppm 0 ppm 0 ppm
Canada. Saskatchewan (Components  carbon dioxide (CAS 124-38-9)  isopropyl alcohol (CAS 67-63-0)  naphtha (petroleum), hydrotreated light (CAS		Type 15 minute 8 hour 15 minute 8 hour 15 minute 8 hour 15 minute	egulations, 1996 Va 30 50 40 50 40 50	5, Table 21) Ilue 000 ppm 00 ppm 0 ppm 0 ppm 0 ppm 0 ppm
Canada. Saskatchewan (Components) carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha (petroleum), light aliph.		Type  15 minute  8 hour  15 minute  8 hour  15 minute  8 hour  15 minute	egulations, 1996 Va 30 50 40 50 40 50 40	5, Table 21) Ilue  000 ppm  0 ppm  0 ppm  0 ppm  0 ppm  0 ppm  0 ppm
Canada. Saskatchewan (Components) carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha		Type  15 minute  8 hour  15 minute  8 hour  15 minute  8 hour  15 minute  8 hour  15 minute  8 hour	20 50 40 50 50 50 50 50 50 50 50 50 50 50 50 50	5, Table 21) Ilue  000 ppm  0 ppm
Canada. Saskatchewan (Components) carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		Type 15 minute 8 hour 15 minute	20 50 40 50 50 50 50 50 50 50 50 50 50 50 50 50	5, Table 21) Ilue  000 ppm  0 ppm
Canada. Saskatchewan (Components) carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) ogical limit values ACGIH Biological Expos	)	Type 15 minute 8 hour 15 minute	20 50 40 50 50 50 50 50 50 50 50 50 50 50 50 50	5, Table 21) Ilue  000 ppm  0 ppm
Canada. Saskatchewan (Components) carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) ogical limit values	)	Type 15 minute 8 hour 15 minute	20 50 40 50 50 50 50 50 50 50 50 50 50 50 50 50	5, Table 21) Ilue  000 ppm  0 ppm

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety

shower

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Laminate film.Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Aerosol.
Color Colorless.
Odor Pleasant.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -131.1 °F (-90.6 °C) estimated Initial boiling point and boiling 180.5 °F (82.5 °C) estimated

range

Flash point 17.6 °F (-8.0 °C) estimated

**Evaporation rate** Fast.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

1.1 % estimated

(%)

Flammability limit - upper

12 % estimated

(%)

Vapor pressure 3078.9 hPa estimated

Vapor density > 1 (air = 1)

Relative density 0.74 estimated

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 539.6 °F (282 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

#### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous No dangerous reaction known under conditions of normal use.

reactions

Conditions to avoid Heat. Contact with incompatible materials.

Incompatible materials

Hazardous decomposition

products

Acids. Strong oxidizing agents. Chlorine. Isocyanates.

Carbon oxides, Hydrocarbon fumes and smoke, Aldehydes, Formaldehyde,

## 11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Causes skin irritation. Skin contact

Eye contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness.

Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

May be fatal if swallowed and enters airways. **Acute toxicity** 

Components **Species Test Results** 

heptane, branched, cyclic and linear (CAS 426260-76-6)

**Acute** 

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 60 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

isopropyl alcohol (CAS 67-63-0)

**Acute** 

Dermal

LD50 Rabbit 5030 - 7900 mg/kg

Inhalation

LC50 Rat 16000 ppm, 4 hours

Oral

LD50 Rat 4700 - 5800 mg/kg

Causes skin irritation. Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Not a respiratory sensitizer. Respiratory sensitization

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

**ACGIH Carcinogens** 

isopropyl alcohol (CAS 67-63-0) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

isopropyl alcohol (CAS 67-63-0) Not classifiable as a human carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -Not classified.

repeated exposure

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

#### 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Persistence and degradability 
No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

isopropyl alcohol 0.05 n-heptane 4.66

Bioconcentration factor (BCF)

naphtha (petroleum), hydrotreated light 10 - 25000

Mobility in soil No data available.

Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation

potential.

# 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

#### 14. Transport information

**TDG** 

UN number UN1950

UN proper shipping name AEROSOLS, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1950

UN proper shipping name A

Transport hazard class(es)

Aerosols, flammable, Limited Quantity

Class 2.1 Subsidiary risk -

Packing group Not applicable.

ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.


**Environmental hazards** 

**Marine pollutant** Yes, but exempt from the regulations.


EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

#### IATA



#### IMDG; TDG



## 15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

#### **Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

**Greenhouse Gases** 

carbon dioxide (CAS 124-38-9)

**Precursor Control Regulations** 

Not regulated.

# International regulations

#### Stockholm Convention

Not applicable.

#### **Rotterdam Convention**

Not applicable.

#### **Kyoto protocol**

carbon dioxide (CAS 124-38-9) Listed.

#### **Montreal Protocol**

Not applicable.

#### **Basel Convention**

Not applicable.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Country(s) or region Inventory name On inventory (yes/no)\*

KoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryNo

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information

**Issue date** 07-02-2020

Version # 01

Further information CRC # 937A/1002953

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Canada Co..

Material name: Brakleen® Brake Parts Cleaner - 411 g
Item# 1752253 Version #: 01 Issue date: 07-02-2020

Yes