SAFETY DATA SHEET

Deepfreeze Refrigerants Inc. 2695 Slough Street Mississauga Ontario Canada

Duracool 12a 134a Replacement Refrigerant

SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer...... Deepfreeze Refrigerants Inc.

2695 Slough Street Mississauga L4T 1G2 905 671 4222

24 hour emergency telephone number..... In Canada & The United States: Call CHEMTREC (800) 424-9300.

Recommended Use...... Environmental friendly refrigerant.

Chemical Family...... Hydrocarbon blend.

SECTION 02: HAZARDS IDENTIFICATION



Label Elements: Signal Word...... DANGER. Hazard Classification:

Physical Hazards...... Flammable Aerosols - Category 1. Gases Under Pressure - Liquefied Gas .

Health Hazards...... Not Classified. Environmental Hazards...... Not Classified.

Hazard Statement...... Extremely flammable aerosol. Pressurized container: may burst if heated. Contains gas

under pressure; may explode if heated.

Precautionary Statements:

Prevention....... Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Response......None

well ventilated place.

regulations.

Hazard(s) not otherwise classified (HNOC) Avoid inhalation of the product. Use only as directed.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS			
HAZARDOUS INGREDIENTS	CAS#	WT. %	
Isobutane	75-28-5	10-60	
Propane	74-98-6	10-60	

SECTION 04: FIRST AID MEASURES

Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain
Skin Contact	immediate medical assistance. Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20
Eye Contact	minutes. Consult a poison control centre or physician immediately. Check for and remove contact lenses. Immediately flush eyes with water for a minimum of
Ingestion	15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Ingestion is unlikely to occur. If swallowed do not induce vomiting because of risk of
Most important symptoms/effects, acute and delayed	aspiration into the lungs. If aspiration is suspected obtain immediate medical attention. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.

SECTION 04: FIRST AID MEASURES

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE FIGHTING MEASURES

General Fire Hazards...... Extremely flammable aerosol.

Suitable Extinguishing Media...... Dry chemical powder. Carbon dioxide. Foam, water spray or fog. Unsuitable Extinguishing Media................ Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical In case of fire, the following can be released: Carbon Oxides (CO, CO2), Other unidentified

Organic Compounds.

Precautions for Firefighters

Special Protective Equipment and Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use

unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective No action shall be taken involving any personal risk or without suitable training. Evacuate Equipment and Emergency Procedures

surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate

personal protective equipment (see Section 08).

and Cleaning Up

Methods and Materials for Containment .. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.)

away from spilled material.

Environmental Precautions.................. Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent

environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling...... Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is

missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged

exposure. Use in well-ventilated areas.

Incompatibilities

Conditions for Safe Storage including any Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA AC	CGIH TLV STEL	OSHA PEL	A PEL STEL	NIOSH REL
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available
Propane	Not available	Not available	1,000 ppm	Not available	Not available
Appropriate Engineering Controls					

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Form...... Aerosol.

Odor...... Characteristic .

Odor Threshold (ppm)...... N/A.

SAFETY DATA SHEET

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Aerosol Vapour Pressure (psig, 21°C)....... 80-95. Vapour Density (Air=1)...... > 1.

Flashback......N/A. Evaporation Rate (n-Butyl Acetate = 1)..... No data. VOC Content...... > 95 wt.%.

Viscosity...... N/A.

SECTION 10: STABILITY AND REACTIVITY

Reactivity Product not reactive under normal conditions of use.

Chemical Stability...... Material is stable under normal conditions.

Possibility of Hazardous Reactions...... Will not occur.

Conditions to Avoid....... Avoid sources of heat and flame, and electrostatic charge.

Incompatible Materials...... Keep away from heat. Strong oxidizing agents.

Hazardous Decomposition Products...... See Section 05.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS LC50 LD50

658 mg/L (Rat - 4hrs) Isobutane Not available Propane 658 mg/L (Rat - 4hrs) Not available

Information on Likely Routes of Exposure:

Routes of entry - Inhalation...... Prolonged inhalation may be harmful.

Routes of entry - Skin Absorption...... No.

Symptoms Related to the Physical, Chemical and Toxicological Characteristics

nausea. Prolong inhalation may be harmful.

Skin Corrosion/Irritation...... N/A. Serious Eye Damage/Eye Irritation...... N/A. Respiratory or Skin Sensitization...... N/A.

mutagenic.

STOT - Single Exposure...... Not classified. STOT - Repeated Exposure...... Not classified.

exposure. Symptoms of overexposure are dizziness, headache, tiredness, nausea,

unconsciousness.

SECTION 12: ECOLOGICAL INFORMATION

not be released into the environment.

Persistence and degradability The product itself has not been tested. Bioaccumulation Potential...... The product itself has not been tested.

Other Adverse Effects...... None Known.

SAFETY DATA SHEET

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods....... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.

SECTION 14: TRANSPORT INFORMATION

TDG (C	anada- Road)	UN1075, AEROSOLS, Class 2.1.
IMDG (I	International- Marine)	UN1075, AEROSOLS, Class 2.1.
IATA (Ìr	nternational- Air)	UN1075, AEROSOLS, Class 2.1, LTD QTY.
DOT (Ù	IS-Road)	UN1075, AEROSOLS, Class 2.1, LTD QTY, Consumer Commodity ORM-D.

SECTION 15: REGULATORY INFORMATION

US Regulations

TSCA Inventory Status...... All components are listed on TSCA.

OSHA.........this product is considered hazardous under the Federal OSHA hazard communication

standard.

California Proposition 65...... This product does not contain any chemical(s) known to the state of California to cause

cancer or reproductivity toxicity.

SECTION 16: OTHER INFORMATION

warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act

1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

Prepared by Regulatory Affairs Latest Revision JAŇ 03 /2021