1. Identification

page 1 of 7

Product identifier used on the label

Eaton Multi-Purpose Grease Lithium Complex Thickener System

Recommended use of the chemical and restriction on use

Recommended use*: lubricants

* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company: BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: preparation

Synonyms: Mechanical lubricating grease

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Eye Dam./Irrit. 2A Serious eye damage/eye irritation

Aquatic Acute 3 Hazardous to the aquatic environment - acute

Aquatic Chronic 3 Hazardous to the aquatic environment - chronic

Label elements

Pictogram:

Signal Word: Warning

Hazard Statement:

H319 Causes serious eye irritation.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280 Wear eye/face protection.

P273 Avoid release to the environment.

P264 Wash with plenty of water and soap thoroughly after handling.



page 2 of 7

Eaton® Multi-Purpose Grease Lithium Complex Thickener System

Safety Data Sheet

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337 + P311 If eye irritation pe

If eye irritation persists: Call a POISON CENTER or doctor/physician.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point,

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Emergency overview

MARNING

Irritating to eyes, May cause skin irritation. Avoid contact with the skin, eyes and clothing. Wear NIOSH-certified chemical goggles.

3. Composition/Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Weight %	Chemical name
64741-88-4	>= 50.0 - 75.0%	Distillates (petroleum), solvent-refined heavy paraffinic
68649-42-3	>= 1.0 - < 5.0%	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts
1317-65-3	>= 1.0 - < 3.0%	Limestone
110-25-8	< 1.0%	N-oleoyl-sarcoside .

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Weight %	Chemical name
64741-88-4	>= 50.0 - 75.0%	Distillates (petroleum), solvent-refined heavy paraffinic
1317-65 - 3	>= 1.0 - < 3.0%	Limestone
68649-42-3	>= 10 - < 3.0%	Phosphorodithioic acid. O O-di-C1-14-alkyl esters, zinc salts

4. First-Aid Measures

Description of first aid measures

General advice:

Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

lf on skin

Remove contaminated clothing. Rinse skin immediately with plenty of water for 15 - 20 minutes, If irritation develops, seek medical attention.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed

Rinse mouth immediately with water. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting due to aspiration hazard. Seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further important symptoms and effects are so far not known. Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Eaton® Multi-Purpose Grease Lithium Complex Thickener System

Safety Data Sheet

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: water spray, dry powder, foam Unsuitable extinguishing media for safety reasons: water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting; harmful vapours

Evolution of furnes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product. Clean up spills immediately.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Keep people away and stay on the upwind side. Breathing protection required.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling

No special measures necessary provided product is used correctly.

Protection against fire and explosion:

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

OSHA PEL

PEL 5 mg/m3 Respirable fraction; PEL 15 mg/m3 Total dust; TWA value 15 mg/m3 Total dust;

TWA value 5 mg/m3 Respirable fraction

Distillates (petroleum), OSHA PEL

solvent-refined heavy

Limestone

ACGIH TLV paraffinic

PEL 500 ppm 2,000 mg/m3; PEL 5 mg/m3 Mist; TWA value 5 mg/m3 Mist

Included in the regulation, but with no data values - See the regulation for further details;

Exposure by all routes should be carefully controlled to levels as low as possible.

TWA value 5 mg/m3 Inhalable fraction

Advice on system design:

Ensure adequate ventilation

Eaton® Multi-Purpose Grease Lithium Complex Thickener System

Safety Data Sheet

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Tightly fitting safety goggles (chemical goggles) and face shield.

Body protection:

Suitable materials

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:

Odour:

almost odourless

Odour threshold:

No applicable information available.

Colour: pH value: blue insoluble

Melting point: Boiling point:

No applicable information available. No applicable information available. No applicable information available.

Flash point:

243.00 °C (ASTM D92)

Flammability:

Sublimation point:

not flammable

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

not applicable

Autoignition: Vapour pressure: No applicable information available. No applicable information available.

Density:

0,889 g/cm3 (15.6 °C) 0.886 g/cm3 (20 °C)

Relative density:

No applicable information available. No applicable information available.

Vapour density: Partitioning coefficient

n-octanol/water (log Pow): Study scientifically not justified.

Self-ignition temperature: not self-igniting

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Viscosity, dynamic:

not determined

Viscosity, kinematic: Solubility in water:

No applicable information available.

insoluble

Solubility (quantitative): Solubility (qualitative):

No applicable information available. No applicable information available.

Evaporation rate:

The product is a non-volatile solid.

Other Information:

If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No applicable information available.

Corrosion to metals: No corrosive effect on metal.

Oxidizing properties: Not fire-propagating

Reactions with water/air:

Reaction with Flammable gases: no Toxic gases: no Corrosive gases: no Smoke or fog: no Peroxides: Reaction with air Flammable gases: no Toxic gases: no Corrosive gases: no

Smoke or fog: Peroxides:

no no

Eaton® Multi-Purpose Grease Lithium Complex Thickener System Safety Data Sheet

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Peroxides: 0.000 % The product does not contain peroxides.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions. The product is chemically stable.

Conditions to avoid

No special precautions other than good housekeeping of chemicals.

Incompatible materials

Strong oxidizing agents, strong bases, strong acids

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated. Nitrogen oxides, sulfur oxides, carbon monoxide: The substances/groups of substances mentioned can be released in case of fire.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

11. Toxilogical Information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Primary routes of entry

Dermal contact

Eyes

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion.

Oral

Type of value: LD50

Species: rat

Value: 2,000 - 5,000 mg/kg

Analogous: Assessment derived from products with similar chemical character.

Inhalation

No applicable information available.

Derma

No applicable information available.

Irritation/corrosion

Assessment of irritating effects: May cause slight irritation to the skin. Irritating to eyes.

<u>Sensitization</u>

Assessment of sensitization: Based on the ingredients, there is no suspicion of a skin-sensitizing potential.

Guinea pig maximization test

Species: guinea pig

Result: Non-sensitizing.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: None known

<u>Genetic toxicity</u>

Assessment of mutagenicity: Based on the ingredients, there is no suspicion of a carcinogenic effect.

Carcinogenicity

Assessment of carcinogenicity: Based on the ingredients there is no suspicion of a carcinogenic effect in humans.

Reproductive toxicity

Assessment of reproduction toxicity: Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

page 6 of 7

Eaton® Multi-Purpose Grease Lithium Complex Thickener System

Safety Data Sheet

Other Information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further important symptoms and effects are so far not known.

Medical conditions aggravated by overexposure

Individuals with pre-existing diseases of the respiratory system, skin or eyes may have increased susceptibility to excessive exposures.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Assessment biodegradation and elimination (H2O) Not readily biodegradable (by OECD criteria).

Bioaccumulative potential

Assessment bioaccumulation potential

No data available.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Other ecotoxicological advice: The product has not been tested. The statement has been derived from the properties of the individual components.

13. Disposal Considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Recommend crushing, puncturing or other means to prevent unauthorized use of used containers. Dispose of in accordance with national, state and local regulations.

14. Transportation Information

Land transport

USDOT Not classified as a dangerous good under transport regulations

Sea transport

IMDG Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

TSCA, US Chemical

released / listed

EPCRA 311/312 (Hazard categories): Acute

EPCRA 313:

CAS Number

Chemical name

68649-42-3

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts

State regulations

CAS Number State RTK Chemical name 1317-65-3 Limestone 64741-88-4 Distillates (petroleum), solvent-refined heavy paraffinic 68649-42-3 Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts PΑ 1317-65-3 64741-88-4 Distillates (petroleum), solvent-refined heavy paraffinic

NFPA Hazard codes:

Health: 2 Fire: 1 Reactivity: 0

Special:

HMIS III rating

Health: 2

Flammability: 1

Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2015/10/28

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY, BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

BACKED BY

Roadranger

SUPPORT

For spec'ing or service assistance, call 1-800-826-HELP (4357) or visit www.eaton.com/roadranger. In Mexico, call 001-800-826-4357.

Roadranger: Eaton and trusted partners providing the best products and services in the industry, ensuring more time on the road.

Eaton Vehicle Group 13100 E. Michigan Ave. Kalamazoo, MI 49053 USA 800-826-HELP (4357) www.eaton.com/roadranger

© 2016 Eaton All Rights Reserved, Printed in USA. TCSL0029 0216

Note: Features and specifications listed in this document are subject to change without notice and represent the maximum capa-bilities of the software and products with all options installed. Although every attempt has been made to ensure the accuracy of information contained within, Eaton makes no representation about the completeness, correctness or accuracy and assumes no responsibility for any errors or omissions. Features and functionality may vary depending on selected options.

Eaton, Fuller, Roadranger, Solo, UltraShift and Fuller Advantage are registered trademarks of Eaton. All trademarks, logos and copyrights are those of their respective owner

