

Solvent UC500S clear

SECTION 1. IDENTIFICATION

Product Identifier Solvent UC500S clear
Other Identification solvent
Product Family organic solvent
Manufacturer Glass-Shield, 111 Bombardier, Chateauguay, Quebec, J6J 4Z2, H&S Department, 1-800-361-6652
Emergency Phone No. CANUTEC, 1-613-996-6666, 24 hours
SDS No. 0061
Date of Preparation avril 09, 2015

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquid - Category 2; Acute toxicity (Inhalation) - Category 2; Skin corrosion/irritation - Category 2; Serious eye damage/eye irritation - Category 1; Aspiration hazard - Category 1; Aquatic hazard (Acute) - Category 2

GHS Label Elements



Signal Word:

Danger

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage.

Toxic to aquatic life.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTRE/doctor

Wear respiratory protection (NIOSH approved self-contained breathing apparatus (SCBA) or supplied air respirator).

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Xylene (mixed isomers)	1330-20-7	40-70%	
Methyl ethyl ketone	78-93-3	10-30%	

Product Identifier: Solvent UC500S clear

Date of Preparation: avril 09, 2015

Ethyl acetate	141-78-6	7-13%	
Ethyl Benzene	100-41-4	7-13%	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Move to fresh air. Keep at rest in a position comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Call a Poison Centre or doctor if you feel unwell or are concerned.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Immediately call a Poison Centre or doctor.

First-aid Comments

Some of the first-aid procedures recommended here require advanced first-aid training.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

Unsuitable Extinguishing Media

Water is not effective for extinguishing a fire. It may not cool product below its flash point.

Specific Hazards Arising from the Chemical

Reactive flammable. Heating increases the release of toxic vapour.

In a fire, the following hazardous materials may be generated: flammable chemicals; irritating chemicals; toxic chemicals; very toxic carbon monoxide, carbon dioxide.

Special Protective Equipment and Precautions for Fire-fighters

Use extreme caution. Fight fire from a safe distance or a protected location.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Eliminate all ignition sources. Use grounded, explosion-proof equipment.

Environmental Precautions

It is good practice to prevent releases into the environment. Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

Methods and Materials for Containment and Cleaning Up

Stop or reduce leak if safe to do so. Contain and soak up spill with absorbent that does not react with spilled product. Do not use absorbents. Contain spill using noncombustible material such as vermiculite, earth or sand. Collect using shovel/scoop or approved HEPA vacuum and place in a suitable container for disposal.

Other Information

Report spills to local health, safety and environmental authorities, as required.

SECTION 7. HANDLING AND STORAGE

Product Identifier: Solvent UC500S clear

Date of Preparation: avril 09, 2015

Page 02 of 06

Precautions for Safe Handling

Prevent all skin contact. Obtain special instructions before use. Only use where there is adequate ventilation. Avoid release to the environment. Immediately report leaks, spills or failures of the safety equipment (e.g. ventilation system).

Conditions for Safe Storage

Store in an area that is: cool, temperature-controlled, dry, well-ventilated, clear of combustible and flammable materials (e.g. old rags, cardboard). Restrict access to authorized personnel only.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Ethyl acetate	100 ppm A4	150 ppm A4	100 ppm			
Methyl ethyl ketone	20 ppm	125 ppm	100 ppm			
Xylene (mixed isomers)	100 ppm A4	150 ppm A4	100 ppm			
Ethyl Benzene	20 ppm	125 ppm	100 ppm			

Appropriate Engineering Controls

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Control static electricity discharges which includes bonding of equipment to ground. Provide eyewash and safety shower if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.
Nitrile rubber.

Respiratory Protection

Wear a NIOSH approved air-purifying respirator with an organic vapour cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Colourless. Particle Size: Not applicable
Odour	Ethereal
Odour Threshold	Not available
pH	Not applicable
Melting Point/Freezing Point	Not available (melting); -87 °C (freezing)
Initial Boiling Point/Range	80 °C
Flash Point	-3 °C
Evaporation Rate	1
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	10% (upper); 2% (lower)
Vapour Pressure	> 95 kPa
Vapour Density (air = 1)	>= 2
Relative Density (water = 1)	1
Solubility	Soluble in water; Soluble in all proportions in common organic solvents.
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	516 °C

Product Identifier: Solvent UC500S clear

Date of Preparation: avril 09, 2015

Decomposition Temperature	Not available
Viscosity	Not available (kinematic); Not available (dynamic)
Other Information	
Physical State	Liquid
Molecular Formula	Not available
Molecular Weight	Not available
Bulk Density	Not available
Surface Tension	Not available
Critical Temperature	Not available
Electrical Conductivity	Not available
Vapour Pressure at 50 deg C	Not available
Saturated Vapour Concentration	Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

May cause or intensify fire.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

Reacts in the presence of acidic conditions (low pH).

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources. Acidic conditions (low pH). Incompatible materials. Temperatures above 40 °C

Incompatible Materials

Organic acids (e.g. acetic acid).

Not corrosive to metals.

Hazardous Decomposition Products

Very toxic carbon monoxide, carbon dioxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Ethyl acetate	6700 ppm (rat) (4-hour exposure)	3523 mg/kg (rat)	Not available
Methyl ethyl ketone	4000 ppm (rat) (4-hour exposure)	3500 mg/kg (rat)	15380 mg/kg (rabbit)
Xylene (mixed isomers)	6700 ppm (rat) (4-hour exposure)	3523 mg/kg (rat)	Not available
Ethyl Benzene	4000 ppm (rat) (4-hour exposure)	3500 mg/kg (rat)	15380 mg/kg (rabbit)

Skin Corrosion/Irritation

Human experience shows moderate or severe irritation.

Serious Eye Damage/Irritation

Human experience and animal tests show mild irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May be harmful based on animal tests.

Product Identifier: Solvent UC500S clear

Date of Preparation: avril 09, 2015

Skin Absorption

Harmful based on human experience and animal tests.

Ingestion

Based on human experience and animal tests.

Aspiration Hazard

Symptoms may include coughing, choking, shortness of breath, difficult or rapid breathing, and wheezing.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Based on studies in people and animals.

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Ethyl acetate	Group 3			
Xylene (mixed isomers)	Group 3			

Reproductive Toxicity**Development of Offspring**

No information was located.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

(Xylene (mixed isomers)). (Ethyl Benzene). (Light aromatic solvent naphtha). (n-Butyl acetate)

Persistence and Degradability

Does not degrade rapidly based on quantitative tests.

Bioaccumulative Potential

This product and its degradation products are not known to bioaccumulate.

Mobility in Soil

If released into the environment, this product can move rapidly through the soil.

Other Adverse Effects

This product contains volatile organic compounds.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal Methods**

Recycle and reuse product, if possible. Contact local environmental authorities for approved disposal or recycling methods in your jurisdiction. Dispose of or recycle empty containers through an approved waste management facility.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
US DOT	1263	UC 500 S SOLVENT clear	3	II

Special Precautions for User Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Product Identifier: Solvent UC500S clear

Date of Preparation: avril 09, 2015

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

WHMIS Classification



Class B2



Class D2B

B2 - Flammable Liquid; D2B - Toxic

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Listed on the DSL.

CEPA - National Pollutant Release Inventory (NPRI)

Part 1A.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

SECTION 16. OTHER INFORMATION

Revision Indicators	The following MSDS content was changed on avril 09, 2015: Section 8 - Exposure Controls/Personal Protection; Exposure Guidelines.
Key to Abbreviations	ACGIH® = American Conference of Governmental Industrial Hygienists AIHA = American Industrial Hygiene Association HSDB® = Hazardous Substances Data Bank IARC = International Agency for Research on Cancer NFPA = National Fire Prevention Association NIOSH = National Institute for Occupational Safety and Health NTP = National Toxicology Program OSHA = US Occupational Safety and Health Administration RTECS® = Registry of Toxic Effects of Chemical Substances

Product Identifier: Solvent UC500S clear

Date of Preparation: avril 09, 2015

Page 06 of 06