Canadian Krown Dealers Inc. 35 Magnum Dr. Schomberg, Ontario, L0G 1T0 Canada (905)939-8750 / 1(800)267-5744

CODE: KR-093400

PRODUCT: Krown KE93 Brake and Parts Cleaner - 390 g

SECTION 01: IDENTIFICATION

Product Item Numbers...... KR-093400

Product Identity...... Krown KE93 Brake and Parts Cleaner - 390 g

Manufacturer.... Empack Spraytech Inc. 98 Walker Drive

Brampton Ontario Canada L6T 4H6 905-792-6571

24 hour emergency telephone number..... In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800)

424-9300.

SECTION 02: HAZARD IDENTIFICATION



Label Elements: Signal Word..... DANGER. Hazard Classification: Flammable Aerosols - Category 1. Gases Under Pressure - Liquefied Gas . Physical Hazards..... Health Hazards..... Skin Irritation - Category 2. Špécific Target Organ Toxicity, Single Exposure - Category 3. Aspiration Hazard - Category 1. Environmental Hazards..... Not Classified. Hazard Statement..... H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated (1). H280:Contains gas under pressure; may explode if heated (L). H315:Causes skin irritation. H336:May cause drowsiness or dizziness. H304:May be fatal if swallowed and enters airways. Precautionary Statements:

international regulations.

Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS					
HAZARDOUS INGREDIENTS	CAS#	WT. %			
Heptane (includng isomers)	64742-49-0	80-100			
Carbon dioxide	124-38-9	1-5			

CODE: KR-093400

PRODUCT: Krown KE93 Brake and Parts Cleaner - 390 g

SECTION 04: FIRST-AID MEASURES

If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain Inhalation..... immediate medical assistance. Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately. Skin Contact..... Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the Eye Contact..... upper and lower eyelids. Get medical attention if irritation persists. If swallowed do not induce vomiting because of risk of aspiration into the lungs. If Ingestion..... aspiration is suspected obtain immediate medical attention. Do not attempt to give anything by mouth to an unconscious person. If victim is alert and not convulsing, rinse mouth out and give 1/2 to 1 glass of water to dilute material. DO NOT induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomitus, rinse mouth and administer more water. Obtain medical attention IMMEDIATEL' Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may Most important symptoms/effects, acute ... and delayed cause headache, fatigue, dizziness and nausea. May cause redness and pain. Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be Indication of immediate medical attention and special treatment needed delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog. Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire. Specific Hazards Arising from the Chemical Contents under pressure. Pressurized container may explode when exposed to heat or flame Special Protective Equipment and Firefighters must use standard protective equipment including flame retardant coat, helmet Precautions for Firefighters with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. General Fire Hazards..... Extremely flammable aerosol.

SECTION 06: ACCIDENTAL RELEASE MEASURES

No action shall be taken involving any personal risk or without suitable training. Evacuate Personal Precautions, Protective **Equipment and Emergency Procedures** surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate

ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08). Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand,

Methods and Materials for Containment .. and Cleaning Up

Conditions for Safe Storage including any

Incompatibilities

earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Environmental Precautions.....

Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent

environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling..... Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid

contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from

incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	CGIH TLV STEL	PEL OS	SHA PEL STEL	NIOSH REL
Heptane (including isomers)	1,600 mg/m3 (RCP-TWA)	Not available	Not available	Not available	Not available
Carbon dioxide	5000 ppm	30000 ppm	9000 mg/m3	Not available	STEL: 30000ppm; TWA: 5000ppm



PRODUCT: Krown KE93 Brake and Parts Cleaner - 390 g

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Local exhaust ventilation required to maintain the point of use below the Threshold Limit Appropriate Engineering Controls..... Value if unprotected personnel are involved. Ensure that eyewash stations and safety

showers are available.

Individual Protection Measures:

Eye/Face Protection.....

Do not get in eyes. Wear safety glasses with side-shields.

Chemical resistant gloves are recommended. Avoid contact with the skin. Wear Skin Protection.....

appropriate chemical resistant clothing. Use dust and mist respirator.

Respiratory Protection.....

Thermal Hazards..... None Known.

General Hygiene Considerations..... When using, do not eat, drink or smoke. Always observe good personal hygiene measures,

such as washing after handling the material and before eating, drinking, and/or smoking.

CODE: KR-093400

Routinely wash work clothing and protective equipment prior to use.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Aerosol. Form..... Physical Appearance..... Clear liquid. Odor..... Heptane. Odor Threshold (ppm)..... Specific Gravity (Liquid).... N/À. 0.680-0.700. Specific Gravity (Aerosol)...... Aerosol Vapour Pressure (psig, 21°C)..... 0.720-0.750. 80-100. Vapour Density (Air=1)..... Not applicable. 94-98. (Heptanes). -8. [ASTM D-56]. Yes. Evaporation Rate (n-Butyl Acetate = 1)..... > 1 (n-Butyl Acetate = 1). VOC Content..... 96wt% (669g/L - 5.59 lb/gal). Solubility in water..... Immiscible. Aerosol Flame Projection..... > 45 cm but < 100 cm. Auto Ignition Temperature (liquid), °C...... 245. 1.1. (Heptane). 6.7. (Heptane). Coefficient of Water/Oil Distribution...... Viscosity..... 0.49 cSt (0.49 mm2/sec) at 40 °C. (Heptane).

SECTION 10: STABILITY AND REACTIVITY

Product not reactive under normal conditions of use.

Material is stable under normal conditions.

Possibility of Hazardous Reactions..... Will not occur.

Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.

Incompatible Materials..... Strong oxidizing agents. Strong acids.

Hazardous Decomposition Products...... Carbon Oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Heptane (includng isomers)	>23.3 mg/L (Rat - 4hrs)	>5,840 mg/kg (Oral - Rat); >2,920 mg/kg (Dermal - Rat)
Carbon dioxide	Not available	Not available

Information on Likely Routes of Exposure: Routes of entry - Inhalation..... Yes. Routes of entry - Skin & Eye..... Yes. Yes.

Symptoms Related to the Physical, Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred Chemical and Toxicological Characteristics vision. Defatting of the skin. Symptoms of overexposure may be headache, dizziness, Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred

tiredness, nausea and vomiting. Acute Toxicity..... Harmful or fatal if swallowed.

Skin Corrosion/Irritation..... Causes skin irritation.

Serious Eye Damage/Eye Irritation..... Direct eye contact may cause slight redness. Spraying directly into the eyes may cause

frostbite, damage to the cornea resulting in permanent eye injury.

Respiratory or Skin Sensitization..... May cause sensitization by skin contact.

No data available to indicate product or any components present at greater than 0.1% are Germ Cell Mutagenicity..... mutagenic.



PRODUCT: Krown KE93 Brake and Parts Cleaner - 390 g

SECTION 11: TOXICOLOGICAL INFORMATION

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity..... Reproductive Toxicity..... Contains no ingredient listed as toxic to reproduction. Specific target organ toxicity single exposure Category 3. May cause drowsiness and STOT - Single Exposure..... dizziness. STOT - Repeated Exposure..... No data available. Aspiration Hazard..... Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.
Organic solvents may be absorbed into the body by inhalation and ingestion and cause Chronic Effects.....

permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

CODE: KR-093400

SECTION 12: ECOLOGICAL INFORMATION

Harmful to aquatic life. Should not be released into the environment. This product contains Ecotoxicity..... the following ingredients: . Heptane (CAS#.142-82-5): Toxicity to fish: LC50 1.284 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 0.1 mg/L, 96 hrs; Toxicity to algae: EL50 4.338 mg/L, 72 hrs.

The product itself has not been tested. Persistence and degradability

Bioaccumulation Potential..... Heptane: Readily Biodegradability:28 days (media - water).

Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... This material and its container must be disposed of as hazardous waste. Avoid release to

the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations.

Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.1. DOT (US-Road).....IMDG (International- Marine)..... UN1950, AEROSOLS, Class 2.1, LTD QTY, Consumer Commodity ORM-D.

UN1950, AEROSOLS, Class 2.1. UN1950, AEROSOLS, Class 2.1, LTD QTY. IATA (International- Air).....

SECTION 15: REGULATORY INFORMATION

Canada Regulations:.... WHMIS Classification. A: Compressed gas. B5: Flammable aerosol. D2B: Material causing other toxic Materials.

Canadian Environmental Protection Act ... All ingredients listed appear on the Domestic Substances List (DSL). (CEPA)

ÙS Regulations..... Environmental Protection Act: Constituents of this product are included on the TSCA inventory. This product is considered hazardous under the OSHA Hazard Communication

Standard.
This product does not contain any chemical(s) known to the state of California to cause

California Proposition 65.....

cancer or reproductivity toxicity.

SECTION 16: OTHER INFORMATION

The information contained herein is based on data considered accurate. No guarantee or Disclaimer..... warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information

required by the CPR. .

ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abbreviations.....

Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous

Materials Information System STOT: Specific Target Organ Toxicity.

Regularity Affairs. Prepared by

Latest Revision OCT 04/2018