

Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 1 of 13

## SAFETY DATA SHEET

### SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Northland BREAK THRU**

Product Code(s) : C5 (145 g); C10 (370 g); BT60SC; BT60BP

Recommended use of the chemical and restrictions on use

: Fast penetrating oil for frozen and rusted parts.  
No restrictions on use known.

Chemical family : Mixture of: Petroleum oil; Propellant; Ketones; Sodium salts

Name, address, and telephone number of the supplier:

**NLS Products**

Box 790, 1 Lakewood Crescent  
Bobcaygeon, ON, Canada  
K0M 1A0

Supplier's Telephone # : (705) 732-2321

24 Hr. Emergency Tel # : INFOTRAC - (800) 535-5053 (Within Continental US); (352) 323-3500 (Outside US)

Name, address, and telephone number of the manufacturer:

Refer to supplier

### SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear to yellow liquid, contained in a pressurized aerosol can. Slightly aromatic odour.

*Most important hazards:*

Extremely flammable aerosol. May be ignited by open flame. Closed containers are contained under pressure and may explode if exposed to excess heat for a prolonged period of time.

Causes serious eye damage. Occupational exposure to the substance or mixture may cause adverse effects. For further information, please refer to section 11 of the SDS.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. See Section 12 for more environmental information.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Hazardous classification:

Flammable aerosol - Category 1

Gases under pressure

Eye damage/irritation - Category 1

Label elements

Hazard pictogram(s)



Signal Word  
DANGER!

Hazard statement(s)

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye damage.

Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 2 of 13

## SAFETY DATA SHEET

### Precautionary statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Wear eye/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
Store in a well-ventilated place.

### Other hazards

#### Other hazards which do not result in classification:

Burning produces obnoxious and toxic fumes. May be mildly irritating to skin and respiratory system. In extremely high concentrations, may cause symptoms of central nervous system depression. May cause gastrointestinal irritation. Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Distillates (petroleum), hydrotreated heavy naphthenic	Mineral oil	64742-52-5	71.783
Propane	Dimethylmethane Propyl hydride	74-98-6	10.335
Cyclohexanone	Cyclohexyl ketone Ketoexamethylene	108-94-1	7.14
Isobutane	2-Methylpropane Trimethylmethane	75-28-5	4.665
Petroleum sulfonate	Sodium petroleum sulfonate Sulfonic acids, petroleum, sodium salts	68608-26-4	3.34

## SECTION 4. FIRST-AID MEASURES

### Description of first aid measures

- |                     |   |  |
|---------------------|---|--|
| <i>Ingestion</i>    | : | Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if symptoms persist.  |
| <i>Inhalation</i>   | : | If inhaled, move to fresh air. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing is irregular or stopped, administer artificial respiration. If irritation or symptoms develop, seek medical attention. |
| <i>Skin contact</i> | : | For skin contact, wash with soap and water while removing contaminated clothing. If irritation or symptoms develop, seek medical attention. Wash contaminated clothing before reuse.   |
| <i>Eye contact</i>  | : | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.   |

Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 3 of 13

## SAFETY DATA SHEET

### Most important symptoms and effects, both acute and delayed

- : Causes serious eye damage. Contact may cause redness, swelling and a painful sensation. May cause irreversible eye damage.
- : May be mildly irritating to skin and respiratory system. May cause coughing and breathing difficulties. Symptoms may include mild redness and swelling. In extremely high concentrations, may also cause nausea, vomiting, dizziness, drowsiness and other symptoms of central nervous system depression.
- : Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
- : Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

### Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

### Extinguishing media

#### *Suitable extinguishing media*

- : Carbon dioxide (CO<sub>2</sub>); Dry chemical; Alcohol resistant foam

#### *Unsuitable extinguishing media*

- : Do not use a solid water stream as it may scatter and spread fire.

### Special hazards arising from the substance or mixture / Conditions of flammability

- : Extremely flammable aerosol. Pressurized container: may burst if heated. Vapours are heavier than air and may spread along floors. Product may float, and be re-ignited at the water's surface. This product is contained under pressure, and could explode when exposed to heat and flame.

### Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable aerosol. - Category 1

### Hazardous combustion products

- : Carbon oxides; Hydrocarbons; Sulfur oxides; Phosphorus oxides; Nitrogen oxides (NO<sub>x</sub>); Polycyclic aromatic hydrocarbons; Other unidentified organic compounds.

### Special protective equipment and precautions for firefighters

#### *Protective equipment for fire-fighters*

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

#### *Special fire-fighting procedures*

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Shield personnel to protect from venting or rupturing containers. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

- : All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

### Environmental precautions

- : Prevent product from entering drains, sewers, waterways and soil.



Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 4 of 13

## SAFETY DATA SHEET

### Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.

### Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).  
US CERCLA Reportable quantity (RQ): Cyclohexanone (5000 lbs / 2270 kg)

In Canada: Contact appropriate local and provincial environmental authorities for assistance and/or reporting requirements.

## SECTION 7. HANDLING AND STORAGE

### Precautions for safe handling

- : Use with adequate ventilation. Avoid breathing dust, mist or vapours. Wear suitable protective equipment during handling. Wear eye/face protection. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flame. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Keep away from incompatibles. Always replace cap after use. Wash thoroughly after handling.

### Conditions for safe storage

- : Store in cool/well-ventilated place. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Protect from sunlight. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area.

### Incompatible materials

- : Strong oxidizing agents; Halogenated compounds; Strong acids; Strong bases

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b><u>Exposure Limits:</u></b>				
<b><u>Chemical Name</u></b>	<b><u>ACGIH TLV</u></b>		<b><u>OSHA PEL</u></b>	
	<b><u>TWA</u></b>	<b><u>STEL</u></b>	<b><u>PEL</u></b>	<b><u>STEL</u></b>
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m <sup>3</sup> (As 'Oil mist, mineral') (inhalable)	N/Av	5 mg/m <sup>3</sup> (As 'Oil mist, mineral')	N/Av
Propane	N/Av	N/Av	1000 ppm (1800 mg/m <sup>3</sup> )	N/Av
Cyclohexanone	20 ppm (skin)	N/Av	50 ppm (200 mg/m <sup>3</sup> )	N/Av
Isobutane	1000 ppm (as 'Butane, all isomers')	N/Av	N/Av	N/Av
Petroleum sulfonate	N/Av	N/Av	N/Av	N/Av

Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 5 of 13

## SAFETY DATA SHEET

### Exposure controls

#### Ventilation and engineering measures

- : Provide adequate ventilation. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient ventilation wear suitable respiratory equipment.

#### Respiratory protection

- : If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

#### Skin protection

- : Gloves impervious to the material are recommended. Wear sufficient clothing to prevent skin contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

#### Eye / face protection

- : Wear eye/face protection. Wear as appropriate: Tightly fitting safety goggles; Safety glasses with side shields. A full face shield may also be necessary.

#### Other protective equipment

- : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

#### General hygiene considerations

- : Avoid breathing dust, mist or vapours. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : Clear to yellow liquid, contained in a pressurized aerosol can.

**Odour** : Slightly aromatic odour.

**Odour threshold** : N/Av

**pH** : N/Av

**Melting/Freezing point** : N/Av

#### Initial boiling point and boiling range

: 130.03°C (266.1°F) (concentrate) (estimation)

**Flash point** : 44°C (111°F) (concentrate)

**Flashpoint (Method)** : closed cup

**Evaporation rate (BuAe = 1)** : N/Av

**Flammability (solid, gas)** : Not applicable.

#### Lower flammable limit (% by vol.)

: N/Av

#### Upper flammable limit (% by vol.)

: N/Av

**Oxidizing properties** : None known.

**Explosive properties** : Aerosols are sensitive to mechanical impact. Closed containers are contained under pressure and may explode if exposed to excess heat for a prolonged period of time.

**Vapour pressure** : 276 - 345 kPa (40 - 50 psi)

**Vapour density** : > 1 (Air = 1.0)

#### Relative density / Specific gravity

: 0.72 - 0.89 (concentrate)

**Solubility in water** : Insoluble.

**Other solubility(ies)** : N/Av

#### Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

**Auto-ignition temperature** : N/Av

**Decomposition temperature** : N/Av

Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 6 of 13

## SAFETY DATA SHEET

Viscosity : 55 mm<sup>2</sup>/sec @ 40°C (104°F) (concentrate)

Volatiles (% by weight) : 8.085%

Volatile organic Compounds (VOC's)

: N/Av

Absolute pressure of container

: N/Av

Flame projection length : > 45 cm, < 100 cm

Other physical/chemical comments

: Chemical heat of combustion: N/Av

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerization does not occur.

Conditions to avoid

: Direct sources of heat. Keep away from direct sunlight. Do not use in areas without adequate ventilation. Avoid contact with incompatible materials.

Incompatible materials

: Strong oxidizing agents; Halogenated compounds; Strong acids; Strong bases

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure:

Routes of entry inhalation : YES

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption

: YES

#### Potential Health Effects:

##### Signs and symptoms of short-term (acute) exposure

###### *Sign and symptoms Inhalation*

: May cause mild transient irritation. May cause coughing and breathing difficulties. In extremely high concentrations, may also cause nausea, vomiting, dizziness, drowsiness and other symptoms of central nervous system depression.

###### *Sign and symptoms ingestion*

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache).

###### *Sign and symptoms skin*

: May cause mild skin irritation. Symptoms may include mild redness and swelling. May be absorbed through the skin.

###### *Sign and symptoms eyes*

: Causes serious eye damage. Contact may cause redness, swelling and a painful sensation. May cause irreversible eye damage.

##### Potential Chronic Health Effects

: Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.

##### Mutagenicity

: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 7 of 13

## SAFETY DATA SHEET

- Carcinogenicity** : Not classifiable as a human carcinogen. No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.
- Reproductive effects & Teratogenicity** : This product is not expected to cause reproductive or developmental effects.
- Sensitization to material** : No data available to indicate product or components may be respiratory sensitizers.  
No data available to indicate product or components may be skin sensitizers.
- Specific target organ effects** : According to the classification criteria of U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015), this product is not expected to cause target organ toxicity through single or repeated exposures.
- Mild effects may be seen in the following organs: Eyes; Skin; Respiratory system; Digestive system; Central nervous system; Liver; Kidneys
- Medical conditions aggravated by overexposure** : Pre-existing skin, eye, respiratory and central nervous system disorders.
- Synergistic materials** : None reported by the manufacturer.
- Toxicological data** : No data is available on the product itself. The calculated ATE values for this mixture are:  
ATE oral = 18,798 mg/kg  
ATE dermal = 13,165 mg/kg  
ATE inhalation (vapours) = 148.5 mg/L/4H

See below for individual ingredient acute toxicity data.

<u>Chemical name</u>	<u>LC<sub>50</sub> (4hr)</u> <u>inh, rat</u>	<u>LD<sub>50</sub></u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Distillates (petroleum), hydrotreated heavy naphthenic	> 5 mg/L (mist)	> 5000 mg/kg	> 2000 mg/kg
Propane	N/Av	N/Ap (gas)	N/Ap (gas)
Cyclohexanone	2639 ppm (10.6 mg/L) (vapour)	1340 mg/kg	940 mg/kg
Isobutane	368 000 ppm (mouse)	N/Ap (gas)	N/Ap (gas)
Petroleum sulfonate	> 1.9 mg/L (aerosol) (No mortality)	> 5000 mg/kg	> 5000 mg/kg

### Other important toxicological hazards

- : None reported by the manufacturer.

## SECTION 12. ECOLOGICAL INFORMATION

- Ecotoxicity** : Not expected to be harmful to aquatic organisms. No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

See the following tables for individual ingredient ecotoxicity data.



Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 8 of 13

## SAFETY DATA SHEET

### Ecotoxicity data:

<u>Ingredients</u>	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 100 mg/L (Fathead minnow)	N/Av	None.
Propane	74-98-6	N/Ap	N/Ap	N/Ap
Cyclohexanone	108-94-1	527 - 732 mg/L (Fathead minnow)	N/Av	None.
Isobutane	75-28-5	N/Ap	N/Ap	N/Ap
Petroleum sulfonate	68608-26-4	> 100 mg/L (Rainbow trout)	N/Av	None.

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 10 000 mg/L (Daphnia magna)	10 mg/L	None.
Propane	74-98-6	N/Ap	N/Ap	N/Ap
Cyclohexanone	108-94-1	> 100 mg/L (Daphnia magna) (Read-across)	N/Av	None.
Isobutane	75-28-5	N/Ap	N/Ap	N/Ap
Petroleum sulfonate	68608-26-4	> 100 mg/L (Daphnia magna)	N/Av	None.

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 1000 mg/L/96hr (Green algae)	≥ 100 mg/L/72hr	None.
Propane	74-98-6	N/Ap	N/Ap	N/Ap
Cyclohexanone	108-94-1	> 100 mg/L/72hr (Green algae) (Read-across)	≥ 100 mg/L/72hr (Read-across)	None.
Isobutane	75-28-5	N/Ap	N/Ap	N/Ap
Petroleum sulfonate	68608-26-4	> 100 mg/L/72hr (Green algae)	1000 mg/L/96hr	None.

### Persistence and degradability

- : The product itself has not been tested.
- The following ingredients are considered to be readily biodegradable: Cyclohexanone.
- Contains the following chemicals which are considered to be inherently biodegradable: Distillates (petroleum), hydrotreated heavy naphthenic.
- Contains the following chemicals which are not readily biodegradable: Petroleum sulfonate.



Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 9 of 13

## SAFETY DATA SHEET

**Bioaccumulation potential** : The product itself has not been tested. See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	3.9 - 6 (calculated)	N/Av
Cyclohexanone (CAS 108-94-1)	0.0805	2.4
Isobutane (CAS 75-28-5)	2.76 (calculated)	27 (estimated)
Petroleum sulfonate (CAS 68608-26-4)	N/Av	3 (estimated)

**Mobility in soil** : The product itself has not been tested.

**Other Adverse Environmental effects**

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### SECTION 13. DISPOSAL CONSIDERATIONS

**Handling for Disposal** : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

**Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations.

**RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

Northland BREAK THRU





C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 10 of 13

## SAFETY DATA SHEET

### SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	UN1950	AEROSOLS	2.1	none	
<b>TDG Additional information</b>	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass. Under the TDG, refer to Section 1.17 for additional exemption requirements, if shipping under this exemption.				
49CFR/DOT	UN1950	Aerosols	2.1	none	
<b>49CFR/DOT Additional information</b>	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass.				
ICAO/IATA	UN1950	Aerosols, flammable	2.1	none	
<b>ICAO/IATA Additional information</b>	Refer to the appropriate Packing Instruction, prior to shipping this material. Review all State and Operator Variations, prior to shipping this material.				
IMDG	UN1950	AEROSOLS	2.1	none	
<b>IMDG Additional information</b>	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass.				

**Special precautions for user** : Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame. - No smoking.

**Environmental hazards** : This product does not meet the criteria for an environmentally hazardous mixture, according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

: Not applicable.



Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 11 of 13

## SAFETY DATA SHEET

### SECTION 15 - REGULATORY INFORMATION

#### US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Yes	None.	None.	No	N/Ap
Propane	74-98-6	Yes	None.	None.	No	N/Ap
Cyclohexanone	108-94-1	Yes	5000 lb/ 2270 kg	None.	No	N/Ap
Isobutane	75-28-5	Yes	None.	None.	No	N/Ap
Petroleum sulfonate	68608-26-4	Yes	None.	None.	No	N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Physical hazards (Flammable aerosol; Gas Under Pressure)

Health hazards (Eye Damage).

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

#### US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	No	N/Ap	No	No	No	No	No	No
Propane	74-98-6	No	N/Ap	No	Yes	Yes	Yes	Yes	Yes
Cyclohexanone	108-94-1	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Isobutane	75-28-5	No	N/Ap	No	Yes	No	Yes	Yes	No
Petroleum sulfonate	68608-26-4	No	N/Ap	No	No	No	No	No	No

#### Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI:  
Propane (Part 5: Individual Substances)

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.



Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 12 of 13

## SAFETY DATA SHEET

### International Information:

Components listed below are present on the following International Inventory list:

Ingredients	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	Present	Present	(9)-1689	KE-12543	Present	May be used as a single component chemical under an appropriate group standard.
Propane	74-98-6	200-827-9	Present	Present	(2)-3	KE-29258	Present	HSR001010
Cyclohexanone	108-94-1	203-631-1	Present	Present	(3)-2376	KE-09188	Present	HSR001112
Isobutane	75-28-5	200-857-2	Present	Present	(2)-4	KE-24865	Present	HSR001003
Petroleum sulfonate	68608-26-4	271-781-5	Present	Present	(8)-424; (9)-1739; (9)-1780	KE-32519	Present	HSR003545

### SECTION 16. OTHER INFORMATION

#### Legend

: ACGIH: American Conference of Governmental Industrial Hygienists  
AICS: Australian Inventory of Chemical Substances  
ATE: Acute Toxicity Estimate  
CA: California  
CAS: Chemical Abstract Services  
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980  
CFR: Code of Federal Regulations  
CSA: Canadian Standards Association  
DOT: Department of Transportation  
EC50: Effective Concentration 50%  
EINECS: European Inventory of Existing Commercial chemical Substances  
ENCS: Existing and New Chemical Substances  
EPA: Environmental Protection Agency  
HSDB: Hazardous Substances Data Bank  
IARC: International Agency for Research on Cancer  
IBC: Intermediate Bulk Container  
IECSC: Inventory of Existing Chemical Substances  
IMDG: International Maritime Dangerous Goods  
IOC: Inventory of Chemicals  
KECI: Korean Existing Chemicals Inventory  
KECL: Korean Existing Chemicals List  
LC: Lethal Concentration  
LD: Lethal Dose  
MA: Massachusetts  
MN: Minnesota  
N/Ap: Not Applicable  
N/Av: Not Available  
NIOSH: National Institute of Occupational Safety and Health  
NJ: New Jersey  
NOEC: No observable effect concentration  
NTP: National Toxicology Program  
OECD: Organisation for Economic Co-operation and Development  
OSHA: Occupational Safety and Health Administration  
PA: Pennsylvania  
PEL: Permissible exposure limit

Northland BREAK THRU

C5 (145 g); C10 (370 g); BT60SC; BT60BP

SDS Preparation Date (mm/dd/yyyy): 01/16/2018

Page 13 of 13

## SAFETY DATA SHEET

PICCS: Philippine Inventory of Chemicals and Chemical Substances  
RCRA: Resource Conservation and Recovery Act  
RI: Rhode Island  
RTECS: Registry of Toxic Effects of Chemical Substances  
SARA: Superfund Amendments and Reauthorization Act  
SDS: Safety Data Sheet  
STEL: Short Term Exposure Limit  
TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
TLV: Threshold Limit Values  
TSCA: Toxic Substance Control Act  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System

### References

- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2017.
2. International Agency for Research on Cancer Monographs, searched 2017.
3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2017 (Chempendium, HSDB and RTECs).
4. Material Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists - March 2015 version.
6. California Proposition 65 List - December 15, 2017 version.
7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2017.

### Preparation Date (mm/dd/yyyy)

: 01/16/2018

### Other special considerations for handling

: Provide adequate information, instruction and training for operators.

<p><b><u>Prepared for:</u></b> NLS Products Box 790, 1 Lakewood Crescent Bobcaygeon, ON, Canada K0M 1A0 Telephone: (705) 738-2321 Direct all enquiries to: NLS Products</p>	
<p><b><u>Prepared by:</u></b> ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada) <a href="http://www.thecompliancecenter.com">http://www.thecompliancecenter.com</a></p>	

## DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by NLS Products and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and NLS Products expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and NLS Products.

**END OF DOCUMENT**