

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	BIO-MAX
Other means of identification	780
Recommended use	All Purpose Cleaner
Manufacturer	Prolab Technolub inc. 4531 rue industrielle Thetford Mines, (Québec), Canada G6H 2J1 Phone: (418) 423-2777

Emergency Phone (CANUTEC Emergency only) : (613) 996-6666

2. Hazards Identification

Physical hazards	Corrosive to metals	Category 1
Risques pour la santé	Eye damage/irritation	Category 1
	Skin corrosion/irritation	Category 1
Environmental hazards	Not classified	
OSHA defined hazards	Not classified	
Label elements		



Signal word	Danger
Hazard statement	May be corrosive to metals Causes severe skin burns and eye damage.
Precautionary statement	
Prevention	Do not breathe dust/fumes/gas/mist/vapours/spray. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. Immediately call a POISON CENTER/doctor. Specific treatment (see this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.
Storage	Keep only in original container. Store locked up. Store in a corrosive resistant container or a container with resistant inner liner.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None

3. Composition/Information on Ingredients

Mixture	Common name and synonyms	CAS number	%
Chemical name			
Sodium Silicate		6834-92-0	1 – 5
Potassium Hydroxide 1		310-58-3	1 - 5
2-Butoxyethanol		111-76-2	7 -13

4. First Aid Measures

Inhalation

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor/.

Skin contact

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Specific treatment (see product label). Immediately call a poison center/doctor/.

Eye contact

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Ingestion

If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center/doctor/.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Wear rubber gloves and chemical splash goggles. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media

Treat for surrounding material.

Unsuitable extinguishing media

Use appropriate extinguisher, as surrounding material.

Specific hazards arising from the chemical

Firefighters should wear a self-contained breathing apparatus.

Special protective equipment and precautions for firefighters Fire-fighting equipment/instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

Move containers from fire area if you can do so without risk.

Precautions for firefighters Fire-fighting

Éloigner les récipients de l'incendie si cela peut se faire sans risque.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

Hazardous combustion products

May include and are not limited to: Carbon oxide

Explosion data

Sensitivity to mechanical impact

Not available.

Sensitivity to static discharge

Not available.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Should not be released into the environment.

Large Spills: Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb spillage to prevent material damage. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water .

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewers, basements or confined areas.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling

Use only with adequate ventilation. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. Avoid breathing vapors or mists of this product. DO NOT get in eyes, on skin or clothing.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in corrosive resistant container with a resistant inner liner. Keep only in the original container. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls/Personal Protection

Occupational exposure limits

Components

Sodium silicate

Potassium Hydroxide

2-Butoxyethanol TWA :

Value

Exposition limit : 2mg/m³ (15 min TWA)

Ceiling : 2 mg/m³

Maximum concentration : 20 ppm ACGIH

Biological limit values Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical splash goggles.

Skin protection. Hand protection

Chemical resistant gloves. Confirm with a reputable supplier first.

Other

Wear appropriate chemical resistant clothing. As required by employer code.

Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Thermal hazards

Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Wash hands before breaks and immediately after handling the product.

9. Physical and Chemical Properties

Appearance	Clear
Physical state	Liquid
Form	Liquid
Color	Translucent green
Odor	Green apple
Odor threshold	Not available
pH	> 13.0
Melting point/freezing point	0 °C
Initial boiling point and boiling range	100 °C
Pour point	Not available
Partition coefficient (n-octanol/water)	Not available
Flash point	> 94°C
Evaporation rate	Not available
Flammability (solid, gas)	Not applicable
Flammability limit - lower (%)	Not available
Flammability limit - upper (%)	Not available
Explosive limit - lower (%)	Not available
Explosive limit - upper (%)	Not available
Vapor pressure	Not available
Vapor density	Not available
Relative density	1.04
Solubility(ies)	Complete
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available.

10. Stability and Reactivity

Reactivity	Strong acids. This product may react with oxidizing agents.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Reacts with strong acids. This product may react with oxidizing agents.
Incompatible materials	Oxidizing agents. Acids.
Hazardous decomposition products	May include and are not limited to: Carbon oxide

Routes of exposure
Information on likely routes of exposure
Ingestion
Inhalation
Skin contact
Eye contact

11. Toxicological Information

Eye, Skin contact, Inhalation, Ingestion.

Causes digestive tract burns.
 Prolonged inhalation may be harmful.
 Causes severe skin burns.
 Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity

Components

Sodium silicate

Acute

Dermal DL50

Inhalation CL50

Oral

Species

Rat

Rat

Rat

Test Results

> 5000 mg/kg

>2.06 g/m³ (4Hours)

3400 mg/kg

2-Butoxyethanol

Acute

Oral DL50

Dermal DL50

Rat

Rat

1300 mg/kg

> 2000 mg/kg

Potassium Hydroxide

Oral DL50

Dermal DL50

Rat

Rabbit

273 mg/kg

50 mg/kg

Skin corrosion/irritation

Exposure minutes

Erythema value

Oedema value

Serious eye damage/eye irritation

Corneal opacity value

Causes severe skin burns and eye damage.

Not available.

Not available.

Not available.

Causes serious eye damage.

Pas disponible.

Iris lesion value

Valeur des rougeurs de la conjonctive

Valeur d'un oedème de la conjonctive

Jours de récupération

Not available.

Not available.

Not available.

Not available.

Respiratory or skin sensitization

Respiratory sensitization

Skin sensitization

Germ cell mutagenicity

Mutagenicity

Carcinogenicity

Reproductive toxicity

Teratogenicity

Not available.

This product is not expected to cause skin sensitization.

Non-hazardous by WHMIS/OSHA criteria.

Non-hazardous by WHMIS/OSHA criteria.

None

Non-hazardous by WHMIS/OSHA criteria.

Non-hazardous by WHMIS/OSHA criteria.

Specific target organ toxicity - single exposure

Specific target organ toxicity - repeated exposure

Not classified.

Not classified.

Aspiration hazard

Chronic effects

Further information

Name of Toxicologically

Synergistic Products

Not available.

Prolonged inhalation may be harmful.

Not available.

Not available.

12. Ecological Information

Ecotoxicity Components	Species	Test Results
Sodium silicate	Fish (Brachydanio rerio) LC50 (96 hours)	1108 mg/l
	Aquatic invertebrates (Daphnia magna) EC50(48 hour)	1700 mg/l
2-Butoxyethanol	LC50 Fish (Rainbow Trout) (96 hours)	1474 mg/l
	EC50 Daphnia magna (48 hours)	1550 mg/l
	EC50 Algae (72 hours)	1840 mg/l
Persistence and degradability	Biodegradable	
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Mobilité générale	Pas disponible.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal Consideration

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. ITransport Information

General	Canada: TDG Proof of Classification: In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue. If applicable, the technical name and the classification of the product will appear below.
----------------	---

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number	Un1760
Proper shipping name	Corrosive liquids, n.o.s. (Sodium silicate)
Hazard class	8
Packing group	III



Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	Un1760
Proper shipping name	Corrosive liquids, n.o.s. (Sodium silicate)
Hazard class	8
Packing group	III



Special precautions (transport/conveyance)

May also be shipped as a LIMITED QUANTITY up to 5 litres in accordance with TDG.

15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.


WHMIS status Controlled
WHMIS classification Class E - Corrosive Material
WHMIS labeling



16. Other Information

LÉGENDE	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 2
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

The data contained in this material safety data sheet was obtained from sources that were technically accurate, reliable, and state of the art when this document was prepared. If data was unavailable to complete certain sections, the absence of that data is identified in this document. Because the supplier cannot know the exact circumstances during actual use of this product, other hazards, exposure scenarios, disposal considerations, and regulations may apply and it is the responsibility of the user to read and understand the product label and this document before use.

Issue date

October 24, 2018

Effective date

October 24, 2018

Further information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Prepared for

Prolab Technolub inc. Tél: (418) 423-2777

Other information

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).