

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations


Printing date: June 06, 2017

Revision: June 06, 2017

1 Identification

- **Product identifier**
- **Trade name:** Gumout Multi-System Tune-Up
- **Other means of identification:** 30002
- **Recommended use and restriction on use**
- **Recommended use:** Cleaner for fuel injection systems.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
ITW Permatex Canada
35 Brownridge Rd., Unit 1, Halton Hills ON L7G 0C6
(905 693-8900 (Tel), (905) 864-8602 (Fax))
- **Emergency telephone number:**
ChemTel Inc.
(800) 255-3924 (North America)
(801) 1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Eye Irrit. 2A H319 Causes serious eye irritation.
Carc. 1B H350 May cause cancer.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

GHS02 GHS07 GHS08
- **Signal word:** Danger
- **Hazard statements:**
H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H350 May cause cancer.
H304 May be fatal if swallowed and enters airways.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 1)

· Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash thoroughly after handling.
- P280 Wear protective gloves and eye protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P331 Do NOT induce vomiting.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:

64742-47-8	Distillates (petroleum), hydrotreated light ⚠ Asp. Tox. 1, H304 ⚠ Flam. Liq. 4, H227	30-45%
64742-46-7	Distillates (petroleum), hydrotreated middle ⚠ Asp. Tox. 1, H304	30-40%
67-63-0	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	5-10%
1398506-12-1	Oxirane, 2-ethyl-, homopolymer, 3-aminopropyl C11-14-isoalkyl ethers, C13-rich ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	2-6%
	Succinic anhydride, alkylation products with C12-rich branched olefins from propene oligomerisation, hydrolyzed, esterification products with propylene oxide ⚠ Eye Irrit. 2A, H319; Skin Sens. 1B, H317	<1%

(Cont'd. on page 3)

Safety Data Sheet






acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 2)

100-41-4	ethylbenzene <hr style="border-top: 1px dashed black;"/>  Flam. Liq. 2, H225  Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H332	<1%
122-39-4	diphenylamine <hr style="border-top: 1px dashed black;"/>  Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331  STOT RE 2, H373	<1%

· **Additional information:** For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

- Supply fresh air.
- Provide oxygen treatment if affected person has difficulty breathing.
- If experiencing respiratory symptoms: Call a doctor.
- In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

- Wash with soap and water.
- If skin irritation continues, consult a doctor.

· **After eye contact:**

- Remove contact lenses if worn.
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

- Rinse out mouth and then drink plenty of water.
- Do not induce vomiting; immediately call for medical help.
- A person vomiting while lying on their back should be turned onto their side.

· **Most important symptoms and effects, both acute and delayed:**

- Breathing difficulty
- Coughing
- Dizziness
- Nausea in case of ingestion.
- Gastric or intestinal disorders when ingested.
- Causes eye irritation.
- Causes mild skin irritation.
- Disorientation

· **Danger:**

- Danger of impaired breathing.
- Danger of disturbed cardiac rhythm.
- May be fatal if swallowed and enters airways.
- May cause neurotoxic effects.
- May cause cancer.

· **Indication of any immediate medical attention and special treatment needed:**

- If swallowed or in case of vomiting, danger of entering the lungs.
- If necessary oxygen respiration treatment.
- Later observation for pneumonia and pulmonary edema.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Foam
 - Gaseous extinguishing agents
 - Carbon dioxide
 - Water fog / haze
- **For safety reasons unsuitable extinguishing agents:**
 - Water stream.
 - Water spray
- **Special hazards arising from the substance or mixture**
 - Highly flammable liquid and vapor.
 - Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
- **Additional information:**
 - Cool endangered containers with water fog.
 - Use large quantities of foam as it is partially destroyed by the product.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Use personal protective equipment as required.
 - For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
 - Ensure adequate ventilation.
 - Keep away from ignition sources.
- **Environmental precautions**
 - Do not allow to enter sewers/ surface or ground water.
 - Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
 - Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
 - Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
 - Prevent formation of aerosols.
 - Avoid splashes or spray in enclosed areas.

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 4)

Use only in well ventilated areas.

Avoid contact with the eyes and skin.

Keep out of reach of children.

· **Information about protection against explosions and fires:**

Highly flammable liquid and vapor.

Keep ignition sources away - Do not smoke.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:**

Store in cool, dry conditions in well sealed receptacles.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

· **Further information about storage conditions:** Storage Temperatures : <122 °F / <50 °C.

· **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

64742-47-8 Distillates (petroleum), hydrotreated light

EL (Canada)	Long-term value: 200 mg/m ³ Skin
-------------	--

67-63-0 propan-2-ol

PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI
EL (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
EV (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
LMPE (Mexico)	Short-term value: 400 ppm Long-term value: 200 ppm A4, IBE

100-41-4 ethylbenzene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 5)

TLV (USA)	Long-term value: 87 mg/m ³ , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm IARC 2B
EV (Canada)	Short-term value: 540 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
LMPE (Mexico)	Long-term value: 20 ppm

122-39-4 diphenylamine

REL (USA)	Long-term value: 10 mg/m ³
TLV (USA)	Long-term value: 10 mg/m ³
EL (Canada)	Long-term value: 10 mg/m ³
EV (Canada)	Long-term value: 10 mg/m ³
LMPE (Mexico)	Long-term value: 10 mg/m ³ A4

Ingredients with biological limit values:

67-63-0 propan-2-ol

BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----------	---

100-41-4 ethylbenzene

BEI (USA)	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	- Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Engineering controls: Provide adequate ventilation.

Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device when aerosol or mist is formed.

Protection of hands:



Protective gloves

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 6)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection:


Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· **Body protection:** Protection may be required for spills.

Limitation and supervision of exposure into the environment

No relevant information available.

9 Physical and chemical properties

Information on basic physical and chemical properties
Appearance:

· Form:	Liquid
· Color:	Amber colored
· Odor:	Petroleum-like
· Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Melting point/Melting range:** Not determined.

· **Boiling point/Boiling range:** Not determined.

· **Flash point:** 18 °C (64 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Auto-ignition temperature:** Not determined.

· **Decomposition temperature:** Not determined.

· **Danger of explosion:** Not determined.

Explosion limits

· **Lower:** Not determined.

· **Upper:** Not determined.

· **Oxidizing properties:** Non-oxidizing.

· **Vapor pressure:** Not determined.

Density:

· **Relative density:** 0.843

· **Vapor density:** >1 (air=1)

· **Evaporation rate:** Not determined.

Solubility in / Miscibility with

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

Viscosity

· **Dynamic:** Not determined.

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 7)

Kinematic:	Not determined.
VOC content:	10 % Vol
Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Highly flammable liquid and vapor.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Toxic fumes may be released if heated above the decomposition point.
Reacts violently with oxidizing agents.
- **Conditions to avoid** Keep ignition sources away - Do not smoke.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**

Under fire conditions only:
Carbon monoxide and carbon dioxide
Nitrogen oxides

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

64742-47-8 Distillates (petroleum), hydrotreated light

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

36878-20-3 bis(nonylphenyl)amine

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

122-39-4 diphenylamine

Oral	LD50	1120 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **On the skin:**
Causes mild skin irritation.
Based on available data, the classification criteria are not met.
- **On the eye:** Causes serious eye irritation.
- **Sensitization:** Based on available data, the classification criteria are not met.

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 8)

· **IARC (International Agency for Research on Cancer):**

100-41-4 ethylbenzene	2B
-----------------------	----

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

- Ingestion.
- Inhalation.
- Eye contact.
- Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** May cause cancer.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- **Additional ecological information**
- **General notes:** Avoid release to the environment.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Contact waste processors for recycling information.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017




Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 9)

- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA 	<p>UN1993</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR, IMDG · IATA 	<p>Flammable liquids, n.o.s. (Petroleum distillates, Isopropanol) FLAMMABLE LIQUID, N.O.S. (Petroleum distillates, Isopropanol) Flammable liquid, n.o.s. (Petroleum distillates, Isopropanol)</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<p></p> <p>3 Flammable liquids</p>
<ul style="list-style-type: none"> · ADR · Class · Label 	<p></p> <p>3 (F1) Flammable liquids 3</p>
<ul style="list-style-type: none"> · IMDG, IATA · Class · Label 	<p></p> <p>3 Flammable liquids 3</p>
<ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA 	<p>II</p>
<ul style="list-style-type: none"> · Environmental hazards · Marine pollutant: 	<p>No</p>
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): 	<p>Warning: Flammable liquids 33</p>

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 10)

· **EMS Number:** F-E,S-E

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

· **ADR**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

· **IATA**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **United States (USA)**

· **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

67-63-0 | propan-2-ol

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

(Cont'd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 11)

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency):**

100-41-4	ethylbenzene	D
----------	--------------	---

· **IARC (International Agency for Research on Cancer):**

100-41-4	ethylbenzene	2B
----------	--------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** June 06, 2017 / -

· **Abbreviations and acronyms:**

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bio-accumulable, Toxique
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: l'Institut national de recherche sur la sécurité et la santé au travail / National Institute for Occupational Safety (États-Unis)
- OSHA: Occupational Safety & Health Administration
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 4: Flammable liquids – Category 4
- Acute Tox. 3: Acute toxicity – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
- Skin Sens. 1B: Skin sensitisation – Category 1B
- Carc. 1B: Carcinogenicity – Category 1B
- Carc. 2: Carcinogenicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1

(Cont'd. on page 13)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: June 06, 2017

Revision: June 06, 2017

Trade name: Gumout Multi-System Tune-Up

(Cont'd. of page 12)

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com