SAFETY DATA SHEET

1. Identification

Product identifier The Right Stuff® Black 90 Minute Gasket

Other means of identification

Synonyms 30873

Recommended useGasket sealant
Recommended restrictions
None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Permatex Canada

Address c/o ITW Global Brands Canada 2360 Bristol Circle, Suite 101

Oakville, ON L6H 6M5

Telephone 905-693-8900

e-mail literature.canada@permatex.com

Emergency phone number 1-877-504-9352
Supplier See above.

2. Hazard identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 1

Sensitization, skin Category 1
Carcinogenicity Category 2
Specific target organ toxicity following Category 2

repeated exposure

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes serious eye damage.

May cause an allergic skin reaction. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe fume.

Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection.

Response Immediately call a POISON CENTER or doctor.

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on

this label).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Storage Store locked up.

Disposal Dispose of container in accordance with local, regional, national and international regulations.

Other hazards None known.

Supplemental information

Exempt - Consumer product

This product is not subject to the Hazardous Products Act (HPA) Part II (Hazardous Products) as per paragraph 12(j); Schedule 1 (Non-Application of Part II). This restriction states that Part II does not apply in respect of the sale or importation of anything listed in Schedule 1 which includes any cosmetic, device, drug or food, as defined in section 2 of the Food and Drugs Act, or any consumer product as defined in section 2 of the Canada Consumer Product Safety Act.

Consult the product label for special protection or precautions that have been identified for using this product under directed use conditions.

3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
2-Butanone, O,O',O''-(ethenylsilylidyne)trioxime		2224-33-1	1 - 5 *
2-Butanone, oxime		96-29-7	0.5 - 1.5 *
Aluminium		7429-90-5	0.1 - 1 *
Carbon black		1333-86-4	0.1 - 1 *
Distillates (petroleum), light hydrotreated		64742-47-8	1 - 10 *

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid me	asures
-----------------	--------

Inhalation

If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

Skin contact

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take

off contaminated clothing and wash it before reuse. Specific treatment (see information on this label).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present Eye contact

and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor.

Ingestion

Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Dermatitis. Rash.

Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Wash contaminated clothing before reuse. Keep out of reach of children.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide.

Not available.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Hazardous combustion products

None known.

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

No unusual fire or explosion hazards noted. General fire hazards

#30546 Page: 2 of 9 Issue date 24-April-2019

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Flood spill with water. Allow material to solidify, and scrape up. Shovel into suitable container for disposal. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Do not discharge into lakes, streams, ponds or public waters.

7. Handling and storage

Precautions for safe handling

Do not get this material in contact with eyes.

Avoid contact with eyes, skin, and clothing.

Provide adequate ventilation. Avoid prolonged exposure.

Wear appropriate personal protective equipment.

Observe good industrial hygiene practices.

Wash thoroughly after handling. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container.

Store away from incompatible materials (see Section 10 of the SDS).

Keep out of reach of children.

Store locked up.

8. Exposure controls/Personal protection

Occupational exposure limits	Occu	pational	exposure	limits
------------------------------	------	----------	----------	--------

JS.	ACGIH	Threshold	Limit Values
-----	--------------	-----------	--------------

Components	Туре	Value	Form	
Aluminium (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.	
Carbon black (CAS	TWA	3 mg/m3	Inhalable fraction.	
1333-86-4)				

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m3 10 mg/m3	Pyrophoric powder. Dust.
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Distillates (petroleum), light hydrotreated (CAS	TWA	200 mg/m3	Vapour.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form	
Aluminium (CAS 7429-90-5)	TWA	1 mg/m3	Respirable.	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.

#30546 Page: 3 of 9 Issue date 24-April-2019

Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment) Components Type Value Aluminium (CAS 7429-90-5) **TWA** 5 ma/m3 Welding fume. 10 mg/m3 Carbon black (CAS **TWA** 3.5 mg/m3 1333-86-4) Distillates (petroleum), light **TWA** 1590 mg/m3 hydrotreated (CAS 64742-47-8) 400 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Canada - Alberta OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS Can be absorbed through the skin.

64742-47-8)

Canada - British Columbia OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS Can be absorbed through the skin.

64742-47-8)

Canada - Saskatchewan OELs: Skin designation

Distillates (petroleum), light hydrotreated (CAS Can be absorbed through the skin.

64742-47-8)

Appropriate engineering

controls

Ensure adequate ventilation.

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Nitrile, butyl rubber or neoprene gloves are recommended. Confirm with a reputable supplier first.

Other As required by employer code.

Individual protection measures, such as personal protective equipment

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respiratory protection

Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134),

CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards Not applicable.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke.

9. Physical and chemical properties

Paste. **Appearance** Solid. Physical state Paste **Form** Colour Black Odour Mild

Odour threshold Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

> 95.0 °C (> 203.0 °F) Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit - upper

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit – upper

Not available.

(%)

Vapour pressure < 5 mm Hg @70°F

#30546 Page: 4 of 9 Issue date 24-April-2019 Vapour density 3 Air = 1 Relative density 1.44

Solubility(ies)

Solubility (Water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidising properties Not oxidising.

VOC (Weight %) < 3 %

10. Stability and reactivity

Reactivity May react with incompatible materials. **Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Do not mix with other chemicals.

Incompatible materials Strong oxidising agents. Acids. Reacts with water.

Hazardous decomposition

products

May include and are not limited to: Oxides of carbon. Oxides of nitrogen. Formaldehyde.

11. Toxicological information

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.Eye contactCauses serious eye damage.

Ingestion May cause stomach distress, nausea or vomiting.

Symptoms related to the physical, chemical and

Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Permanent eye damage including blindness could result.

toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Components Species Test results

2-Butanone, O,O',O"-(ethenylsilylidyne)trioxime (CAS 2224-33-1)

Acute

Dermal

LD50 Rat > 2009 mg/kg, 24 Hours, ECHA

Inhalation

LC50 Not available

Oral

LD50 Rat > 2000 mg/kg, ECHA

4510 mg/kg, ECHA 3519 mg/kg, ECHA

3.5 ml/kg, ECHA

2-Butanone, oxime (CAS 96-29-7)

Acute

Dermal

LD50 Rabbit > 1000 mg/kg, 24 Hours, ECHA

0.2 - 2 ml/kg, 24 Hours, ECHA

Inhalation

LC50 Rat > 10.5 mg/L, 8 Hours, ECHA

> 4.8 mg/L, 4 Hours, ECHA

Components	Species	Test results
<i>Oral</i> LD50	Rat	- 000 mg/kg FCHA
LD90	nai	> 900 mg/kg, ECHA
		2528 mg/kg, ECHA
AL ' ' (0A0 7400 00 5)		2326 mg/kg, ECHA
Aluminium (CAS 7429-90-5)		
Acute Dermal		
LD50	Not available	
Inhalation		
LC50	Rat	> 1000 mg/m3, 4 Hours, CCOHS
		> 2.3 mg/L, 4 Hours, ECHA
		> 0.9 mg/L, 4 Hours, ECHA
		7.6 mg/L, 1 Hours, ECHA
Oral		
LD50	Rat	> 15900 mg/kg, ECHA
		> 10000 mg/kg, ECHA
		> 2000 mg/kg, ECHA
Carbon black (CAS 1333-86-4)		,,
Acute		
Dermal		
LD50	Rabbit	> 3000 mg/kg
Inhalation		
LC50	Not available	
Oral		
LD50	Rat	> 15400 mg/kg
		> 10000 mg/kg, ECHA
		> 8000 mg/kg, ECHA/HSDB
Distillates (petroleum), light hydro	treated (CAS 64742-47-8)	
Acute		
Dermal		
LD50	Rabbit	> 4000 mg/kg, 24 Hours, ECHA
		> 2000 mg/kg
		> 2000 mg/kg, 24 Hours, ECHA
Inhalation		
LC50	Cat	> 6.4 mg/L, 6 Hours, ECHA
	Rat	> 7.5 mg/L, 6 Hours, ECHA
		> 6 mg/L, 4 Hours, ECHA
		> 5.7 mg/L, 4 Hours, ECHA
		> 5.3 mg/L, 4 Hours, ECHA
		> 5.3 mg/L, 4 Hours, ECHA
		> 5.2 mg/L, 4 Hours, ECHA
		> 4.6 mg/L, 4 Hours, ECHA
		> 4.5 mg/L, 4 Hours, ECHA
		> 4.3 mg/L, 4 Hours, ECHA
		> 0.1 mg/L, 8 Hours, ECHA
		5.2 mg/l/4h, LOLI
Oral		<u>.</u>
LD50	Rat	> 20000 mg/kg, ECHA
		> 5000 mg/kg, LOLI
		> 25 ml/kg
Skin corrosion/irritation	Prolonged skin contact may cause tempora	·
Can con osion/intration	i rolongoù skin contact may cause tempora	y mitation.

Exposure minutesNot available.Erythema valueNot available.Oedema valueNot available.

Serious eye damage/eye

irritation

Causes serious eye damage.

Corneal opacity value Not available.

Iris lesion value Not available.

Conjunctival reddening value

Conjunctival oedema value

Recover days

ue Not available.

Not available.

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Aluminium (CAS 7429-90-5) Irritant

Respiratory sensitisation Not a respiratory sensitizer.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity See below.

ACGIH Carcinogens

Aluminium (CAS 7429-90-5)

A4 Not classifiable as a human carcinogen.

Carbon black (CAS 1333-86-4)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

ALUMINUM METAL AND INSOLUBLE COMPOUNDS. Not classifiable as a human carcinogen.

RESPIRABLE FRACTION (CAS 7429-90-5)

CARBON BLACK, INHALABLE FRACTION (CAS Confirmed animal carcinogen with unknown relevance to humans.

1333-86-4)

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4) Volume 65, Volume 93 - 2B Possibly carcinogenic to humans.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure.

Further information Not available.

10	Eggle	-aioo	info	rmation
12.	CCOIC	ouca	HIHO	rmation

			12. Ecological information	
Ecotoxici	ity	See below		
Ecotoxico Compone	ological data ents		Species	Test results
2-Butanor	ne, oxime (CAS 96-	29-7)		
A	Algae	IC50	Algae	83 mg/L, 72 Hours
(Crustacea	EC50	Daphnia	750 mg/L, 48 Hours
	Aquatic			
F	ish	LC50	Fathead minnow (Pimephales promelas)	777 - 914 mg/L, 96 hours
Aluminiun	n (CAS 7429-90-5)			
A	Aquatic			
F	-ish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.16 mg/L, 96 hours
Distillates	(petroleum), light h	nydrotreated (CAS 6	4742-47-8)	
	Aquatic			
(Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/L, 48 hours
F	Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/L, 96 hours

#30546 Page: 7 of 9 Issue date 24-April-2019

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Mobility in soil No data available. Not available. Mobility in general

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Local disposal regulations

Hazardous waste code

Waste from residues / unused

products

Contaminated packaging

Dispose of contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

14. Transport information

Canada: TDG Proof of Classification: Classification Method: Classified as per Part 2, Sections General

2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical

name and the classification of the product will appear below.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory information

Canadian federal regulations

Exempt- consumer product

This product is not subject to the Hazardous Products Act (HPA) Part II (Hazardous Products) as per paragraph 12(j); Schedule 1 (Non-Application of Part II). This restriction states that Part II does not apply in respect of the sale or importation of anything listed in Schedule 1 which includes any cosmetic, device, drug or food, as defined in section 2 of the Food and Drugs Act, or any consumer product as defined in section 2 of the Canada Consumer Product Safety Act.

Canada CEPA Schedule I: Listed substance

2-Butanone, oxime (CAS 96-29-7) Listed. Aluminium (CAS 7429-90-5) Listed.

disposal.

Canada DSL Challenge Substances: Listed substance

2-Butanone, oxime (CAS 96-29-7) Listed Carbon black (CAS 1333-86-4) Listed

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Distillates (petroleum), light hydrotreated (CAS 1 TONNES

64742-47-8)

Canada Priority Substances List (Second List): Listed substance

Aluminium (CAS 7429-90-5) Listed

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS status Controlled International regulations Exempt

Inventory status

Country(s) or region **Inventory Name** On Inventory (Yes/No)*

Canada Domestic Substances List (DSL) No


Canada Non-Domestic Substances List (NDSL) Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	3
FLAMMABILITY		0
PHYSICAL HAZA	ARD	0
PERSONAL PROTECTION		х



Issue date
Revision date
Effective date

24-April-2019 24-April-2019 24-April-2019

Version No.

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Disclaimer

Other information

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Prepared by Dell Tech Laboratories Ltd. Phone: (519) 858-5021