

Revision Date 21-Jul-2015

Version 3

SAFETY DATA SHEET

	1. IDENTIFICATION			
Product identifier				
Product Name	PC COLD WELD METAL EPOXY 56 GR			
Froduct Name				
Other means of identification				
Product Code	84319			
Synonyms	None			
Recommended use of the chemical	and restrictions on use			
Recommended Use	Sealant			
Uses advised against	No information available			
Details of the supplier of the safety	data sheet			
Manufacturer Address	Distributor			
ITW Permatex	ITW Permatex Canada			
10 Columbus Blvd.	35 Brownridge Road, Unit 1			
Hartford, CT 06106 USA	Halton Hills, ON Canada L7G 0C6			
	Telephone: (800) 924-6994			
Company Phone Number	1-87-Permatex			
	(877) 376-2839			
24 Hour Emergency Phone Number				
	International Emergency:			
	00+1+ 813-248-0585			
	Contract Number: MIS0003453			
E-mail address	mail@permatex.com			
	2. HAZARDS IDENTIFICATION			

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A

Label elements

Danger

Emergency Overview

Causes skin irritation Causes serious eye irritation May cause an allergic skin reaction May cause cancer



Appearance Gray

Physical state Solid

Odor Pungent sulfur

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

61.5 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
MAGNESIUM SILICATE	14807-96-6	30 - 60	*
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN	25068-38-6	10 - 30	*
GLASS OXIDE	65997-17-3	10 - 30	*
FERROSILICON	8049-17-0	10 - 30	*
NEPHELINE SYENITE	37244-96-5	1 - 5	*
SILICA, QUARTZ	14808-60-7	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Description of first aid measures			
General advice	Get medical advice/attention if you feel unwell.		
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.		
Skin contact	IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.		
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.		
Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.		
Self-protection of the first aider	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.		
Most important symptoms and effe	ects, both acute and delayed		
Symptoms	See section 2 for more information.		
Indication of any immediate medic	al attention and special treatment needed		
Note to physicians	Treat symptomatically.		
	5. FIRE-FIGHTING MEASURES		
<u>Suitable extinguishing media</u> Carbon dioxide (CO2), Dry chemical,	Foam		
<u>Unsuitable extinguishing media</u> None.			
Specific hazards arising from the on None in particular.	chemical		
<u>Explosion data</u> Sensitivity to Mechanical Impact Sensitivity to Static Discharge	None. None.		
Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.			
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions, protective equipment and emergency procedures			
Personal precautions	Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required.		
Environmental precautions			
Environmental precautions	Do not flush into surface water or sanitary sewer system. Collect spillage. See Section 12 for additional ecological information.		

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up	Ensure adequate ventilation. Sweep up and shovel into suitable containers for disposal.	
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.	
	7. HANDLING AND STORAGE	
Precautions for safe handling		
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.	
Conditions for safe storage, including any incompatibilities		
Storage Conditions	Store locked up.	
Incompatible materials	Strong oxidizing agents	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Exposure Guidelines			
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
MAGNESIUM SILICATE 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
GLASS OXIDE 65997-17-3	TWA: 1 fiber/cm3 respirable fibers: length >5 μm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m ³ inhalable fraction	-	-
SILICA, QUARTZ 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	 (vacated) TWA: 0.1 mg/m³ respirable dust : (30)/(%SiO2 + 2) mg/m³ TWA total dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction 	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers
	Eyewash stations
	Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Odor Odor threshold	Solid Gray Pungent sulfur No information available	
<u>Property</u> pH Melting point / freezing point Pailing point / bailing same	<u>Values</u> No information available No information available	<u>Remarks • Method</u>
Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas)	> 93 °C / > 200 °F Not applicable No information available	Setaflash Closed Cup
Flammability Limit in Air Upper flammability limit: Lower flammability limit: Vapor pressure	No information available No information available No information available	
Vapor density Relative density Water solubility Solubility in other solvents	No information available 2.25 No information available No information available	
Partition coefficient Autoignition temperature Decomposition temperature	No information available No information available >200°C (>392°F)	
Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties	No information available No information available No information available No information available	
Other Information		
Softening point Molecular weight VOC Content (%) Density Bulk density	No information available No information available 0 No information available No information available	

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid Excessive heat.

Incompatible materials

Hazardous Decomposition Products Carbon oxides Oxides of sulfur Metal oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.				
Eye contact	Contact with eyes may ca	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.			
Skin contact	May cause skin irritation a	May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.			
Ingestion	Ingestion may cause irrita	Ingestion may cause irritation to mucous membranes.			
Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50		
BISPHENOL	= 11400 mg/kg (Rat)	-	-		

onennoarmanie		Dermai ED00		
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN 25068-38-6	= 11400 mg/kg(Rat)	-	-	
FERROSILICON 8049-17-0	-	> 20 g/kg (Rabbit)	-	
SILICA, QUARTZ 14808-60-7	= 500 mg/kg (Rat)	-	-	

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No informatio	on available.		
Germ cell mutagenicity	No information available.			
Carcinogenicity	The table bel	ow indicates whether each	n agency has listed any ing	redient as a carcinogen.
Chemical Name	ACGIH	IARC	NTP	OSHA
MAGNESIUM SILICATE 14807-96-6	-	Group 3	-	-
GLASS OXIDE 65997-17-3	-	Group 3	-	-
SILICA, QUARTZ 14808-60-7	A2	Group 1	Known	Х
Group 1 - Carcinogenic to Not classifiable as a hum NTP (National Toxicolog Known - Known Carcinog OSHA (Occupational Sa X - Present	ency for Research on Cance o Humans an carcinogen gy Program) gen afety and Health Administra	tion of the US Department c		
Target Organ Effects Central Vascular System (CVS), Eyes, Respiratory system.				
The following values are ATEmix (oral) ATEmix (dermal)	calculated based on cha 21945 mg/kg 42821 mg/kg	<u>)</u>	ument .	

12. ECOLOGICAL INFORMATION

Ecotoxicity

39 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name Algae/aguatic plants Fish Crustacea

MAGNESIUM SILICATE	-	100: 96 h Brachydanio rerio g/L	-
14807-96-6		LC50 semi-static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	Not applicable

14. TRANSPORT INFORMATION

DOT Proper shipping name:	Not regulated
IATA Proper shipping name:	Not regulated
IMDG Proper shipping name:	Not regulated

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Not determined
ENCS	Not determined
IECSC	Not determined
KECL	Not determined
PICCS	Not determined
AICS	Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
SILICA, QUARTZ - 14808-60-7	Carcinogen	
LLS State Dight to Know Degulations		

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
MAGNESIUM SILICATE 14807-96-6	Х	X	Х
FERROSILICON 8049-17-0	Х	-	-
SILICA, QUARTZ 14808-60-7	Х	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

<u>NFPA</u>	Health hazards 2	Flammability 1	Instability 0	-
HMIS	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 21-Jul-2015

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet