# **Permatex.**

# SAFETY DATA SHEET

Revision Date 18-Apr-2016 Version 2

# 1. IDENTIFICATION

**Product identifier** 

Product Name VERSACHEM SPIDERPATCH MUFFLER TAILPIPE BANDAGE JUMBO

Other means of identification

**Product Code** 90332 **Synonyms** None

Recommended use of the chemical and restrictions on use
Recommended Use Automotive Care Product
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address <u>Distributor</u>

ITW PermatexITW Permatex Canada6875 Parkland Blvd.35 Brownridge Road, Unit 1Solon, OH 44139 USAHalton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

#### Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

#### Label elements

#### **Emergency Overview**

#### Warning

Causes skin irritation Causes serious eye irritation May cause an allergic skin reaction



Appearance White Physical state Solid Odor Ketone

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace

#### **Precautionary Statements - Response**

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water

Take off contemprated elething and wash before rouse.

Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention

# **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

- Not applicable

Unknown acute toxicity 62.5 % of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN	25068-38-6	25-50	*
METHYL ETHYL KETONE (BUTANONE)	78-93-3	<3	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

# **Description of first aid measures**

**General advice** Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Revision Date 18-Apr-2016

\_\_\_\_\_

**Skin contact** IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians**Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

**Explosion data** 

**Sensitivity to Mechanical Impact** None. **Sensitivity to Static Discharge** None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**Ensure adequate ventilation. Sweep up and shovel into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 7. HANDLING AND STORAGE

Precautions for safe handling

# 90332 - VERSACHEM SPIDERPATCH MUFFLER TAILPIPE BANDAGE JUMBO

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials Strong oxidizing agents, Reducing agent

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
METHYL ETHYL KETONE	STEL: 300 ppm	TWA: 200 ppm	IDLH: 3000 ppm
(BUTANONE)	TWA: 200 ppm	TWA: 590 mg/m <sup>3</sup>	TWA: 200 ppm
78-93-3		(vacated) TWA: 200 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 590 mg/m <sup>3</sup>	STEL: 300 ppm
		(vacated) STEL: 300 ppm	STEL: 885 mg/m <sup>3</sup>
		(vacated) STEL: 885 mg/m <sup>3</sup>	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection**Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Physical state Solid
Appearance White
Odor Ketone

Odor threshold No information available

Property Values Remarks • Method

pH No information available
Melting point / freezing point
Boiling point / boiling range
Flash point
Evaporation rate
Flammability (solid, gas)
No information available
No information available
No information available
No information available

# 90332 - VERSACHEM SPIDERPATCH MUFFLER **TAILPIPE BANDAGE JUMBO**

Flammability Limit in Air

**Upper flammability limit:** No information available Lower flammability limit: No information available No information available Vapor pressure Vapor density No information available Relative density No information available Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available **Oxidizing properties** No information available

**Other Information** 

Softening point No information available Molecular weight No information available

**VOC Content (%)** 1.5%

No information available **Density Bulk density** No information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### Chemical stability

Stable under recommended storage conditions

#### Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

Excessive heat.

#### Incompatible materials

Strong oxidizing agents, Reducing agent

#### **Hazardous Decomposition Products**

Carbon oxides

Ketones and their derivatives

Hydrogen fluoride

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Contact with eyes may cause irritation. May cause redness and tearing of the eyes. Eye contact

May cause skin irritation and/or dermatitis. May cause sensitization by skin contact. Skin contact

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
BISPHENOL	= 11400 mg/kg (Rat)	-	<del>-</del>
A/EPICHLOROHYDRIN BASED			

Revision Date 18-Apr-2016

EPOXY RESIN 25068-38-6			
METHYL ETHYL KETONE (BUTANONE) 78-93-3	= 2483 mg/kg ( Rat ) = 2737 mg/kg ( Rat )	= 5000 mg/kg ( Rabbit ) = 6480 mg/kg ( Rabbit )	= 11700 ppm(Rat)4 h

Information on toxicological effects

**Symptoms** No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 9968 mg/kg

 ATEmix (dermal)
 125000 mg/kg

 ATEmix (inhalation-vapor)
 292500 mg/l

# 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

62.5 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
METHYL ETHYL KETONE	-	3130 - 3320: 96 h Pimephales	520: 48 h Daphnia magna mg/L
(BUTANONE)		promelas mg/L LC50 flow-through	EC50 5091: 48 h Daphnia magna
78-93-3			mg/L EC50 4025 - 6440: 48 h
			Daphnia magna mg/L EC50 Static

#### Persistence and degradability

No information available.

## **Bioaccumulation**

No information available.

#### **Mobility**

No information available.

Chemical Name	Partition coefficient
METHYL ETHYL KETONE (BUTANONE)	0.29
78-93-3	

#### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

# 90332 - VERSACHEM SPIDERPATCH MUFFLER TAILPIPE BANDAGE JUMBO

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ETHYL KETONE	U159		200.0 mg/L regulatory level	U159
(BUTANONE)		F005, F039		
78-93-3				

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
METHYL ETHYL KETONE (BUTANONE)	Toxic
78-93-3	Ignitable

# 14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

<u>IATA</u>

Proper shipping name: Not regulated

**IMDG** 

Proper shipping name: Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies Complies **EINECS/ELINCS** Complies **ENCS IECSC** Complies Complies **KECL** Complies **PICCS** Complies **AICS** 

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Revision Date 18-Apr-2016

# **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHYL ETHYL KETONE	5000 lb	=	RQ 5000 lb final RQ
(BUTANONE)			RQ 2270 kg final RQ
78-93-3			

# **US State Regulations**

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
METHYL ETHYL KETONE	X	X	X
(BUTANONE)			
78-93-3			

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

#### **WHMIS Hazard Class**

D2B - Toxic materials

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 1 Instability 0 -

HMIS Health hazards 1 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 18-Apr-2016

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**