

Isopropyl Alcohol, Fuel Injection Gas Line Antifreeze

SECTION 1. IDENTIFICATION

Product Identifier	Isopropyl Alcohol, Fuel Injection Gas Line Antifreeze
Other Means of Identification	25-139, 15-316, 44-078
Other Identification	Fuel Injection Gas Line Antifreeze
Recommended Use	Please refer to Product label.
Restrictions on Use	None known.
Manufacturer / Supplier	Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory Department, 905-878-5544, www.recochem.com
Emergency Phone No.	CANUTEC, 613-996-6666, 24 Hours
SDS No.	1522

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquid - Category 2; Serious eye damage/eye irritation - Category 2A; Specific target organ toxicity (single exposure) - Category 3

GHS Label Elements



Signal Word:

Danger

Hazard Statement(s):

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statement(s):

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, lighting, and other equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust, fume, gas, mist, vapours or spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/eye protection/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

Product Identifier: Isopropyl Alcohol, Fuel Injection Gas Line Antifreeze

SDS No.: 1522

Date of Preparation: August 17, 2015

and easy to do. Continue rinsing.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/attention. carbon dioxide
dry chemical powder
water spray or fog

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Other Hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance:

Chemical Name	CAS No.	%	Other Identifiers
2-Propanol	67-63-0	60-100	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Move to fresh air. Call a Poison Centre or doctor if you feel unwell or are concerned.

Skin Contact

Immediately wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 15-20 minutes. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely. Call a Poison Centre or doctor if you feel unwell or are concerned.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. If eye irritation persists, get medical advice/attention.

Ingestion

Rinse mouth with water. Call a Poison Centre or doctor if you feel unwell or are concerned. Do not induce vomiting.

First-aid Comments

Get medical advice/attention if you feel unwell or are concerned.

Most Important Symptoms and Effects, Acute and Delayed

None known.

Immediate Medical Attention and Special Treatment

Target Organs

Skin, nervous system, eyes.

Special Instructions

Not applicable.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Small fire: Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog. Large fire: Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

Product Identifier: Isopropyl Alcohol, Fuel Injection Gas Line Antifreeze

SDS No.: 1522

Page 02 of 07

Date of Preparation: August 17, 2015

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Chemical

Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapour forms explosive mixture with air between upper and lower flammable limits.

Not known to generate any hazardous decomposition products in a fire.

Special Protective Equipment and Precautions for Fire-fighters

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills.

Fire-fighters should enter area wearing specialized protective equipment. (Bunker Gear will not provide adequate protection.).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, if ventilation is not sufficient. Eliminate all ignition sources. Use grounded, explosion-proof equipment. Use the personal protective equipment recommended in Section 8 of this safety data sheet. Evacuate downwind locations.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for Safe Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA

Product Identifier: Isopropyl Alcohol, Fuel Injection Gas Line Antifreeze

SDS No.: 1522

Page 03 of 07

Date of Preparation: August 17, 2015

2-Propanol	200 ppm	400 ppm	400 ppm	500 ppm		
------------	---------	---------	---------	---------	--	--

Appropriate Engineering Controls

Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Control static electricity discharges which includes bonding of equipment to ground. Provide eyewash and safety shower if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles and face shield when contact is possible.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

Respiratory Protection

Wear a NIOSH approved air-purifying respirator with an appropriate cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear liquid. Particle Size: Not available
Odour	Alcoholic
Odour Threshold	7.6 - 49 ppm (18.6 - 120.2 mg/m ³)
pH	Not available
Melting Point/Freezing Point	-88.9 °C (-128.0 °F) (melting); -88.9 °C (-128.0 °F) (freezing)
Initial Boiling Point/Range	82.5 °C (180.5 °F)
Flash Point	11.85 °C (53.33 °F) (closed cup)
Evaporation Rate	1.5 (n-butyl acetate = 1)
Flammability (solid, gas)	Not applicable
Upper/Lower Flammability or Explosive Limit	12% (upper); 2% (lower)
Vapour Pressure	44.3 mm Hg (5.9 kPa) at 20 °C
Vapour Density (air = 1)	2.07
Relative Density (water = 1)	0.785 at 20 °C
Solubility	Soluble in water; Soluble in all proportions in common organic solvents.
Partition Coefficient, n-Octanol/Water (Log K _{ow})	0.05 at 20 °C
Auto-ignition Temperature	399 °C (750 °F)
Decomposition Temperature	Not available
Viscosity	2.61 mm ² /s at 25 °C (kinematic); 2.04 mPa.s at 20 °C (dynamic)
Other Information	
Physical State	Liquid
Molecular Weight	60.09

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

Product Identifier: Isopropyl Alcohol, Fuel Injection Gas Line Antifreeze
SDS No.: 1522
Date of Preparation: August 17, 2015

None known.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources. Light. Prolonged storage. Temperatures above 12.0 °C (53.6 °F)

Incompatible Materials

Increased risk of fire and explosion on contact with: strong oxidizing agents (e.g. perchloric acid). Reacts violently with: strong acids (e.g. hydrochloric acid), acid anhydrides (e.g. acetic anhydride).

Not corrosive to metals.

Hazardous Decomposition Products

None known.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin absorption; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
2-Propanol	17000 ppm (rat) (4-hour exposure)	3600 mg/kg (mouse)	12890 mg/kg (rabbit)

Skin Corrosion/Irritation

Human experience and animal tests show no or very mild irritation.

Serious Eye Damage/Irritation

Animal tests show serious eye irritation. The vapour also irritates the eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

Harmful based on animal tests. Severe nose and throat irritation. At high concentrations depression of the central nervous system, harmful effects on the liver, lung injury.

May be harmful based on human experience. At low concentrations nose and throat irritation.

Skin Absorption

May be harmful At high concentrations.

Ingestion

May be harmful If large amounts are swallowed based on animal tests.

Aspiration Hazard

No information was located.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Causes If inhaled: effects on the central nervous system, harmful effects on the kidneys, harmful effects on the liver.

Causes If swallowed: at high concentrations harmful effects on the liver, harmful effects on the kidneys.

May cause Following skin contact: at high concentrations harmful effects on the heart.

Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
2-Propanol	Group 3	A4	Not Listed	Not Listed

Not known to cause cancer.

Reproductive Toxicity

Development of Offspring

May harm the unborn child. However, these effects are only seen with significant toxicity in the mothers. If

Product Identifier: Isopropyl Alcohol, Fuel Injection Gas Line Antifreeze

SDS No.: 1522

Page 05 of 07

Date of Preparation: August 17, 2015

swallowed: has been associated with: decreased weight. May harm the unborn child. However, these effects are only seen with significant toxicity in the mothers. If inhaled: decreased weight. Embryotoxic (late resorptions).

Sexual Function and Fertility

Animal studies show effects on sexual function and/or fertility. However, these effects were seen in the presence of significant other toxicity. Has been associated with: effects in men. Animal studies show effects on sexual function and/or fertility. However, these effects were seen in the presence of significant other toxicity. If inhaled: effects in women.

Effects on or via Lactation

Does not cause effects on or via lactation.

Germ Cell Mutagenicity

Conclusions cannot be drawn from the limited studies available.

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
2-Propanol	9640 mg/L (Pimephales promelas (fathead minnow); 96-hour)	7500-13299 mg/L (Daphnia magna (water flea); 48-hour)		> 2000 mg/L (Pseudokirchneriella subcapitata (algae); 72-hour)

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

Other Adverse Effects

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	1219	ISOPROPANOL; OR ISOPROPYL ALCOHOL	3	II
US DOT	1219	ISOPROPANOL; OR ISOPROPYL ALCOHOL	3	II

Environmental Hazards

Not applicable

Product Identifier: Isopropyl Alcohol, Fuel Injection Gas Line Antifreeze

SDS No.: 1522

Page 06 of 07

Date of Preparation: August 17, 2015

Special Precautions for User Please note: In containers of 1 L (1Kg) capacity or less this product is classified as a "Limited Quantities""Consumer Commodity" under TDG regulations.
IB2, T4, TP1. In containers of 1 L (1Kg) this product is qualified as a "consumer commodity" ORM-D under DOT

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Listed on the DSL.

CEPA - National Pollutant Release Inventory (NPRI)

Part 1A.

Part 5.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

Listed on the TSCA Inventory.

Additional USA Regulatory Lists

New Jersey Right To Know: F3.

SECTION 16. OTHER INFORMATION

SDS Prepared By Compliance and Regulatory Department

Phone No. 905-878-5544

Date of Preparation August 17, 2015

Additional Information We are committed to uphold the Industry Consumer Ingredient Communication Voluntary Initiative.
Please send us your request by visiting our website at www.recochem.com.

Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without respect to order of predominance.

Disclaimer

Notice to reader: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Product Identifier: Isopropyl Alcohol, Fuel Injection Gas Line Antifreeze

SDS No.: 1522

Page 07 of 07

Date of Preparation: August 17, 2015