SAFETY DATA SHEET

WL09010CN

Section 1. Identification

Product name	: WHITE LIGHTNING® Silicone RTV All Purpose Sealant Clear
Product code	: WL09010CN
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Not applicable.	
Manufacturer	: White Lightning Products 180 Brunel Road Mississauga, ON L4Z 1T5
Emergency telephone number of the company	: (216) 566-2917
Product Information Telephone Number	: Not available.
Regulatory Information Telephone Number	: (216) 566-2902
Transportation Emergency Telephone Number	: (800) 424-9300

Section 2. Hazards identification

Classification of the	: SKIN CORROSION/IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
substance or mixture	SERIOUS ETE DAMAGE/ ETE IRRITATION - Calegory 1 SKIN SENSITIZATION - Category 1
	TOXIC TO REPRODUCTION (Fertility) - Category 1B
	TOXIC TO REPRODUCTION (Unborn child) - Category 1B
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract
	irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -
	Category 3
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	ASPIRATION HAZARD - Category 1
	Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 25.6% Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 38.4% Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 12. 8%
GHS label elements	
Hazard pictograms	
Signal word	: Danger

Section 2. Hazards identification

Hazard statements Precautionary statements	 Causes severe skin burns and eye damage. May cause an allergic skin reaction. May damage fertility or the unborn child. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Please refer to the SDS for additional information. Keep out of reach of children. Do
	not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Middle Petroleum Distillates	25.58	64742-46-7
Amorphous Silica	11.51	7631-86-9
Methyl Triacetoxysilane	6.39	4253-34-3
Ethyl Triacetoxysilane	6.39	17689-77-9
Dibutyltin Dilaurate	0.13	77-58-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date	ate of revision	: 4/17/2018	Date of previous issue	: 3/27/2018	Version : 4
WL09010CN	WHITE LIGHTNING Clear	G® Silicone RTV A	Il Purpose Sealant		SHW-85-NA-GHS-CA

2/13

Section 4. First aid measures

Description of necess	ary first aid measures
Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	: Causes serious eye damage.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
Over-exposure signs/sympto	i <u>ms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations

: 3/27/2018

Section 4. First aid measures

Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur			
	reduced fetal weight increase in fetal deaths skeletal malformations			
Ingestion	Adverse symptoms may include the following: stomach pains nausea or vomiting reduced fetal weight increase in fetal deaths skeletal malformations			
Indication of immediate me	dical attention and special treatment needed, if necessary			
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 			
Specific treatments	: No specific treatment.			
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.			

See toxicological information (Section 11)

Section 5. Fire-fighting measures

	_
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Clear

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Evacuate su entering. De Provide ade	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.			
For emergency responders		n suitable and unsuitable		e, take note of any inform o the information in "For i	
Date of issue/Date of revision	: 4/17/2018	Date of previous issue	: 3/27/2018	Version : 4	4/13
WL09010CN WHITE LIGHTNIN	G® Silicone RTV A	ll Purpose Sealant		SHW-85-NA-GHS-C	Α

Section 6. Accidental release measures

Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name			Exposure limi	ts	
Middle Petroleum Distillates			TWA: 5 mg/m	nited States, 10/2016). ³ 10 hours. Form: Mist m ³ 15 minutes. Form: Mist	
Amorphous Silica			-	nited States, 10/2016).	
Methyl Triacetoxysilane			None.		
Ethyl Triacetoxysilane			None.		
Dibutyltin Dilaurate			ACGIH TLV (U	nited States, 3/2017).	
Date of issue/Date of revision	: 4/17/2018	Date of previous issue	: 3/27/2018	Version : 4	5/13
VL09010CN WHITE LIGHTNII Clear	NG® Silicone RTV Al	l Purpose Sealant		SHW-85-NA-GHS-CA	

Section 8. Exposure controls/personal protection

Absorbed through skin.
TWA: 0.1 mg/m³, (as Sn) 8 hours.
STEL: 0.2 mg/m ³ , (as Sn) 15 minutes.
NIOSH REL (United States, 10/2016).
Absorbed through skin.
TWA: 0.1 mg/m ³ , (as Sn) 10 hours.
OSHA PEL (United States, 6/2016).
TWA: 0.1 mg/m³, (as Sn) 8 hours.
3 7 7

Occupational exposure limits (Canada)

Ingredient name	Exposure limits
Middle Petroleum Distillates	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 5 mg/m ³ 8 hours. Form: Mist 15 min OEL: 10 mg/m ³ 15 minutes. Form: Mist CA Quebec Provincial (Canada, 1/2014). TWAEV: 5 mg/m ³ 8 hours. Form: mist STEV: 10 mg/m ³ 15 minutes. Form: mist
Dibutyltin Dilaurate	 CA Alberta Provincial (Canada, 4/2009). Absorbed through skin. 15 min OEL: 0.2 mg/m³, (as Sn) 15 minutes. 8 hrs OEL: 0.1 mg/m³, (as Sn) 8 hours. CA British Columbia Provincial (Canada, 6/2017). Absorbed through skin. TWA: 0.1 mg/m³, (as Sn) 8 hours. STEL: 0.2 mg/m³, (as Sn) 15 minutes. CA Quebec Provincial (Canada, 1/2014). Absorbed through skin. TWAEV: 0.1 mg/m³, (as Sn) 8 hours. STEV: 0.2 mg/m³, (as Sn) 15 minutes. CA Ontario Provincial (Canada, 7/2015). Absorbed through skin. TWA: 0.1 mg/m³, (as Sn) 8 hours. STEL: 0.2 mg/m³, (as Sn) 15 minutes. CA Saskatchewan Provincial (Canada, 7/2015). Absorbed through skin. TWA: 0.1 mg/m³, (measured as Sn) 15 minutes. TWA: 0.1 mg/m³, (measured as Sn) 8 hours.

Occupational exposure limits (Mexico)

Ingredient name	Exposure limits
Middle Petroleum Distillates	NOM-010-STPS-2014 (Mexico, 4/2016).
	TWA: 5 mg/m ³ 8 hours. Form: mist
Dibutyltin Dilaurate	NOM-010-STPS-2014 (Mexico, 4/2016).
	Absorbed through skin.
	TWA: 0.1 mg/m ³ , (as Sn) 8 hours.
	STEL: 0.2 mg/m³, (as Sn) 15 minutes.

Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Date of issue/Date of revision	: 4/17/2018	Date of previous issue	: 3/27/2018	Version : 4	6/13
WL09010CN WHITE LIGHTNING® Clear	Silicone RTV A	All Purpose Sealant		SHW-85-NA-GHS-CA	

Section 8. Exposure controls/personal protection

	• •
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Not available.
Boiling point	: 171°C (339.8°F)
Flash point	: Closed cup: >93.3°C (>199.9°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: 0.02 kPa (0.15 mm Hg) [at 20°C]
Vapor density	: Not available.
Relative density	: 1
Solubility	: Not available.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
Molecular weight	: Not applicable.

Date of issue/Date	of revision	: 4/17/2018	Date of previous issue	: 3/27/2018	Version	:4	7/13
WL09010CN	WHITE LIGHTNING® S Clear	Silicone RTV All	Purpose Sealant		SHW-85-	NA-GHS-CA	

Section 9. Physical and chemical properties

Aerosol product

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
Methyl Triacetoxysilane Dibutyltin Dilaurate	LD50 Oral LD50 Oral	Rat Rat	2060 mg/kg 2071 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Amorphous Silica	Eyes - Mild irritant	Rabbit	-	24 hours 25 milligrams	-
Dibutyltin Dilaurate	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Skin - Severe irritant	Rabbit	-	500 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Amorphous Silica	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Date of issue/Date	of revision	: 4/17/2018	Date of previous issue	: 3/27/2018	Version	:4
WL09010CN	WHITE LIGHTNING® S Clear	Silicone RTV All	Purpose Sealant		SHW-85-I	NA-

Name		Category		oute of cposure	Target organs
Middle Petroleum Distilla	Category 3	N	ot applicable.	Respiratory tract irritation and	
Dibutyltin Dilaurate	Category 1	N	ot determined	Narcotic effects Not determined	
Specific target organ to	xicity (repeated exposure)				
Name		Category		oute of cposure	Target organs
Middle Petroleum Distilla Dibutyltin Dilaurate	ites	Category 2 Category 1		ot determined ral	Not determined Not determined
Aspiration hazard			•		
Name			Result		
Middle Petroleum Distilla	ites		ASPIRA	TION HAZARD	- Category 1
formation on the likely outes of exposure					
otential acute health eff					
ye contact	: Causes serious eye dama	•			
halation	: Can cause central nervou dizziness. May cause res	is system (CNS) de	epression	n. May cause d	rowsiness or
kin contact	: Causes severe burns. Ma		c skin re	action.	
gestion	: Can cause central nervou	us system (CNS) de	anraesior	May ha fatal	f annallanna d'anad
	enters airways.		501633101	i. May be latai	It swallowed and
	physical, chemical and toxic	ological characte	ristics	i. May be latar	IT SWAIIOWED AND
<u>ymptoms related to the</u> ye contact		ological characte	ristics	i. May de latar	ir swallowed and
	 physical, chemical and toxic Adverse symptoms may in pain watering 	ological characte nclude the followin	ristics g:	i. May de latai	IT SWAIIOWED and
ye contact	 physical, chemical and toxic Adverse symptoms may in pain watering redness Adverse symptoms may in respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths 	ological characte nclude the followin	ristics g: g:	1. May de lata	IT SWAIIOWED and

Date of issue/Date	of revision	4/17/2018	Date of previous issue	
WL09010CN	WHITE LIGHTNING® S Clear	Silicone RTV All	Purpose Sealant	

Delayed and immediate effects and also chronic effects from short and long term exposure					
Short term exposure					
Potential immediate effects	: Not available.				
Potential delayed effects	: Not available.				
Long term exposure					
Potential immediate effects	: Not available.				
Potential delayed effects	: Not available.				
Potential chronic health et	<u>fects</u>				
Not available.					
General	 May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. 				
Carcinogenicity	: No known significant effects or critical hazards.				
Mutagenicity	: No known significant effects or critical hazards.				
Teratogenicity	: May damage the unborn child.				
Developmental effects	: No known significant effects or critical hazards.				
Fertility effects	: May damage fertility.				

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	2910 mg/kg
Inhalation (vapors)	37.51 mg/l

Section 12. Ecological information

Toxicity			
Product/ingredient name	Result	Species	Exposure
Dibutyltin Dilaurate	Chronic EC10 >2 mg/l Fresh water	Algae - Scenedesmus subspicatus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Dibutyltin Dilaurate	-	2.91	low

Mobility in soil

Soil/water partition : Not available. coefficient (K_{oc})

Other adverse effects : No known significant effects or critical hazards.

Date of issue/Date	of revision	: 4/17/2018	Date of previous issue	: 3/27/2018	Version	:4	10/13
WL09010CN	WHITE LIGHTNING®	Silicone RTV AI	I Purpose Sealant		SHW-85-	NA-GHS-CA	

Section 13. Disposal considerations

Disposal methods	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
------------------	--

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.
 Transport in bulk according : Not available.

to Annex II of MARPOL and the IBC Code	. Not available.	
	Proper shipping name	: No
	Ship type	: No
	Pollution category	• No

Not available.Not available.

: Not available.

Section 15. Regulatory information

SARA 313


SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

Date of issue/Date	of revision	: 4/17/2018	Date of previous issue	: 3/27/2018	Version	:4	11/13
WL09010CN	WHITE LIGHTNING® Clear	Silicone RTV Al	l Purpose Sealant		SHW-85-	NA-GHS-CA	

Not applicable.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 1	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
TOXIC TO REPRODUCTION (Fertility) - Category 1B	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1	Calculation method Calculation method

<u>History</u>	
Date of printing	: 4/17/2018
Date of issue/Date of revision	: 4/17/2018
Date of previous issue	: 3/27/2018
Version	: 4
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to

Date of issue/Date	of revision	: 4/17/2018	Date of previous issue	: 3/27/2018	Version : 4	12/13
WL09010CN WHITE LIGHTNING® Silicone RTV All Purpose Sealant Clear			SHW-85-NA-GHS-CA			

Section 16. Other information

determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.