

Revision Number: 002.0 Issue date: 03/01/2018

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: TEROSON SI 9160 ALM known as IDH number: 475375

SILATECH® SILICONE SEALANT IND

Product type: Silicone Restriction of Use: None identified

Company address: Henkel Canada Corporation

Meadow pine Boulevard 2515 Mississauga, Ontario L5N 6C3

Item number: 32392 Region: Canada Contact information:

Telephone: +1 (905) 814-6511

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1

#### PICTOGRAM(S)



#### **Precautionary Statements**

Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face Prevention:

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation

occurs: Get medical attention. Take off contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Distillates (petroleum), hydrotreated middle	64742-46-7	5 - 10
Silicon dioxide	7631-86-9	5 - 10

IDH number: 475375 Product name: TEROSON SI 9160 ALM known as SILATECH® SILICONE SEALANT IND

Methylsilanetriyl triacetate	4253-34-3	1 - 5
Triacetoxyethylsilane	17689-77-9	1 - 5
Acetic acid	64-19-7	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

# 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:** Wipe off paste w ith paper towel or cloth. Wash w ith soap and w ater.

Eye contact: Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation

persists, consult a specialist.

Ingestion: Do not induce vomiting. If a person feels unwell or symptoms of skin irritation

appear, consult a physician.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

IDH number: 475375

Hazardous combustion products: Formaldehyde. Silica mist. Acrid smoke and fumes.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sew er or waterways.

Clean-up methods: Scrape up as much material as possible. Spilled material will solidify. Store in

a partly filled, closed container until disposal. Maintain good ventilation for

large spills.

# 7. HANDLING AND STORAGE

Handling: Do not handle contact lenses until all sealant has been removed from hands.

Residual sealant may transfer to lenses and cause eye irritation. Avoid contact

with eyes, skin and clothing.

Storage: Keep container closed. Store in a dry area below 90° F.

Shelf Life Statement: Not available.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Product name: TEROSON SI 9160 ALM known as SILATECH® SILICONE SEALANT IND

Page 2 of 5

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated middle	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist.	None	None
Silicon dioxide	6 mg/m3 TWA	20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
Methylsilanetriyl triacetate	None	None	None	None
Triacetoxyethylsilane	None	None	None	None
Acetic acid	15 ppm STEL 10 ppm TWA	10 ppm (25 mg/m3) PEL	None	None

Engineering controls: Use only with adequate ventilation.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). No personal respiratory protective equipment normally required.

Eye/face protection: Safety goggles or safety glasses with side shields.

**Skin protection:** Chemical resistant, impermeable gloves.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Color: Aluminum Odor: Acetic acid Odor threshold: Not available. pH: Not available. Vapor pressure: Not available. Boiling point/range: Not available. Melting point/range: Not available. Specific gravity: 1.01 at 20 °C (68°F) Vapor density: Heavier than air. Flash point: > 93 °C (> 199.4 °F) Flam mable/Explosive limits - low er: 4 % (acetic acid) Flammable/Explosive limits - upper: 19.9 % (acetic acid) Autoignition temperature: Not available. Flam mability: Not applicable Evaporation rate: Not available.

**Solubility in water:** Not soluble. Polymerizes in presence of water.

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not available.

Not available.

Not available.

#### 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 475375

Acetic acid is liberated slow ly upon contact with moisture. Formaldehyde.

Incompatible materials: Acids. Water Oxidizing agents. Bases.

**Reactivity:** Not available.

Conditions to avoid: Prolonged heating at temperatures above 150 °C. Exposure to moisture.

#### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Product name: TEROSON SI 9160 ALM known as SILATECH® SILICONE SEALANT IND Page 3 of 5

#### Potential Health Effects/Symptoms

**Inhalation:** May cause respiratory tract irritation.

Skin contact: Causes skin irritation.
Eye contact: Causes serious eye irritation.

Ingestion: Not a relevant route of exposure. May cause gastrointestinal tract irritation if sw allowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Distillates (petroleum), hydrotreated middle	None	Irritant	
Silicon dioxide	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg	Nuisance dust	
Methylsilanetriyl triacetate	None	Irritant, Allergen	
Triacetoxyethylsilane	None	No Target Organs	
Acetic acid	Oral LD50 (Rabbit) = 1,200 mg/kg Oral LD50 (Mouse) = 4,960 mg/kg Oral LD50 (Rat) = 3.53 g/kg Oral LD50 (Rat) = 3.31 g/kg Dermal LD50 (Rabbit) = 1,060 mg/kg Inhalation LC50 (Rat, 4 h) = 11.4 mg/l	Allergen, Corrosive, Eyes, Gastrointestinal, Immune system, Irritant, Kidney	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated middle	No	No	No
Silicon dioxide	No	No	No
Methylsilanetriyl triacetate	No	No	No
Triacetoxyethylsilane	No	No	No
Acetic acid	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Cured rubber can be incinerated or landfilled following EPA and local

regulations. Follow all local, state, federal and provincial regulations for

disposal.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None
None

IDH number: 475375 Product name: TEROSON SI 9160 ALM known as SILATECH® SILICONE SEALANT IND Page 4 of 5

Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None
None

# 15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

# **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

**Prepared by:** Product Safety and Regulatory Affairs

Issue date: 03/01/2018

IDH number: 475375

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising fromsale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.