TAPE REMOVER

Product: SD762

Revision Date: 2015/04/14

Section 1: PRODUCT INFORMATION

Chemical family: Not available.

Product uses: Tape remover.

Manufacturer: Canadian Custom Packaging

333 Rimrock Road Toronto, Ontario

M3J 3J9.

Manufacturer emergency phone

number:

613-996-6666.

Information phone number: 416–638–1111

Supplier: Same as manufacturer.

TDG classification: TRICHLOROETHYLENE

UN1710 Class 6.1 PG III.

WHMIS classification:

D1B, D2B.

DSL status: Appears on DSL.

Supplier MSDS date: 2015/04/14.

Product name: Tape Remover

Section 2: HAZARDOUS INGREDIENTS

C.A.S.	CONCENTRATION %	Ingredient Name	TLV	LD50	LC50
79–01–6	100	TRICHLOROETHYLENE	10 PPM	4920 MG/KG RAT ORAL 2400 MG/KG MOUSE ORAL	8450 PPM/4H MOUSE INHALATION 220,000 MG/M3/20M MOUSE INHALATION 140700 MG/M3/1H RAT INHALATION
				> 20000 MG/KG RABBIT DERMAL	

Section 3: PHYSICAL DATA

Physical state: Liquid.

Appearance & odor: Colourless.

Clear

Chloroform-like odor.

Odor threshold (ppm): Not available.

Vapour pressure (mmHg): 57.8

SD762 – TAPE REMOVER 1/5

Vapour density (air=1): 4.54

Volatiles (%)

By volume: 100%

Evaporation rate 0.28

(butyl acetate = 1):

Boiling point (°C): 87°C @ 760 mmHG

Freezing point ($^{\circ}$ C): -73 $^{\circ}$ C.

pH: 6.7–7.5.

Specific gravity @ **20** $^{\circ}$ **C:** (water = 1).

1.465

Solubility in water (%): Practically insoluble.

Coefficient of water\oil dist.: Not available.

Section 4: FIRE & EXPLOSION DATA

Flammability: Not flammable.

Conditions of flammability: Surrounding fire.

Vapours are heavier than air and may travel along the ground and be ignited by flames, sparks or other ignition sources at locations distant from the material

handling point.

Extinguishing media: Dry chemical.

Alcohol foam. Carbon dioxide. Foam or water spray.

Special procedures: Self-contained breathing apparatus required.

Firefighters should wear the usual protective gear. Evacuate area and apply water from a safe distance.

Stay upwind if possible.

Auto-ignition temperature (°C): Not available.

Flash point (°C), method: Not available.

Lower flammability 8.0

limit (% vol):

Upper flammability

12.5 limit (% vol):

Explosion Data

Sensitivity to static discharge: Not applicable.

Sensitivity to mechanical impact: Not applicable.

Hazardous combustion products: Oxides of carbon (CO, CO2).

Phosgene. Chlorine (Cl2).

Hydrogen chloride (HCl).

Explosive power: Container explosion may occur when heated.

Vapours are heavier than air and may collect in low-lying areas.

Liquid oxygen or other strong oxidizers may form explosive mixtures with this

product.

SD762 - TAPE REMOVER 2/5

Section 5: REACTIVITY DATA

Chemical stability: Product is stable.

Conditions of instability: Excessive heat.

All ignition sources.

Direct sunlight and open flames.

Hazardous polymerization: Will not occur.

Incompatible substances: Amines.

Strong bases. Powdered metals.

Caustics.
Strong oxidizers.

Alkali metal. Caustic potash.

Strong alkali metal hydroxides.

Hazardous decomposition Hydrogen chloride.

products: Phosgene.

Section 6: TOXICOLOGICAL PROPERTIES

Route of entry: Skin contact, eye contact, inhalation and ingestion.

Effects of acute exposure

Eye contact: Causes redness, swelling & tearing.

Excessive blinking.

Skin contact: Prolonged contact may cause dermatitis.

Prolonged and repeated contact may cause irritation.

Inhalation: May cause central nervous system depression: signs/symptoms can include

headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred

speech, giddiness and unconsciousness. May cause fatal ventricular fibrillation.

Ingestion: May cause gastro–intestinal irritation.

See inhalation effects.

Aspiration pneumonitis: symptoms can include coughing, difficulty breathing,

wheezing, coughing up blood and pneumonia, which can be fatal.

May cause coughing.

May cause irritation to the mouth.

Aspiration may cause pneumonitis.

Aspiration may result in pulmonary injury.

Effects of chronic exposure: See effects of acute exposure.

LD50 of product, species & route: See hazardous ingredients section.

LC50 of product, species & route: See hazardous ingredients section.

Exposure limit of material: See hazardous ingredients section.

Sensitization to product: Not available.

Carcinogenic effects: Not listed as a carcinogen.

Reproductive effects: None known.

SD762 – TAPE REMOVER 3/5

Teratogenicity: None known.

Mutagenicity: Effects have been reported in animals.

Synergistic materials: Not available.

Section 7: PREVENTATIVE MEASURES

Precautionary Measures

Gloves/Type: Chemical resistant gloves.

Respiratory/Type: NIOSH approved organic vapour cartridge respirator or air-supplied when used in

confined areas or if TLV is exceeded.

Eye/Type: Chemical safety goggles.

Face shield if splashing could occur.

Footwear/Type: Impervious boots.

Clothing/Type: Impervious clothing (apron, coveralls).

Other/Type: Eye wash facility should be in close proximity.

Emergency shower should be in close proximity.

Ventilation requirements: Ventilate adequately.

Leak/Spill: Absorb with inert material.

Evacuate all non-essential personnel.

Prevent entry into drains, sewers, and other waterways.

Ventilate area.

Wear appropriate protective equipment.

Stay upwind.

Place in appropriate container for disposal.

After all visible traces have been removed, wet vacuum the area.

Waste disposal: In accordance with municipal, provincial and federal regulations.

Handling procedures and Avoid breathing vapors/mists.

equipment: Use adequate ventilation.

Wear personal protective equipment appropriate to task.

Wash thoroughly after handling.

Empty containers containing residue may cause a hazard.

Avoid contact with skin, eyes and clothing.

Do not pressurize, cut, heat, or weld empty containers.

Handle empty containers as if they were full. Launder contaminated clothing prior to reuse. Application to hot surfaces requires special care.

Storage requirements: Store away from incompatible materials.

Keep out of direct sunlight. Store in a cool and dry place. Keep containers tightly closed.

Do not store in aluminum, zinc, or plastic containers.

TDG classification: TRICHLOROETHYLENE

UN1710 Class 6.1 PG III.

Special shipping information: See transportation information.

SD762 – TAPE REMOVER 4/5

Section 8: FIRST AID MEASURES

Skin contact: Remove contaminated clothing.

Wash thoroughly with soap and water. Seek medical attention if irritation persists.

Eye contact: Flush with plenty of water.

Consult a physician.

Inhalation: Remove victim to fresh air. If not breathing, qualified personnel should administer

artificial respiration. Get medical attention.

Ingestion: Do not induce vomiting, seek medical attention.

Never give anything by mouth to an unconscious person.

If spontaneous vomiting occurs, have victim lean forward with head down to avoid

breathing in of vomitus.

If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiraton must be weighed against toxicity when considering emptying

the stomach.

Additional information: The above information is believed to be correct but does not purport to be all

inclusive and shall be used only as a guide. This company shall not be held liable

for any inaccuracies.

Section 9: ADDITIONAL INFORMATION

General note: This material safety data sheet was prepared from information obtained from

various sources, including product suppliers and the Canadian Center for

Occupational Health and Safety.

Data prepared by: Conform–Action Data Systems

A division of 2843471 Canada Inc. 1840 Transcanada, suite 101

Dorval, QC H9P 1H7

Tel: (514) 683-2060 Fax: (514) 683-1445

24 hr. 1–866–628–7522 support@netmsds.com.

This MSDS was generated by Conform-Plus Application Service. Visit us at www.netmsds.com.

SD762 – TAPE REMOVER 5/5