

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Irus DU-NA Fluid 46

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 2016-05-25          |
| 1.5     | 2016-05-24     | 800001029295 | Date of last issue: 29.04.2016  |
|         |                |              | Date of first issue: 08.12.2010 |

### SECTION 1. IDENTIFICATION

Product name : Shell Irus DU-NA Fluid 46

Product code : 001C6902

#### Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Canada Products**  
400 - 4th Avenue S.W  
Calgary AB T2P 0J4  
Canada

Telephone : (+1) 8006611600

Telefax : (+1) 4033848345

Emergency telephone number : CHEMTREC (24 hr): 1 (703) 527-3887 or 1 (800) 424-9300 (US)  
CANUTEC (24 hr): (+1) 613-996-6666; Toll Free: 1-888-CAN-UTEC (226-8832)

#### Recommended use of the chemical and restrictions on use

Recommended use : Fire-resistant hydraulic fluid.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Not a hazardous substance or mixture.

#### GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:  
Not classified as a physical hazard under GHS criteria.  
HEALTH HAZARDS:  
Not classified as a health hazard under GHS criteria.  
ENVIRONMENTAL HAZARDS:  
Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**  
No precautionary phrases.  
**Response:**  
No precautionary phrases.  
**Storage:**

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Irus DU-NA Fluid 46

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 2016-05-25          |
| 1.5     | 2016-05-24     | 800001029295 | Date of last issue: 29.04.2016  |
|         |                |              | Date of first issue: 08.12.2010 |

No precautionary phrases.

### Disposal:

No precautionary phrases.

### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis.

Not classified as flammable but will burn.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name : Shell Irus DU-NA Fluid 46

Chemical nature : Blend of polyol ester, highly refined mineral oil and additives.

### Hazardous components

No hazardous ingredients

## SECTION 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal conditions.

If inhaled : No treatment necessary under normal conditions of use.  
If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.

When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.  
Obtain medical attention even in the absence of apparent wounds.

In case of eye contact : Flush eye with copious quantities of water.  
If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and delayed : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.  
Ingestion may result in nausea, vomiting and/or diarrhoea.  
Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Iru<sup>s</sup> DU-NA Fluid 46

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 2016-05-25          |
| 1.5     | 2016-05-24     | 800001029295 | Date of last issue: 29.04.2016  |
|         |                |              | Date of first issue: 08.12.2010 |

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

Notes to physician : Treat symptomatically.

High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function.

Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

Specific hazards during fire-fighting : Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide may be evolved if incomplete combustion occurs.  
Unidentified organic and inorganic compounds.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Avoid contact with skin and eyes.

Environmental precautions : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Iruus DU-NA Fluid 46

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 2016-05-25          |
| 1.5     | 2016-05-24     | 800001029295 | Date of last issue: 29.04.2016  |
|         |                |              | Date of first issue: 08.12.2010 |

rivers by using sand, earth, or other appropriate barriers.

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Additional advice : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

### SECTION 7. HANDLING AND STORAGE

General Precautions : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Advice on safe handling : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Avoidance of contact : Strong oxidising agents.

#### Storage

Other data : Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.

Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Iru<sup>s</sup> DU-NA Fluid 46

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 2016-05-25          |
| 1.5     | 2016-05-24     | 800001029295 | Date of last issue: 29.04.2016  |
|         |                |              | Date of first issue: 08.12.2010 |

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

##### Biological occupational exposure limits

No biological limit allocated.

##### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

**Engineering measures** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:  
Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell IruS DU-NA Fluid 46

Version  
1.5

Revision Date:  
2016-05-24

SDS Number:  
800001029295

Print Date: 2016-05-25  
Date of last issue: 29.04.2016  
Date of first issue: 08.12.2010

protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

### Personal protective equipment

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.  
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.  
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

Hand protection  
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes.  
It is good practice to wear chemical resistant gloves.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Iru<sup>s</sup> DU-NA Fluid 46

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 2016-05-25          |
| 1.5     | 2016-05-24     | 800001029295 | Date of last issue: 29.04.2016  |
|         |                |              | Date of first issue: 08.12.2010 |

Thermal hazards : Not applicable

Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

### Environmental exposure controls

General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.  
Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid at room temperature.

Colour : Clear amber

Odour : Slight hydrocarbon

Odour Threshold : Data not available

pH : Not applicable

pour point : -51 °C / -60 °F  
Method: ISO 3016

Initial boiling point and boiling range : > 280 °C / 536 °F  
estimated value(s)

Flash point : 304 °C / 579 °F  
Method: ISO 2592

Evaporation rate : Data not available

Flammability (solid, gas) : Data not available

Upper explosion limit : Typical 10 %(V)

Lower explosion limit : Typical 1 %(V)

Vapour pressure : < 0.5 Pa (20 °C / 68 °F)  
estimated value(s)

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell IruS DU-NA Fluid 46

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 2016-05-25          |
| 1.5     | 2016-05-24     | 800001029295 | Date of last issue: 29.04.2016  |
|         |                |              | Date of first issue: 08.12.2010 |

|  |   |
|--|---|
| Relative vapour density                | : > 1<br>estimated value(s)                                       |
| Relative density                       | : 0.920 (15 °C / 59 °F)   |
| Density                                | : 920 kg/m <sup>3</sup> (20 °C / 68 °F) Method: ISO 12185         |
| Solubility(ies)                        |   |
| Water solubility                       | : negligible  |
| Solubility in other solvents           | : Data not available  |
| Partition coefficient: n-octanol/water | : Pow: > 6<br>(based on information on similar products)          |
| Auto-ignition temperature              | : > 320 °C / 608 °F   |
| Viscosity                              |   |
| Viscosity, dynamic                     | : Data not available  |
| Viscosity, kinematic                   | : 46 mm <sup>2</sup> /s (40.0 °C / 104.0 °F)<br>Method: ASTM D445 |
|  | : 9.5 mm <sup>2</sup> /s (100 °C / 212 °F)<br>Method: ASTM D445   |
| Explosive properties                   | : Not classified  |
| Oxidizing properties                   | : Data not available  |
| Conductivity                           | : This material is not expected to be a static accumulator.       |
| Decomposition temperature              | : Data not available  |

### SECTION 10. STABILITY AND REACTIVITY

|                                    |  |
|------------------------------------|--|
| Reactivity                         | : The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph. |
| Chemical stability                 | : Stable.  |
| Possibility of hazardous reactions | : Reacts with strong oxidising agents.   |
| Conditions to avoid                | : Extremes of temperature and direct sunlight.   |
| Incompatible materials             | : Strong oxidising agents.   |
| Hazardous decomposition products   | : Hazardous decomposition products are not expected to form during normal storage.                                     |



# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Iruv DU-NA Fluid 46

Version  
1.5

Revision Date:  
2016-05-24

SDS Number:  
800001029295

Print Date: 2016-05-25  
Date of last issue: 29.04.2016  
Date of first issue: 08.12.2010

### SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity : LD50 (rat): > 5,000 mg/kg  
Remarks: Expected to be of low toxicity:

Acute inhalation toxicity : Remarks: Not considered to be an inhalation hazard under normal conditions of use.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Expected to be of low toxicity:

#### Skin corrosion/irritation

##### Product:

Remarks: Expected to be slightly irritating.  
Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

#### Serious eye damage/eye irritation

##### Product:

Remarks: Expected to be slightly irritating.

#### Respiratory or skin sensitisation

##### Product:

Remarks: Not expected to be a skin sensitiser.

#### Germ cell mutagenicity

##### Product:

Genotoxicity in vivo : Remarks: Not considered a mutagenic hazard.

#### Carcinogenicity

##### Product:

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Iruis DU-NA Fluid 46

Version  
1.5

Revision Date:  
2016-05-24

SDS Number:  
800001029295

Print Date: 2016-05-25  
Date of last issue: 29.04.2016  
Date of first issue: 08.12.2010

Remarks: Not expected to be carcinogenic.

### Reproductive toxicity

#### Product:

Effects on fertility

:

Remarks: Not expected to impair fertility.  
Not expected to be a developmental toxicant.

### STOT - single exposure

#### Product:

Remarks: Not expected to be a hazard.

### STOT - repeated exposure

#### Product:

Remarks: Not expected to be a hazard.

### Aspiration toxicity

#### Product:

Not considered an aspiration hazard.

### Further information

#### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

## SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment

: Ecotoxicological data have not been determined specifically for this product.  
Information given is based on a knowledge of the components and the ecotoxicology of similar products.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). (LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Iru<sup>s</sup> DU-NA Fluid 46

Version  
1.5

Revision Date:  
2016-05-24

SDS Number:  
800001029295

Print Date: 2016-05-25  
Date of last issue: 29.04.2016  
Date of first issue: 08.12.2010

### Ecotoxicity

#### Product:

Toxicity to fish (Acute toxicity) : Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to crustacean (Acute toxicity) : Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) : Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to crustacean (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) : Remarks: Data not available

### Persistence and degradability

#### Product:

Biodegradability : Remarks: Expected to be not readily biodegradable.  
Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

Partition coefficient: n-octanol/water : Pow: > 6  
Remarks: (based on information on similar products)

### Mobility in soil

#### Product:

Mobility : Remarks: Liquid under most environmental conditions.  
If it enters soil, it will adsorb to soil particles and will not be mobile.

### Other adverse effects

#### Product:

Additional ecological information : Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Iru<sup>s</sup> DU-NA Fluid 46

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 2016-05-25          |
| 1.5     | 2016-05-24     | 800001029295 | Date of last issue: 29.04.2016  |
|         |                |              | Date of first issue: 08.12.2010 |

Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

Poorly soluble mixture.  
May cause physical fouling of aquatic organisms.

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.  
Disposal should be in accordance with applicable regional, national, and local laws and regulations.

### SECTION 14. TRANSPORT INFORMATION

#### National Regulations

##### TDG

Not regulated as a dangerous good

#### International Regulation

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

|                     |                  |
|---------------------|------------------|
| Pollution category  | : Not applicable |
| Ship type           | : Not applicable |
| Product name        | : Not applicable |
| Special precautions | : Not applicable |

#### Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

**Additional Information** : MARPOL Annex 1 rules apply for bulk shipments by sea.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Iruis DU-NA Fluid 46

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 2016-05-25          |
| 1.5     | 2016-05-24     | 800001029295 | Date of last issue: 29.04.2016  |
|         |                |              | Date of first issue: 08.12.2010 |

### SECTION 15. REGULATORY INFORMATION

#### **Safety, health and environmental regulations/legislation specific for the substance or mixture**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

#### **The components of this product are reported in the following inventories:**

EINECS : All components listed or polymer exempt.

TSCA : All components listed.

DSL : All components listed.

### SECTION 16. OTHER INFORMATION

#### **Full text of other abbreviations**

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Shell Iru<sup>s</sup> DU-NA Fluid 46

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Print Date: 2016-05-25          |
| 1.5     | 2016-05-24     | 800001029295 | Date of last issue: 29.04.2016  |
|         |                |              | Date of first issue: 08.12.2010 |

---

A vertical bar (|) in the left margin indicates an amendment from the previous version.  
Revision Date : 2016-05-24

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN