Version 1.5	Revision Date: 2016-05-24		DS Number: 00001030767	Print Date: 2016-05-25 Date of last issue: 29.04.2016 Date of first issue: 06.09.2010
SECTION	1. IDENTIFICATION			
Prod	uct name	:	Shell Rotella T1 3	30
Prod	uct code	:	001D5428	
Manufacturer or supplier's			ails	
Manı	ufacturer/Supplier	:	Shell Canada Pr 400 - 4th Avenue Calgary AB T2P Canada	S.W
Teler Telef	bhone ^j ax		(+1) 8006611600 (+1) 4033848345	
Emei ber	rgency telephone num-	:	(US)	hr): 1 (703) 527-3887 or 1 (800) 424-9300): (+1) 613-996-6666; Toll Free: 1-888-CAN-)
Reco	ommended use of the c	hen	nical and restriction	ons on use
Reco	mmended use	:	Engine oil.	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

	No precautionary phrases. Storage:
	Response:
Precautionary statements	: Prevention: No precautionary phrases.
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Signal word	: No signal word
Hazard pictograms	: No Hazard Symbol required

Version	Revision Date:	SDS Number:	Print Date: 2016-05-25
1.5	2016-05-24	800001030767	Date of last issue: 29.04.2016 Date of first issue: 06.09.2010

No precautionary phrases. **Disposal:** No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.

Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name	: Shell Rotella T1 30
Chemical nature	 Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9.

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Sulphurised calcium phenate	Not Assigned	1 - 3
Zinc dialkyl dithiophosphate	68649-42-3	1 - 2.4
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	0 - 90

SECTION 4. FIRST-AID MEASURES

General advice	Not expected to be a health hazard when used under no conditions.	ormal
If inhaled	No treatment necessary under normal conditions of use If symptoms persist, obtain medical advice.	
In case of skin contact	 Remove contaminated clothing. Flush exposed area wit ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. 	h wa-
In case of eye contact	 Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention. 	
If swallowed	In general no treatment is necessary unless large quant are swallowed, however, get medical advice.	ities
Most important symptoms and effects, both acute and	Oil acne/folliculitis signs and symptoms may include form of black pustules and spots on the skin of exposed area	

Version 1.5	Revision Date: 2016-05-24	SDS Number: 800001030767	Print Date: 2016-05-25 Date of last issue: 29.04.2016 Date of first issue: 06.09.2010
delay	red	Ingestion may	result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders		appropriate per	ering first aid, ensure that you are wearing the rsonal protective equipment according to the and surroundings.
Notes	s to physician	: Treat symptom	atically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

	Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
	Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
			Local authorities should be advised if significant spillages cannot be contained.
	Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent.
			Soak up residue with an absorbent such as clay, sand or other
3 / 1	4		800001030767
			0.4

Version 1.5	Revision Date: 2016-05-24	SDS Number: 800001030767	Print Date: 2016-05-25 Date of last issue: 29.04.2016 Date of first issue: 06.09.2010			
		suitable mat	erial and dispose of properly.			
Addit	ional advice	see Chapter For guidance	 For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet. 			
SECTION	7. HANDLING AND S	TORAGE				
Gene	eral Precautions	vapours, mis Use the info sessment of	haust ventilation if there is risk of inhalation of sts or aerosols. rmation in this data sheet as input to a risk as- local circumstances to help determine appropri- for safe handling, storage and disposal of this			
Advid	ce on safe handling	Avoid İnhalir When handl worn and pro Properly dis	nged or repeated contact with skin. ng vapour and/or mists. ing product in drums, safety footwear should be oper handling equipment should be used. pose of any contaminated rags or cleaning mate- t o prevent fires.			
Avoid	dance of contact	: Strong oxidi	sing agents.			
Prod	uct Transfer	er : This material has the potential to be a static accumul Proper grounding and bonding procedures should be during all bulk transfer operations.				
Stora	-					
Othe	r data	place.	ner tightly closed and in a cool, well-ventilated y labeled and closable containers.			
		Store at amb	pient temperature.			
Pack	aging material	steel or high	terial: For containers or container linings, use mild density polyethylene. naterial: PVC.			
Cont	ainer Advice		: Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.			

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Version	Revision Date:	SDS Number:
1.5	2016-05-24	800001030767

Print Date: 2016-05-25 Date of last issue: 29.04.2016 Date of first issue: 06.09.2010

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhal- able frac- tion))	5 mg/m3	US. ACGIH Threshold Limit Values
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.
	Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.
	Drain down system prior to equipment break-in or mainte- nance. Retain drain downs in sealed storage pending disposal or
14	800001030767

Version 1.5	Revision Date: 2016-05-24	SDS Number: 800001030767	Print Date: 2016-05-25 Date of last issue: 29.04.2016 Date of first issue: 06.09.2010
		washing hands drinking, and/or protective equip	good personal hygiene measures, such as after handling the material and before eating, smoking. Routinely wash work clothing and ment to remove contaminants. Discard con- ng and footwear that cannot be cleaned.
Pers	onal protective equip	oment	
	iratory protection	: No respiratory p conditions of us In accordance w tions should be If engineering co tions to a level w select respirator cific conditions of Check with resp Where air-filterin priate combinati Select a filter su	protection is ordinarily required under normal e. with good industrial hygiene practices, precau- taken to avoid breathing of material. ontrols do not maintain airborne concentra- which is adequate to protect worker health, ry protection equipment suitable for the spe- of use and meeting relevant legislation. biratory protective equipment suppliers. ng respirators are suitable, select an appro- tion of mask and filter. hitable for the combination of organic gases ype A/Type P boiling point >65°C (149°F)].
Hand	I protection		
	emarks	gloves approved US: F739) made suitable chemica gloves Suitabilit usage, e.g. freq sistance of glove glove suppliers. Personal hygier Gloves must on gloves, hands s cation of a non- For continuous through time of 480 minutes wh short-term/splas recognize that s may not be avai time maybe acc and replacemer a good predictoo dependent on th Glove thickness	htact with the product may occur the use of d to relevant standards (e.g. Europe: EN374, e from the following materials may provide al protection. PVC, neoprene or nitrile rubber y and durability of a glove is dependent on uency and duration of contact, chemical re- e material, dexterity. Always seek advice from Contaminated gloves should be replaced. he is a key element of effective hand care. ly be worn on clean hands. After using hould be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- more than 240 minutes with preference for > ere suitable gloves can be identified. For sh protection we recommend the same, but suitable gloves offering this level of protection ilable and in this case a lower breakthrough eptable so long as appropriate maintenance at regimes are followed. Glove thickness is not r of glove resistance to a chemical as it is ne exact composition of the glove material. a should be typically greater than 0.35 mm he glove make and model.
Eyeı	protection		ndled such that it could be splashed into eyes, ear is recommended.

Version 1.5	Revision Date: 2016-05-24	SDS Number: 800001030767	Print Date: 2016-05-25 Date of last issue: 29.04.2016 Date of first issue: 06.09.2010
Skin a	and body protection	work clothes.	is not ordinarily required beyond standard ce to wear chemical resistant gloves.
Therr	nal hazards	: Not applicable	
Prote	ctive measures		tive equipment (PPE) should meet recom- al standards. Check with PPE suppliers.

Environmental exposure controls

General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. In necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.	btection legislation. Avoid contamination following advice given in Chapter 6. If dissolved material from being dis- er. Waste water should be treated in a waste water treatment plant before vater. hission limits for volatile substances
--	--

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid at room temperature.
Colour	: amber
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рН	: Not applicable
pour point	: -24 °C / -11 °F Method: ASTM D97
Initial boiling point and boiling range	: > 280 °C / 536 °F estimated value(s)
Flash point	: 210 °C / 410 °F
	Method: ASTM D92
Evaporation rate	: Data not available
Flammability (solid, gas)	: Data not available
Upper explosion limit	: Typical 10 %(V)

Version 1.5	Revision Date: 2016-05-24	SDS Number:Print Date: 2016-05-25800001030767Date of last issue: 29.04.2016Date of first issue: 06.09.2010	
Lov	ver explosion limit	: Typical 1 %(V)	
Va	oour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Re	ative vapour density	: > 1 estimated value(s)	
Re	lative density	: 0.887 (15 °C / 59 °F)	
De	nsity	: 887 kg/m3 (15.0 °C / 59.0 °F)Method: ASTM D4052	
	ubility(ies) Nater solubility	: negligible	
:	Solubility in other solvents	: Data not available	
	rtition coefficient: n- anol/water	: Pow: > 6 (based on information on similar products)	
Au	to-ignition temperature	: > 320 °C / 608 °F	
	cosity /iscosity, dynamic	: Data not available	
	/iscosity, kinematic	: 107 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445	
		11.9 mm2/s (100 °C / 212 °F) Method: ASTM D445	
Ex	plosive properties	: Not classified	
Ox	idizing properties	: Data not available	
Co	nductivity	: This material is not expected to be a static accumulato	r.
De	composition temperature	: Data not available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reac- tions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.

Version 1.5	Revision Date: 2016-05-24	SDS Number: 800001030767	Print Date: 2016-05-25 Date of last issue: 29.04.2016 Date of first issue: 06.09.2010
Incom	patible materials	: Strong oxidising	g agents.
Hazar produ	dous decomposition cts	: Hazardous dec during normal s	composition products are not expected to form storage.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise,
		the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product: Acute oral toxicity	: LD50 (rat): > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	: Remarks: Not considered to be an inhalation hazard under normal conditions of use.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: Expected to be of low toxicity:

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a skin sensitiser.

Germ cell mutagenicity

Product:

Genotoxicity in vivo

: Remarks: Not considered a mutagenic hazard.

Version	Revision Date:	SDS Number:	Print Date: 2016-05-25
1.5	2016-05-24	800001030767	Date of last issue: 29.04.2016
			Date of first issue: 06.09.2010

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies.

Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not expected to impair fertility. Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	:	Ecotoxicological data have not been determined specifically
		for this product.
		Information given is based on a knowledge of the components

ersion .5	Revision Date: 2016-05-24		S Number: 0001030767	Print Date: 2016-05-25 Date of last issue: 29.04.2016 Date of first issue: 06.09.2010	
			Unless indicated tive of the product ponent(s).(LL/EL/	logy of similar products. otherwise, the data presented is representa- t as a whole, rather than for individual com- IL50 expressed as the nominal amount of to prepare aqueous test extract).	
Ecoto	oxicity				
	<u>Product:</u> Toxicity to fish (Acute toxici- ty)		Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l		
	Toxicity to crustacean (Acute toxicity)		Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l		
	Toxicity to algae/aquatic plants (Acute toxicity)		Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l		
Toxic icity)	Toxicity to fish (Chronic tox- icity)		Remarks: Data no	ot available	
(Chro Toxic	Toxicity to crustacean (Chronic toxicity) Toxicity to microorganisms (Acute toxicity)		Remarks: Data not available Remarks: Data not available		
	stence and degradabili	ity			
-	Product: Biodegradability		Remarks: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegrada ble, but contains components that may persist in the environ ment.		
Bioad	ccumulative potential				
<u>Prodi</u> Bioac	uct: cumulation	:	Remarks: Contair cumulate.	ns components with the potential to bioac-	
Partition coefficient: n- : octanol/water		:	Pow: > 6 Remarks: (based	w: > 6 emarks: (based on information on similar products)	
Mobi	lity in soil				
Produ Mobil		:		under most environmental conditions. will adsorb to soil particles and will not be 800001030767	

Version 1.5	Revision Date: 2016-05-24	SDS Number: 800001030767	Print Date: 2016-05-25 Date of last issue: 29.04.2016 Date of first issue: 06.09.2010			
		Remarks: Floats	on water.			
Other	adverse effects					
<u>Produ</u>	<u>ct:</u>					
Additional ecological infor- mation		expected to be re Not expected to h	: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemi- cal ozone creation potential or global warming potential.			
		Poorly soluble mi May cause physi	xture. cal fouling of aquatic organisms.			
			expected to cause any chronic effects to s at concentrations less than 1 mg/l.			

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
	Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or na- tional requirements and must be complied with.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

TDG

Not regulated as a dangerous good

International Regulation

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Version 1.5	Revision Date: 2016-05-24	SDS Number: 800001030767	Print Date: 2016-05-25 Date of last issue: 29.04.2016 Date of first issue: 06.09.2010	
Pollution category Ship type Product name Special precautions		 Not applicable Not applicable Not applicable Not applicable Not applicable 		
Special pr	ecautions for user			
Remarks		: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.		
Additional Information		: MARPOL Annex 1 rules apply for bulk shipments by sea.		

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

The components of this product are reported in the following inventories:			
EINECS	: All components listed or polymer exempt.		
TSCA	: All components listed.		
DSL	: All components listed.		

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response: ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Tox-

Version	Revision Date:	SDS Number:	Print Date: 2016-05-25
1.5	2016-05-24	800001030767	Date of last issue: 29.04.2016
			Date of first issue: 06.09.2010

icology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version. Revision Date : 2016-05-24

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN