Version 1.2	Revision Date: 2016-05-20	SDS Number: 800001029079	Print Date: 2016-05-21 Date of last issue: 21.10.2015 Date of first issue: 02.08.2012
SECTION	1. IDENTIFICATION		
Produ	uct name	: Shell Rotella	ГЗ NG 15W-40
Product code		: 001E3657	
Manı	ufacturer or supplier	s details	
Manu	ifacturer/Supplier	: Shell Canada 400 - 4th Aver Calgary AB T Canada	nue S.W

Telephone Telefax	:	(+1) 8006611600 (+1) 4033848345
Emergency telephone num- ber	:	CHEMTREC (24 hr): 1 (703) 527-3887 or 1 (800) 424-9300 (US) CANUTEC (24 hr): (+1) 613-996-6666; Toll Free: 1-888-CAN- UTEC (226-8832)

Recommended use of the chemical and restrictions on use

Recommended use	:	Engine oil.
-----------------	---	-------------

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	 Prevention: No precautionary phrases. Response: No precautionary phrases.
14	800001029079

Version Revision Date: 1.2 2016-05-20 SDS Number: 800001029079

Print Date: 2016-05-21 Date of last issue: 21.10.2015 Date of first issue: 02.08.2012

Storage:

No precautionary phrases. **Disposal:** No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name	: Shell Rotella T3 NG 15W-40
Chemical nature	 Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9.

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Alkaryl amine	36878-20-3	1 - 3
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	0 - 90

SECTION 4. FIRST-AID MEASURES

General advice	: Not expected to be a health hazard when used under norma conditions.	I
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.	
In case of skin contact	 Remove contaminated clothing. Flush exposed area with wa ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. 	-
In case of eye contact	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.	
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.	
Most important symptoms	: Oil acne/folliculitis signs and symptoms may include formation	on

Version 1.2	Revision Date: 2016-05-20	SDS Number: 800001029079	Print Date: 2016-05-21 Date of last issue: 21.10.2015 Date of first issue: 02.08.2012
and e delay	effects, both acute and /ed		s and spots on the skin of exposed areas. esult in nausea, vomiting and/or diarrhoea.
Protection of first-aiders		appropriate per	ering first aid, ensure that you are wearing the sonal protective equipment according to the and surroundings.
Notes	s to physician	: Treat symptoma	atically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material.
1/		800001020070

Version 1.2	Revision Date: 2016-05-20	SDS Number: 800001029079	Print Date: 2016-05-21 Date of last issue: 21.10.2015 Date of first issue: 02.08.2012
		Soak up residu	directly or in an absorbent. e with an absorbent such as clay, sand or other al and dispose of properly.
Additio	onal advice	see Chapter 8 o	n selection of personal protective equipment of this Safety Data Sheet. n disposal of spilled material see Chapter 13 of a Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
Storage		
Other data	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

Version	Revision Date:	SDS Number:	Print Date: 2016-05-21
1.2	2016-05-20	800001029079	Date of last issue: 21.10.2015
			Date of first issue: 02.08.2012

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhal- able frac- tion))	5 mg/m3	US. ACGIH Threshold Limit Values
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

 Engineering measures
 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
 Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
 General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Version 1.2	Revision Date: 2016-05-20	SDS Number: 800001029079	Print Date: 2016-05-21 Date of last issue: 21.10.2015 Date of first issue: 02.08.2012
		equipment used equipment, loca Drain down syst nance. Retain drain dor subsequent rec Always observe washing hands drinking, and/or protective equip	good personal hygiene measures, such as after handling the material and before eating, smoking. Routinely wash work clothing and ment to remove contaminants. Discard con- ing and footwear that cannot be cleaned.
	onal protective equip	: No respiratory p conditions of us In accordance w tions should be If engineering c tions to a level w select respirator cific conditions of Check with resp Where air-filterin priate combinat Select a filter su	protection is ordinarily required under normal se. with good industrial hygiene practices, precau- taken to avoid breathing of material. ontrols do not maintain airborne concentra- which is adequate to protect worker health, ry protection equipment suitable for the spe- of use and meeting relevant legislation. biratory protective equipment suppliers. ng respirators are suitable, select an appro- ion of mask and filter. uitable for the combination of organic gases type A/Type P boiling point >65°C (149°F)].
	protection marks	gloves approved US: F739) made suitable chemic gloves Suitabilit usage, e.g. freq sistance of glov glove suppliers. Personal hygier Gloves must on gloves, hands s cation of a non- For continuous through time of 480 minutes wh short-term/splas recognize that s may not be ava time maybe acc and replacemer	ntact with the product may occur the use of d to relevant standards (e.g. Europe: EN374, e from the following materials may provide al protection. PVC, neoprene or nitrile rubber by and durability of a glove is dependent on uency and duration of contact, chemical re- e material, dexterity. Always seek advice from Contaminated gloves should be replaced. he is a key element of effective hand care. If be worn on clean hands. After using should be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- more than 240 minutes with preference for > here suitable gloves can be identified. For sh protection we recommend the same, but suitable gloves offering this level of protection ilable and in this case a lower breakthrough ceptable so long as appropriate maintenance in regimes are followed. Glove thickness is not r of glove resistance to a chemical as it is

Version 1.2	Revision Date: 2016-05-20	SDS Number: 800001029079	Print Date: 2016-05-21 Date of last issue: 21.10.2015 Date of first issue: 02.08.2012
		Glove thicknes	the exact composition of the glove material. Is should be typically greater than 0.35 mm the glove make and model.
Еуе рі	rotection		andled such that it could be splashed into eyes, wear is recommended.
Skin and body protection		work clothes.	n is not ordinarily required beyond standard tice to wear chemical resistant gloves.
Therm	al hazards	: Not applicable	
Protec	tive measures	•	ctive equipment (PPE) should meet recom- al standards. Check with PPE suppliers.

Environmental exposure controls

General advice : Take appropriate measures to fulfill the requirement vant environmental protection legislation. Avoid consistent of the environment by following advice given in Clinecessary, prevent undissolved material from bein charged to waste water. Waste water should be transmission or industrial waste water treatment plant discharge to surface water. Local guidelines on emission limits for volatile sub must be observed for the discharge of exhaust air vapour.	ontamination hapter 6. If ing dis- reated in a nt before bstances
--	--

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid at room temperature.
Colour	: amber
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рН	: Not applicable
pour point	: -33 °C / -27 °F Method: ASTM D97
Initial boiling point and boiling range	: > 280 °C / 536 °F estimated value(s)
Flash point	: 225 °C / 437 °F

Versio 1.2	n Revision Date: 2016-05-20	SDS Number:Print Date: 2016-05-21800001029079Date of last issue: 21.10.2015Date of first issue: 02.08.2012	
		Method: ASTM D92	
Evaporation rate		: Data not available	
F	lammability (solid, gas)	: Data not available	
U	pper explosion limit	: Typical 10 %(V)	
L	ower explosion limit	: Typical 1 %(V)	
V	apour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
R	elative vapour density	: > 1 estimated value(s)	
R	elative density	: 0.880 (15 °C / 59 °F)	
D	ensity	: 880 kg/m3 (15.0 °C / 59.0 °F)Method: ASTM D4052	
S	olubility(ies) Water solubility	: negligible	
	Solubility in other solvents	: Data not available	
	artition coefficient: n- ctanol/water	: Pow: > 6 (based on information on similar products)	
А	uto-ignition temperature	: > 320 °C / 608 °F	
V	iscosity Viscosity, dynamic	: Data not available	
	Viscosity, kinematic	: 117 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445	
		15.5 mm2/s (100 °C / 212 °F) Method: ASTM D445	
E	xplosive properties	: Not classified	
O	vidizing properties	: Data not available	
С	onductivity	: This material is not expected to be a static accumulator.	
D	ecomposition temperature	: Data not available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: The product does not pose any further reactivity hazards in

Version 1.2	Revision Date: 2016-05-20		9S Number: 0001029079	Print Date: 2016-05-21 Date of last issue: 21.10.2015 Date of first issue: 02.08.2012
			addition to those	listed in the following sub-paragraph.
Che	emical stability	:	Stable.	
Possibility of hazardous reac- tions		- :	Reacts with stro	ng oxidising agents.
Co	nditions to avoid	:	Extremes of tem	perature and direct sunlight.
Incompatible materials		:	: Strong oxidising agents.	
	ardous decomposition ducts	:	Hazardous deco during normal st	mposition products are not expected to form orage.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
	whole, rather than for individual component(3).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Draduate

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	:	Remarks: Not considered to be an inhalation hazard under normal conditions of use.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Expected to be of low toxicity:

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

1.2 2016-05-20 800001029079 D	Version	Revision Date:	SDS Number:	Pr
	1.2	2016-05-20	800001029079	Da

Print Date: 2016-05-21 Date of last issue: 21.10.2015 Date of first issue: 02.08.2012

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a skin sensitiser.

Germ cell mutagenicity

Product:

Genotoxicity in vivo

: Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies.

Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not expected to impair fertility. Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

Version	Revision Date:	SDS Number:	Print Date: 2016-05-21
1.2	2016-05-20	800001029079	Date of last issue: 21.10.2015
			Date of first issue: 02.08.2012

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).		
Ecotoxicity				
<u>Product:</u> Toxicity to fish (Acute toxici- ty)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l		
Toxicity to crustacean (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l		
Toxicity to algae/aquatic plants (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l		
Toxicity to fish (Chronic tox- icity)	:	Remarks: Data not available		
Toxicity to crustacean (Chronic toxicity) Toxicity to microorganisms (Acute toxicity)	:	Remarks: Data not available		
	:	Remarks: Data not available		
Persistence and degradability				
Product: Biodegradability	:	Remarks: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegrada- ble, but contains components that may persist in the environ- ment.		

Version 1.2	Revision Date: 2016-05-20	SDS Number: 800001029079	Print Date: 2016-05-21 Date of last issue: 21.10.2015 Date of first issue: 02.08.2012			
Bio	accumulative potential					
Pro	duct:					
	accumulation	: Remarks: Co cumulate.	ontains components with the potential to bioac-			
	ition coefficient: n- nol/water	: Pow: > 6 Remarks: (ba	ased on information on similar products)			
Mot	oility in soil					
Pro	duct:					
Mot			: Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.			
		Remarks: Flo	pats on water.			
Oth	er adverse effects					
Pro	duct:					
	Additional ecological infor- mation	expected to I Not expected	mixture of non-volatile components, which are not be released to air in any significant quantities. It to have ozone depletion potential, photochemi- eation potential or global warming potential.			
		Poorly solubl May cause p	e mixture. hysical fouling of aquatic organisms.			
			not expected to cause any chronic effects to nisms at concentrations less than 1 mg/l.			

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods Waste from residues	: Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
	Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or na- tional requirements and must be complied with.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Revision Date:

2016-05-20

Version

1.2

	2010 00 20			Date of first issue: 02.08.2012
SECTIO	ON 14. TRANSPORT INFO	RM	ATION	
Nationa	al Regulations			
TD No	G It regulated as a dangerous	goo	od	
Interna	tional Regulation			
	TA-DGR tregulated as a dangerous	goo	od	
	DG-Code It regulated as a dangerous	goo	od	
Transp	ort in bulk according to A	nne	x II of MARPOL 7	3/78 and the IBC Code
Sh Pro	llution category ip type oduct name ecial precautions	:	Not applicable Not applicable Not applicable Not applicable	
Specia	I precautions for user			
Re	emarks	:	for special precau	ns: Refer to Chapter 7, Handling & Storage, tions which a user needs to be aware of or vith in connection with transport.
Ad	lditional Information	:	MARPOL Annex	1 rules apply for bulk shipments by sea.

SDS Number:

800001029079

Print Date: 2016-05-21

Date of last issue: 21.10.2015

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

The components of this product are reported in the following inventories:				
EINECS	:	All components listed or polymer exempt.		
TSCA	:	All components listed.		
DSL	:	All components listed.		

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

Version 1.2	Revision Date: 2016-05-20	SDS Number: 800001029079	Print Date: 2016-05-21 Date of last issue: 21.10.2015 Date of first issue: 02.08.2012

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version. Revision Date : 2016-05-20

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN