

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version	Revision Date:	SDS Number:	Print Date: 2016-04-29
1.3	2016-04-28	800001005761	Date of last issue: 11.04.2016
			Date of first issue: 18.10.2010

---

### SECTION 1. IDENTIFICATION

Product name : Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil  
Product code : 001D7556

#### Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Canada Products**  
400 - 4th Avenue S.W  
Calgary AB T2P 0J4  
Canada

Telephone : (+1) 8006611600  
Telefax : (+1) 4033848345

Emergency telephone number : CHEMTREC (24 hr): 1 (703) 527-3887 or 1 (800) 424-9300 (US)  
CANUTEC (24 hr): (+1) 613-996-6666; Toll Free: 1-888-CAN-UTEC (226-8832)

#### Recommended use of the chemical and restrictions on use

Recommended use : Engine oil.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Not a hazardous substance or mixture.

#### GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:  
Not classified as a physical hazard under GHS criteria.  
HEALTH HAZARDS:  
Not classified as a health hazard under GHS criteria.  
ENVIRONMENTAL HAZARDS:  
Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**  
No precautionary phrases.  
**Response:**

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

No precautionary phrases.

**Storage:**

No precautionary phrases.

**Disposal:**

No precautionary phrases.

**Other hazards which do not result in classification**

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name : Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Chemical nature : Highly refined mineral oil.  
Synthetic base oil and additives.  
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

\* contains one or more of the following CAS-numbers: 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9.

**Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Polyolefin Amide Alkeneamine Polyol	Not Assigned	< 3
Alkaryl amine	Not Assigned	< 3
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	0 - 90

### SECTION 4. FIRST-AID MEASURES

General advice : Not expected to be a health hazard when used under normal conditions.

If inhaled : No treatment necessary under normal conditions of use.  
If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.  
If persistent irritation occurs, obtain medical attention.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version	Revision Date:	SDS Number:	Print Date: 2016-04-29
1.3	2016-04-28	800001005761	Date of last issue: 11.04.2016
			Date of first issue: 18.10.2010

- |   |   |
|---|---|
| If swallowed  | : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.  |
| Most important symptoms and effects, both acute and delayed | : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. |
| Protection of first-aiders                                  | : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.                         |
| Notes to physician  | : Treat symptomatically.  |

### SECTION 5. FIRE-FIGHTING MEASURES

- |   |  |
|---|--|
| Suitable extinguishing media                  | : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.   |
| Unsuitable extinguishing media                | : Do not use water in a jet.   |
| Specific hazards during fire-fighting         | : Hazardous combustion products may include:<br>A complex mixture of airborne solid and liquid particulates and gases (smoke).<br>Carbon monoxide may be evolved if incomplete combustion occurs.<br>Unidentified organic and inorganic compounds.   |
| Specific extinguishing methods                | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  |
| Special protective equipment for firefighters | : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469). |

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |   |   |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Avoid contact with skin and eyes.   |
| Environmental precautions   | : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. |
|   | Local authorities should be advised if significant spillages  |

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

cannot be contained.

Methods and materials for  
containment and cleaning up

: Slippery when spilt. Avoid accidents, clean up immediately.  
Prevent from spreading by making a barrier with sand, earth  
or other containment material.  
Reclaim liquid directly or in an absorbent.  
Soak up residue with an absorbent such as clay, sand or other  
suitable material and dispose of properly.

Additional advice

: For guidance on selection of personal protective equipment  
see Chapter 8 of this Safety Data Sheet.  
For guidance on disposal of spilled material see Chapter 13 of  
this Safety Data Sheet.

### SECTION 7. HANDLING AND STORAGE

General Precautions

: Use local exhaust ventilation if there is risk of inhalation of  
vapours, mists or aerosols.  
Use the information in this data sheet as input to a risk as-  
sessment of local circumstances to help determine appropri-  
ate controls for safe handling, storage and disposal of this  
material.

Advice on safe handling

: Avoid prolonged or repeated contact with skin.  
Avoid inhaling vapour and/or mists.  
When handling product in drums, safety footwear should be  
worn and proper handling equipment should be used.  
Properly dispose of any contaminated rags or cleaning mate-  
rials in order to prevent fires.

Avoidance of contact

: Strong oxidising agents.

Product Transfer

: This material has the potential to be a static accumulator.  
Proper grounding and bonding procedures should be used  
during all bulk transfer operations.

#### Storage

Other data

: Keep container tightly closed and in a cool, well-ventilated  
place.  
Use properly labeled and closable containers.

Store at ambient temperature.

Packaging material

: Suitable material: For containers or container linings, use mild  
steel or high density polyethylene.  
Unsuitable material: PVC.

Container Advice

: Polyethylene containers should not be exposed to high tem-  
peratures because of possible risk of distortion.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhalable fraction))	5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH

#### Biological occupational exposure limits

No biological limit allocated.

#### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany

<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

#### Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:  
Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

### Personal protective equipment

Respiratory protection

: No respiratory protection is ordinarily required under normal conditions of use.  
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.  
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

Hand protection  
Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

- Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
- Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes.  
It is good practice to wear chemical resistant gloves.
- Thermal hazards : Not applicable
- Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

### Environmental exposure controls

- General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.  
Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Liquid at room temperature.
- Colour : clear
- Odour : Slight hydrocarbon
- Odour Threshold : Data not available
- pH : Not applicable
- pour point : -36 °C / -33 °F  
Method: ASTM D97

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

Initial boiling point and boiling range	: > 280 °C / 536 °F estimated value(s)
Flash point	: 229 °C / 444 °F  Method: ASTM D93 (PMCC)
Evaporation rate	: Data not available
Flammability (solid, gas)	: Data not available
Upper explosion limit	: Typical 10 %(V)
Lower explosion limit	: Typical 1 %(V)
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)
Relative vapour density	: > 1 estimated value(s)
Relative density	: 0.880 - 0.890 (15 °C / 59 °F)
Density	: 880 - 890 kg/m <sup>3</sup> (15.0 °C / 59.0 °F)Method: Unspecified
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n-octanol/water	: Pow: > 6 (based on information on similar products)
Auto-ignition temperature	: > 320 °C / 608 °F
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: 47.7 mm <sup>2</sup> /s (40.0 °C / 104.0 °F) Method: ASTM D445  8.2 mm <sup>2</sup> /s (100 °C / 212 °F) Method: ASTM D445
Explosive properties	: Not classified
Oxidizing properties	: Data not available
Conductivity	: This material is not expected to be a static accumulator.
Decomposition temperature	: Data not available



# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
----------------------	---

#### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity	: LD50 (rat): > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	: Remarks: Not considered to be an inhalation hazard under normal conditions of use.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: Expected to be of low toxicity:

#### Skin corrosion/irritation

##### Product:

Remarks: Expected to be slightly irritating.  
Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

---

### Serious eye damage/eye irritation

#### Product:

Remarks: Expected to be slightly irritating.

### Respiratory or skin sensitisation

#### Product:

Remarks: Not expected to be a skin sensitiser.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vivo : Remarks: Not considered a mutagenic hazard.

### Carcinogenicity

#### Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies.  
Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

### Reproductive toxicity

#### Product:

Effects on fertility :  
Remarks: Not expected to impair fertility.  
Not expected to be a developmental toxicant.

### STOT - single exposure

#### Product:

Remarks: Not expected to be a hazard.

### STOT - repeated exposure

#### Product:

Remarks: Not expected to be a hazard.

### Aspiration toxicity

#### Product:

Not considered an aspiration hazard.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

### Further information

#### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

## SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically for this product.  
Information given is based on a knowledge of the components and the ecotoxicology of similar products.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). (LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

### Ecotoxicity

#### Product:

Toxicity to fish (Acute toxicity) : Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to crustacean (Acute toxicity) : Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic plants (Acute toxicity) : Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to crustacean (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms (Acute toxicity) : Remarks: Data not available

### Persistence and degradability

#### Product:

Biodegradability : Remarks: Expected to be not readily biodegradable.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

Partition coefficient: n-octanol/water : Pow: > 6  
Remarks: (based on information on similar products)

### Mobility in soil

#### Product:

Mobility : Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

### Other adverse effects

#### Product:

Additional ecological information : Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

Poorly soluble mixture.  
May cause physical fouling of aquatic organisms.

Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version  
1.3

Revision Date:  
2016-04-28

SDS Number:  
800001005761

Print Date: 2016-04-29  
Date of last issue: 11.04.2016  
Date of first issue: 18.10.2010

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

### SECTION 14. TRANSPORT INFORMATION

#### National Regulations

##### TDG

Not regulated as a dangerous good

#### International Regulation

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable  
Ship type : Not applicable  
Product name : Not applicable  
Special precautions : Not applicable

#### Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

**Additional Information** : MARPOL Annex 1 rules apply for bulk shipments by sea.

### SECTION 15. REGULATORY INFORMATION

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

#### The components of this product are reported in the following inventories:

EINECS : All components listed or polymer exempt.

TSCA : All components listed.

DSL : All components listed.

# SAFETY DATA SHEET

According to the Hazardous Products Regulations

## Quaker State Enhanced Durability SAE 5W-20 Synthetic Blend Motor Oil

Version	Revision Date:	SDS Number:	Print Date: 2016-04-29
1.3	2016-04-28	800001005761	Date of last issue: 11.04.2016
			Date of first issue: 18.10.2010

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Revision Date : 2016-04-28

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN