ersion .4	Revision Date: 2017-02-06		DS Number: 00001028992	Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012
ECTION	1. IDENTIFICATION			
Produ	ict name	:	Shell Rotella T6 ()W-40
Produ	Product code		001E3851	
Manufacturer or supplier's details				
Manu	facturer/Supplier	:	Shell Canada Pr 400 - 4th Avenue Calgary AB T2P Canada	S.W
Telep Telefa			(+1) 8006611600 (+1) 4033848345	
Emero ber	gency telephone num-	:	(US)	hr): 1 (703) 527-3887 or 1 (800) 424-9300): (+1) 613-996-6666; Toll Free: 1-888-CAN-)
Reco	mmended use of the c	hen	nical and restriction	

Recommended use of the chemical and restrictions on use

Recommended use	: Engine oil.	
-----------------	---------------	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Precautionary statements	: Prevention: No precautionary phrases. Response:
	Not classified as an environmental hazard under GHS criteria.
	HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS:
Hazard statements	: PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria.
Signal word	: No signal word
Hazard pictograms	: No Hazard Symbol required

Version	Revision Date:	SDS Number:	Print Date: 2017-02-07
1.4	2017-02-06	800001028992	Date of last issue: 23.05.2016
			Date of first issue: 27.09.2012

No precautionary phrases. **Disposal:** No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.

Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

9.

Substance name	: Shell Rotella T6 0W-40
Chemical nature	 Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. The highly refined mineral oil is only present as additive dilu- ent.
	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Zinc dialkyl dithiophosphate	84605-29-8	1 - 2.4
Calcium sulphonate	70024-69-0	0.10 - 0.99
Interchangeable low viscosity base oil (<20,5 cSt	Not Assigned	0 - 90
@40°C) *		

SECTION 4. FIRST-AID MEASURES

General advice	Not expected to be a health hazard when used under nor conditions.	mal
If inhaled	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.	
In case of skin contact	Remove contaminated clothing. Flush exposed area with ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.	wa-
In case of eye contact	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Contin rinsing. If persistent irritation occurs, obtain medical attention.	ue

Version 1.4	Revision Date: 2017-02-06	SDS Number: 800001028992	Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012	
If swallowed		: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.		
	t important symptoms effects, both acute and yed	 Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. 		
Prot	ection of first-aiders	appropriate pe	tering first aid, ensure that you are wearing the ersonal protective equipment according to the and surroundings.	
Note	es to physician	: Treat symptor	natically.	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	Avoid contact with skin and eyes.	
Environmental precautions	Use appropriate containment to avoid environmental connation. Prevent from spreading or entering drains, ditcher rivers by using sand, earth, or other appropriate barriers	es or
	Local authorities should be advised if significant spillage cannot be contained.	s

Version 1.4	Revision Date: 2017-02-06	SDS Number: 800001028992	Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012
Methods and materials for containment and cleaning up		Prevent from s or other contain Reclaim liquid Soak up residu	spilt. Avoid accidents, clean up immediately. preading by making a barrier with sand, earth nment material. directly or in an absorbent. e with an absorbent such as clay, sand or other al and dispose of properly.
Add	itional advice	see Chapter 8	n selection of personal protective equipment of this Safety Data Sheet. n disposal of spilled material see Chapter 13 of a Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
Storage		
Other data	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

Version	Revision Date:	SDS Number:	Print Date: 2017-02-07
1.4	2017-02-06	800001028992	Date of last issue: 23.05.2016
			Date of first issue: 27.09.2012

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhal- able frac- tion))	5 mg/m3	US. ACGIH Threshold Limit Values
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

 Engineering measures
 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
 Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
 General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Version 1.4	Revision Date: 2017-02-06	SDS Number: 800001028992	Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012
		equipment used equipment, loca Drain down syst nance. Retain drain dow subsequent recy Always observe washing hands drinking, and/or protective equip	good personal hygiene measures, such as after handling the material and before eating, smoking. Routinely wash work clothing and ment to remove contaminants. Discard con- ng and footwear that cannot be cleaned.
Pers	onal protective equip	ment	
Resp	iratory protection	conditions of us In accordance w tions should be If engineering co tions to a level w select respirator cific conditions of Check with resp Where air-filterin priate combinati Select a filter su	rotection is ordinarily required under normal e. with good industrial hygiene practices, precau- taken to avoid breathing of material. ontrols do not maintain airborne concentra- which is adequate to protect worker health, ry protection equipment suitable for the spe- of use and meeting relevant legislation. wiratory protective equipment suppliers. Ing respirators are suitable, select an appro- on of mask and filter. witable for the combination of organic gases ype A/Type P boiling point >65°C (149°F)].
	I protection emarks	gloves approved US: F739) made suitable chemica gloves Suitabilit usage, e.g. freq sistance of glove glove suppliers. Personal hygien Gloves must on gloves, hands si cation of a non- For continuous of through time of 480 minutes wh short-term/splas recognize that si may not be avai time maybe acc and replacement a good predictor	htact with the product may occur the use of d to relevant standards (e.g. Europe: EN374, e from the following materials may provide al protection. PVC, neoprene or nitrile rubber y and durability of a glove is dependent on uency and duration of contact, chemical re- e material, dexterity. Always seek advice from Contaminated gloves should be replaced. he is a key element of effective hand care. by be worn on clean hands. After using hould be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- more than 240 minutes with preference for > ere suitable gloves can be identified. For sh protection we recommend the same, but uitable gloves offering this level of protection lable and in this case a lower breakthrough eptable so long as appropriate maintenance at regimes are followed. Glove thickness is not r of glove resistance to a chemical as it is ne exact composition of the glove material.

Version 1.4	Revision Date: 2017-02-06	SDS Number: 800001028992	Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012
			ss should be typically greater than 0.35 mm the glove make and model.
Eye protection			andled such that it could be splashed into eyes, wear is recommended.
Skin and body protection		 Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves. 	
Therr	mal hazards	: Not applicable	
Prote	ective measures		ective equipment (PPE) should meet recom- nal standards. Check with PPE suppliers.

Environmental exposure controls

General advice	 Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
	vapour.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid at high temperatures.
Colour	:	amber
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	-51 °C / -60 °F Method: ASTM D97
Initial boiling point and boiling range	:	> 280 °C / 536 °F estimated value(s)
Flash point	:	226 °C / 439 °F
		Method: ASTM D92 (COC)

Vers 1.4	sion	Revision Date: 2017-02-06		S Number: 0001028992	Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012
	Evapor	ration rate	:	Data not availabl	e
	Flamm	ability (solid, gas)	:	Data not availabl	e
	Upper	explosion limit	:	Typical 10 %(V)	
	Lower	explosion limit	:	Typical 1 %(V)	
	Vapour	rpressure	:	< 0.5 Pa (20 °C / estimated value(
	Relativ	e vapour density	:	> 1 estimated value(s)
	Relativ	e density	:	0.845 (15 °C / 59)°F)
	Density	4	:	845 kg/m3 (15.0	°C / 59.0 °F)Method: ASTM D4052
	Solubil Wate	ity(ies) er solubility	:	negligible	
	Solu	bility in other solvents	:	Data not availabl	e
	Partitio octano	n coefficient: n- I/water	:	Pow: > 6 (based on inform	ation on similar products)
	Auto-ig	nition temperature	:	> 320 °C / 608 °F	=
	Viscosi Visc	ity osity, dynamic	:	Data not availabl	e
	Visc	osity, kinematic	:	75 mm2/s (40.0 ° Method: ASTM [
				13.2 mm2/s (100 Method: ASTM [°C / 212 °F) 0445
	Explos	ive properties	:	Not classified	
	Oxidizi	ng properties	:	Data not availabl	e
	Condu	ctivity	:	This material is r	not expected to be a static accumulator.
	Decom	position temperature	:	Data not availabl	e

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
8 / 14		800001028992

Version 1.4	Revision Date: 2017-02-06	SDS Number: 800001028992	Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012
Poss	sibility of hazardous reac	- : Reacts with	strong oxidising agents.
Con	ditions to avoid	: Extremes of	temperature and direct sunlight.
Inco	mpatible materials	: Strong oxidi	sing agents.
Haza prod	ardous decomposition ucts	: Hazardous during norm	decomposition products are not expected to form al storage.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
		whole, rather than for individual component(3).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity	: LD50 (rat): > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	: Remarks: Not considered to be an inhalation hazard under normal conditions of use.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: Expected to be of low toxicity:

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Components:

Zinc dialkyl dithiophosphate:

Remarks: Based on available data, the classification criteria are not met.

Version	Revision Date:	SDS Number:	Print Date
1.4	2017-02-06	800001028992	Date of la
			D () ()

Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a skin sensitiser.

Components:

Calcium sulphonate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Germ cell mutagenicity

Product:

Genotoxicity in vivo

: Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not expected to impair fertility. Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product: Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the

Version	Revision Date:	SDS Number:	Print Date: 2017-02-07
1.4	2017-02-06	800001028992	Date of last issue: 23.05.2016
			Date of first issue: 27.09.2012

environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment :	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity	
Product: Toxicity to fish (Acute toxici- ty)	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to crustacean (Acute : toxicity)	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to algae/aquatic : plants (Acute toxicity)	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to fish (Chronic tox- : icity)	Remarks: Data not available
Toxicity to crustacean : (Chronic toxicity)	Remarks: Data not available
Toxicity to microorganisms : (Acute toxicity)	Remarks: Data not available
Persistence and degradability	
Product: Biodegradability :	Remarks: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegrada- ble, but contains components that may persist in the environ- ment.

Version 1.4	Revision Date: 2017-02-06	SDS Number: 800001028992	Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012	
Bioac	cumulative potential			
<u>Produ</u> Bioace	<u>ıct:</u> cumulation	: Remarks: Col cumulate.	: Remarks: Contains components with the potential to bioac- cumulate.	
	on coefficient: n- bl/water	: Pow: > 6 Remarks: (ba	Pow: > 6 Remarks: (based on information on similar products)	
Mobil	ity in soil			
<u>Product:</u> Mobility		lf it enters soi mobile.		
		Remarks: Flo	ats on water.	
Other	adverse effects			
Produ Additio mation	onal ecological infor-	expected to b Not expected cal ozone cre Poorly soluble	nixture of non-volatile components, which are not e released to air in any significant quantities. to have ozone depletion potential, photochemi- ation potential or global warming potential. e mixture. hysical fouling of aquatic organisms.	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth- ods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Version 1.4	Revision Date: 2017-02-06	SDS Number: 800001028992	Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012	
Local legislation Remarks			: Disposal should be in accordance with applicable regional, national, and local laws and regulations.	
SECTION	14. TRANSPORT INI	FORMATION		
National F	Regulations			
TDG Not re	egulated as a dangero	ous good		
Internatio	nal Regulations			
	-DGR egulated as a dangero	ous good		
-	-Code egulated as a dangero	ous good		
Transport	t in bulk according to	o Annex II of MARPOI	_ 73/78 and the IBC Code	
Ship t Produ	tion category type uct name ial precautions	 Not applicable Not applicable Not applicable Not applicable Not applicable 		
Special p	recautions for user			
Rema	arks	for special prec	tions: Refer to Chapter 7, Handling & Storage, autions which a user needs to be aware of or y with in connection with transport.	
Addit	tional Information	: MARPOL Anne	ex 1 rules apply for bulk shipments by sea.	

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

The components of this product are reported in the following inventories:		
EINECS	: All components listed or polymer exempt.	
TSCA	: All components listed.	
DSL	: All components listed.	

Version	Revision Date:	SDS Number:
1.4	2017-02-06	800001028992

Print Date: 2017-02-07 Date of last issue: 23.05.2016 Date of first issue: 27.09.2012

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version. Revision Date : 2017-02-06

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN