Version 1.1	Revision Date: 2016-10-14	SDS Number: 800010026864	Print Date: 2016-10-15 Date of last issue: 18.04.2016 Date of first issue: 18.04.2016	
SECTION	1. IDENTIFICATION			
Product name		: Shell Rotella T6 5W-40		
Product code		: 001F8875		
Manufacturer or supplier's details				
Manı	ufacturer/Supplier	: Shell Canada F 400 - 4th Avenu Calgary AB T2I	e S.W	

Canada

Telephone Telefax	:	(+1) 8006611600 (+1) 4033848345
Emergency telephone num- ber	:	CHEMTREC (24 hr): 1 (703) 527-3887 or 1 (800) 424-9300 (US) CANUTEC (24 hr): (+1) 613-996-6666; Toll Free: 1-888-CAN- UTEC (226-8832)

### Recommended use of the chemical and restrictions on use

Recommended use	: Engine oil.
-----------------	---------------

## **SECTION 2. HAZARDS IDENTIFICATION**

### **GHS Classification**

Not a hazardous substance or mixture.

## GHS label elements

Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	<ul> <li>PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.</li> </ul>
Precautionary statements	<ul> <li>Prevention: No precautionary phrases.</li> <li>Response: No precautionary phrases.</li> </ul>
14	800010026864

Version	Revision Date:	SDS Number:	Print Date: 2016-10-15
1.1	2016-10-14	800010026864	Date of last issue: 18.04.2016
			Date of first issue: 18.04.2016

#### Storage:

No precautionary phrases. **Disposal:** No precautionary phrases.

#### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name	: Shell Rotella T6 5W-40
Chemical nature	<ul> <li>Highly refined mineral oils and additives. The highly refined mineral oil contains &lt;3% (w/w) DMSO- extract, according to IP346.</li> </ul>
	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9.

#### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Zinc dialkyldithiophosphate	113706-15-3	1 - 2.4
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	0 - 90

### **SECTION 4. FIRST-AID MEASURES**

General advice	Not expected to be a health hazard when used under no conditions.	ormal
If inhaled	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.	
In case of skin contact	Remove contaminated clothing. Flush exposed area with ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.	h wa-
In case of eye contact	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.	
If swallowed	In general no treatment is necessary unless large quant are swallowed, however, get medical advice.	ities
Most important symptoms	Oil acne/folliculitis signs and symptoms may include forr	nation

Version 1.1	Revision Date: 2016-10-14	SDS Number: 800010026864	Print Date: 2016-10-15 Date of last issue: 18.04.2016 Date of first issue: 18.04.2016
and effects, both acute and delayed			es and spots on the skin of exposed areas. result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders		: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.	
Notes to physician		: Treat symptom	atically.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

## SECTION 6. ACCIDENTAL RELEASE MEASURES

	Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
	Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
			Local authorities should be advised if significant spillages cannot be contained.
	Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material.
,	1 /		800010026864

Version 1.1	Revision Date: 2016-10-14	SDS Number: 800010026864	Print Date: 2016-10-15 Date of last issue: 18.04.2016 Date of first issue: 18.04.2016
		Soak up residu	directly or in an absorbent. e with an absorbent such as clay, sand or other al and dispose of properly.
Additional advice		see Chapter 8	n selection of personal protective equipment of this Safety Data Sheet. n disposal of spilled material see Chapter 13 of a Sheet.

## SECTION 7. HANDLING AND STORAGE

General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
Storage		
Other data	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

Version	Revision Date:	SDS Number:	Print Date: 2016-10-15
1.1	2016-10-14	800010026864	Date of last issue: 18.04.2016
			Date of first issue: 18.04.2016

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhal- able frac- tion))	5 mg/m3	US. ACGIH Threshold Limit Values
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

#### **Biological occupational exposure limits**

No biological limit allocated.

### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this

Version 1.1	Revision Date: 2016-10-14	SDS Number: 800010026864	Print Date: 2016-10-15 Date of last issue: 18.04.2016 Date of first issue: 18.04.2016
		equipment used equipment, local Drain down syste nance. Retain drain dow subsequent recy Always observe washing hands a drinking, and/or s protective equipr	good personal hygiene measures, such as ifter handling the material and before eating, smoking. Routinely wash work clothing and nent to remove contaminants. Discard con- ng and footwear that cannot be cleaned.
Perso	onal protective equip	ment	
	iratory protection	: No respiratory pr conditions of use In accordance wi tions should be to If engineering co tions to a level w select respiratory cific conditions o Check with respi Where air-filterin priate combination Select a filter sui	rotection is ordinarily required under normal b. ith good industrial hygiene practices, precau- aken to avoid breathing of material. ntrols do not maintain airborne concentra- hich is adequate to protect worker health, / protection equipment suitable for the spe- f use and meeting relevant legislation. ratory protective equipment suppliers. g respirators are suitable, select an appro- on of mask and filter. table for the combination of organic gases /pe A/Type P boiling point >65°C (149°F)].
	protection marks	gloves approved US: F739) made suitable chemica gloves Suitability usage, e.g. frequ sistance of glove glove suppliers. O Personal hygiene Gloves must only gloves, hands sh cation of a non-p For continuous of through time of m 480 minutes whe short-term/splash recognize that su may not be availa- time maybe acce	tact with the product may occur the use of to relevant standards (e.g. Europe: EN374, from the following materials may provide al protection. PVC, neoprene or nitrile rubber and durability of a glove is dependent on tency and duration of contact, chemical re- ematerial, dexterity. Always seek advice from Contaminated gloves should be replaced. e is a key element of effective hand care. y be worn on clean hands. After using hould be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- nore than 240 minutes with preference for > ere suitable gloves can be identified. For n protection we recommend the same, but uitable gloves offering this level of protection able and in this case a lower breakthrough eptable so long as appropriate maintenance t regimes are followed. Glove thickness is not

Version 1.1	Revision Date: 2016-10-14	SDS Number: 800010026864	Print Date: 2016-10-15 Date of last issue: 18.04.2016 Date of first issue: 18.04.2016
		dependent on Glove thicknes	or of glove resistance to a chemical as it is the exact composition of the glove material. Is should be typically greater than 0.35 mm the glove make and model.
Eye p	rotection		andled such that it could be splashed into eyes, wear is recommended.
Skin a	and body protection	work clothes.	n is not ordinarily required beyond standard tice to wear chemical resistant gloves.
Thern	nal hazards	: Not applicable	
Prote	ctive measures		ctive equipment (PPE) should meet recom- al standards. Check with PPE suppliers.
Envir	onmental exposure c	ontrols	

General advice	<ul> <li>Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.</li> <li>Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.</li> </ul>

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	Clear amber
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	-42 °C / -44 °F Method: ASTM D97
Initial boiling point and boiling range	:	> 280 °C / 536 °F estimated value(s)
Flash point	:	224 °C / 435 °F

Version 1.1	Revision Date: 2016-10-14	SDS Number:Print Date: 2016-10-15800010026864Date of last issue: 18.04.2016Date of first issue: 18.04.2016	
		Method: ASTM D92 (COC)	
Ev	aporation rate	: Data not available	
Fla	mmability (solid, gas)	: Data not available	
Up	per explosion limit	: Typical 10 %(V)	
Lo	wer explosion limit	: Typical 1 %(V)	
Va	pour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Re	lative vapour density	: > 1 estimated value(s)	
Re	lative density	: 0.858 (15 °C / 59 °F)	
De	nsity	: 858 kg/m3 (15.0 °C / 59.0 °F)Method: ASTM D4052	
	lubility(ies) Water solubility	: negligible	
:	Solubility in other solvents	: Data not available	
	rtition coefficient: n- anol/water	: Pow: > 6 (based on information on similar products)	
Au	to-ignition temperature	: > 320 °C / 608 °F	
	cosity Viscosity, dynamic	: Data not available	
,	Viscosity, kinematic	: 14.2 mm2/s (100 °C / 212 °F) Method: ASTM D445	
Ex	plosive properties	: Not classified	
Ox	idizing properties	: Data not available	
Co	nductivity	: This material is not expected to be a static accumulato	r.
De	composition temperature	: Data not available	

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in
	addition to those listed in the following sub-paragraph.

Versio	on Revision Date: 2016-10-14	SDS Number: 800010026864	Print Date: 2016-10-15 Date of last issue: 18.04.2016 Date of first issue: 18.04.2016
(	Chemical stability	: Stable.	
	Possibility of hazardous tions	reac- : Reacts with s	strong oxidising agents.
(	Conditions to avoid	: Extremes of	temperature and direct sunlight.
I	Incompatible materials	: Strong oxidis	ing agents.
	Hazardous decomposit products	ion : Hazardous d during norma	ecomposition products are not expected to form al storage.

## SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise,
	the data presented is representative of the product as a whole, rather than for individual component(s).

### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

### Acute toxicity

Product:	
Acute oral toxicity	: LD50 (rat): > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	: Remarks: Not considered to be an inhalation hazard under normal conditions of use.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: Expected to be of low toxicity:

### Skin corrosion/irritation

## Product:

Remarks: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

#### Serious eye damage/eye irritation

#### Product:

Remarks: Expected to be slightly irritating.

#### Components:

Zinc dialkyldithiophosphate:

Version	Revision Date:	SDS Number:	Print Date: 2016-10-15
1.1	2016-10-14	800010026864	Date of last issue: 18.04.2016
			Date of first issue: 18.04.2016

Remarks: Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

#### Product:

Remarks: Not expected to be a skin sensitiser.

#### Germ cell mutagenicity

#### Product:

Genotoxicity in vivo

: Remarks: Not considered a mutagenic hazard.

### Carcinogenicity

## Product:

Remarks: Not expected to be carcinogenic.

#### **Reproductive toxicity**

#### Product:

Effects on fertility

Remarks: Not expected to impair fertility. Not expected to be a developmental toxicant.

### STOT - single exposure

### Product:

Remarks: Not expected to be a hazard.

### STOT - repeated exposure

### Product:

Remarks: Not expected to be a hazard.

### **Aspiration toxicity**

### Product:

Not considered an aspiration hazard.

### **Further information**

### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

VersionRevision Date:SDS Nu1.12016-10-14800010	
--	--

Remarks: Slightly irritating to respiratory system.

### **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment	this product. ormation given is base I the ecotoxicology of less indicated otherwi e of the product as a v nent(s).(LL/EL/IL50 ex	ve not been determined specifically ed on a knowledge of the components similar products. ise, the data presented is representa- vhole, rather than for individual com- kpressed as the nominal amount of are aqueous test extract).	
Ecotoxicity			
<u>Product:</u> Toxicity to fish (Acute toxici- ty)	marks: Expected to b EL/IL50 > 100 mg/l	e practically non toxic:	
Toxicity to crustacean (Acute toxicity)	marks: Expected to b EL/IL50 > 100 mg/l	e practically non toxic:	
Toxicity to algae/aquatic plants (Acute toxicity)	marks: Expected to b EL/IL50 > 100 mg/l	e practically non toxic:	
Toxicity to fish (Chronic tox- icity)	marks: Data not avail	able	
Toxicity to crustacean	marks: Data not avail	able	
(Chronic toxicity) Toxicity to microorganisms (Acute toxicity)	marks: Data not avail	able	
Persistence and degradability			
<u>Product:</u> Biodegradability	jor constituents are e	e not readily biodegradable. xpected to be inherently biodegrada- nents that may persist in the environ-	
Bioaccumulative potential			
Product: Bioaccumulation	marks: Contains com nulate.	ponents with the potential to bioac-	

Version 1.1	Revision Date: 2016-10-14	SDS Number: 800010026864	Print Date: 2016-10-15 Date of last issue: 18.04.2016 Date of first issue: 18.04.2016	
	Partition coefficient: n- octanol/water		: Pow: > 6 Remarks: (based on information on similar products)	
Mobility in soil				
<u>Product:</u> Mobility		lf it enters soil mobile.	<ul> <li>Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.</li> <li>Remarks: Floats on water.</li> </ul>	
Othe	r adverse effects			
Product: Additional ecological infor- mation		expected to b Not expected cal ozone created Poorly soluble	nixture of non-volatile components, which are not e released to air in any significant quantities. to have ozone depletion potential, photochemi- ation potential or global warming potential. e mixture. hysical fouling of aquatic organisms.	

## SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>Recover or recycle if possible.</li> <li>It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.</li> <li>Do not dispose into the environment, in drains or in water courses</li> </ul>
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks	: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

12 / 14

Version	Revision Date:	SDS Number:	I
1.1	2016-10-14	800010026864	l

Print Date: 2016-10-15 Date of last issue: 18.04.2016 Date of first issue: 18.04.2016

## **SECTION 14. TRANSPORT INFORMATION**

#### **National Regulations**

TDG

Not regulated as a dangerous good

#### **International Regulations**

#### IATA-DGR

Not regulated as a dangerous good

**IMDG-Code** Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category Ship type Product name Special precautions	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
pecial precautions for user	
Remarks	: Special Precautions:

## Sp

Remarks	: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
Additional Information	: MARPOL Annex 1 rules apply for bulk shipments by sea.

### **SECTION 15. REGULATORY INFORMATION**

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

The components of this product are reported in the following inventories:			
EINECS	: All components listed or polymer exempt.		
TSCA	: All components listed.		
DSL	: All components listed.		

### **SECTION 16. OTHER INFORMATION**

### Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -

Version 1.1	Revision Date: 2016-10-14	SDS Number: 800010026864	Print Date: 2016-10-15 Date of last issue: 18.04.2016 Date of first issue: 18.04.2016

Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version. Revision Date : 2016-10-14

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN