Version 1.0	Revision Date: 2016-09-14		DS Number: 00010027858	Print Date: 2016-09-15 Date of last issue: - Date of first issue: 14.09.2016		
SECTION	1. IDENTIFICATION					
Produ	uct name	:	Shell Rotella T5 l	Jltra 10W-30		
Produ	uct code	:	: 001F8879			
Manufacturer or supplier's details						
Manu	facturer/Supplier	:	Shell Canada Pr 400 - 4th Avenue Calgary AB T2P Canada	S.W		
Telep Telefa		:	(+1) 8006611600 (+1) 4033848345			
Emer ber	gency telephone num-	:	UTEC (226-8832): (+1) 613-996-6666; Toll Free: 1-888-CAN-) hr): 1 (703) 527-3887 or 1 (800) 424-9300		

Recommended use of the chemical and restrictions on use

Recommended use	: Engine oil.
-----------------	---------------

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Chronic aquatic toxicity	: Category 3
GHS label elements	
Hazard pictograms	: No symbol
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	 Prevention: P273 Avoid release to the environment. Response: No precautionary phrases.
14	800010027858

Version	Revision Date:	SDS Number:	Print Date: 2016-09-15
1.0	2016-09-14	800010027858	Date of last issue: -
			Date of first issue: 14.09.2016

Storage:

No precautionary phrases. **Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name	: Shell Rotella T5 Ultra 10W-30
Chemical nature	 Highly refined mineral oil. Synthetic base oil and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9.

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Alkaryl amine	36878-20-3	1 - 3
Calcium sulphonate	70024-69-0	0.1 - 0.99
Alkyl borate	Not Assigned	0.1 - 0.99
Dialkyl alkaryl aminomethyl dicarboxylate	Not Assigned	0.1 - 0.99
Alkoxylated alcohol	68551-12-2	0.1 - 0.99
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	0 - 90

SECTION 4. FIRST-AID MEASURES

General advice	: Not expected to be a health hazard when used under normal conditions.
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	 Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

Version 1.0	Revision Date: 2016-09-14	SDS Number: 800010027858	Print Date: 2016-09-15 Date of last issue: - Date of first issue: 14.09.2016	
lf sw	allowed		reatment is necessary unless large quantities , however, get medical advice.	
	t important symptoms effects, both acute and yed	: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.		
Protection of first-aiders		: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.		
Note	s to physician	: Treat sympton	natically.	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
A A		000040007050

Version 1.0	Revision Date: 2016-09-14	SDS Number: 800010027858	Print Date: 2016-09-15 Date of last issue: - Date of first issue: 14.09.2016
Methods and materials for containment and cleaning up		 Slippery when spilt. Avoid accidents, clean up immediate Prevent from spreading by making a barrier with sand, ea or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or suitable material and dispose of properly. 	
Addit	ional advice	see Chapter 8 o	selection of personal protective equipment f this Safety Data Sheet. disposal of spilled material see Chapter 13 of Sheet.

SECTION 7. HANDLING AND STORAGE

:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
:	Strong oxidising agents.
:	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
	Store at ambient temperature.
:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

Version	Revision Date:	SDS Number:	Pri
1.0	2016-09-14	800010027858	Da
			_

Print Date: 2016-09-15 Date of last issue: -Date of first issue: 14.09.2016

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhal- able frac- tion))	5 mg/m3	US. ACGIH Threshold Limit Values
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information: Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this

Version 1.0	Revision Date: 2016-09-14	SDS Number: 800010027858	Print Date: 2016-09-15 Date of last issue: - Date of first issue: 14.09.2016
		equipment used equipment, loca Drain down sys nance. Retain drain do subsequent rec Always observe washing hands drinking, and/or protective equip	good personal hygiene measures, such as after handling the material and before eating, smoking. Routinely wash work clothing and ment to remove contaminants. Discard con- ng and footwear that cannot be cleaned.
Pers	onal protective equip	ment	
Resp	viratory protection	conditions of us In accordance w tions should be If engineering c tions to a level w select respirato cific conditions Check with resp Where air-filteri priate combinat Select a filter su	protection is ordinarily required under normal e. with good industrial hygiene practices, precau- taken to avoid breathing of material. ontrols do not maintain airborne concentra- which is adequate to protect worker health, ry protection equipment suitable for the spe- of use and meeting relevant legislation. biratory protective equipment suppliers. ng respirators are suitable, select an appro- tion of mask and filter. hitable for the combination of organic gases ype A/Type P boiling point >65°C (149°F)].
	l protection emarks	gloves approve US: F739) mad suitable chemic gloves Suitabilit usage, e.g. freq sistance of glov glove suppliers. Personal hygier Gloves must on gloves, hands s cation of a non- For continuous through time of 480 minutes wh short-term/splas recognize that s may not be ava time maybe acc and replacemer	htact with the product may occur the use of d to relevant standards (e.g. Europe: EN374, e from the following materials may provide al protection. PVC, neoprene or nitrile rubber y and durability of a glove is dependent on uency and duration of contact, chemical re- e material, dexterity. Always seek advice from Contaminated gloves should be replaced. he is a key element of effective hand care. ly be worn on clean hands. After using hould be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- more than 240 minutes with preference for > ere suitable gloves can be identified. For sh protection we recommend the same, but suitable gloves offering this level of protection ilable and in this case a lower breakthrough eeptable so long as appropriate maintenance at regimes are followed. Glove thickness is not r of glove resistance to a chemical as it is

Version 1.0	Revision Date: 2016-09-14	SDS Number: 800010027858	Print Date: 2016-09-15 Date of last issue: - Date of first issue: 14.09.2016	
		Glove thickn	n the exact composition of the glove material. ess should be typically greater than 0.35 mm n the glove make and model.	
Eye protection		: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.		
Skin and body protection		work clothes	 Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves. 	
Therr	nal hazards	: Not applicab	le	
Protective measures		•	tective equipment (PPE) should meet recom- onal standards. Check with PPE suppliers.	

Environmental exposure controls

General advice	 Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
----------------	---

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: amber
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рН	: Not applicable
pour point	: -51 °C / -60 °F Method: ASTM D97
Initial boiling point and boiling range	: > 280 °C / 536 °F estimated value(s)
Flash point	: 231 °C / 448 °F
	Method: ASTM D92 (COC)

Versi 1.0	ion	Revision Date: 2016-09-14		S Number: 0010027858	Print Date: 2016-09-15 Date of last issue: - Date of first issue: 14.09.2016
I	Evaporation rate		:	Data not availabl	e
I	Flamma	ability (solid, gas)	:	Data not availabl	e
ι	Upper e	explosion limit	:	Typical 10 %(V)	
I	Lower e	explosion limit	:	Typical 1 %(V)	
N	Vapour pressure		:	< 0.5 Pa (20 °C / estimated value(
I	Relative	e vapour density	:	> 1 estimated value(s)
I	Relative	edensity	:	0.865 (15 °C / 59	∂°F)
I	Density		:	865 kg/m3 (15.0	°C / 59.0 °F)Method: ASTM D4052
Ś	Solubilii Wate	ty(ies) r solubility	:	negligible	
	Solut	oility in other solvents	:	Data not availabl	e
	Partitior octanol/	n coefficient: n- /water	:	Pow: > 6 (based on inform	nation on similar products)
/	Auto-ignition temperature		:	> 320 °C / 608 °F	=
N	Viscosit	y sity, dynamic		Data not availabl	
		osity, kinematic		66 mm2/s (40.0 °	
	viscosity, kinematic		·	Method: ASTM E	
				10 mm2/s (100 ° Method: ASTM E	
I	Explosiv	ve properties	:	Not classified	
(Oxidizir	ng properties	:	Data not availabl	le
(Conduc	tivity	:	This material is n	not expected to be a static accumulator.
I	Decom	position temperature	:	Data not availabl	e

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in
	addition to those listed in the following sub-paragraph.

Vers 1.0	ion	Revision Date: 2016-09-14		S Number: 0010027858	Print Date: 2016-09-15 Date of last issue: - Date of first issue: 14.09.2016	
	Chemio	cal stability	:	Stable.		
	Possibility of hazardous reac- tions		:	: Reacts with strong oxidising agents.		
	Conditions to avoid		:	: Extremes of temperature and direct sunlight.		
	Incompatible materials		:	Strong oxidising agents.		
	Hazardous decomposition products		:	Hazardous decomposition products are not expected to forr during normal storage.		

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and
		the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:	
Acute oral toxicity	: LD50 (rat): > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	: Remarks: Not considered to be an inhalation hazard under normal conditions of use.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: Expected to be of low toxicity:

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Respiratory or skin sensitisation

Product:

Version	Revision Date:	SDS Number:
1.0	2016-09-14	800010027858

Print Date: 2016-09-15 Date of last issue: -Date of first issue: 14.09.2016

Remarks: Not expected to be a skin sensitiser.

Components:

Calcium sulphonate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Alkyl borate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Dialkyl alkaryl aminomethyl dicarboxylate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Germ cell mutagenicity

Product:

Genotoxicity in vivo

: Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies.

Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not expected to impair fertility. Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Version	Revision Date:	SDS Number:
1.0	2016-09-14	800010027858

Print Date: 2016-09-15 Date of last issue: -Date of first issue: 14.09.2016

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the compone and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is represen tive of the product as a whole, rather than for individual com ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).	ents Ita- n-
Ecotoxicity		
<u>Product:</u> Toxicity to fish (Acute toxici- ty)	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l	
Toxicity to crustacean (Acute toxicity)	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l	
Toxicity to algae/aquatic plants (Acute toxicity)	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l	
Toxicity to fish (Chronic tox- icity)	Remarks: Data not available	
Toxicity to crustacean (Chronic toxicity)	Remarks: Data not available	
(Acute toxicity) (Acute toxicity)	Remarks: Data not available	

ersion)	Revision Date: 2016-09-14		6 Number: 010027858	Print Date: 2016-09-15 Date of last issue: - Date of first issue: 14.09.2016
Persi	stence and degradal	oility		
<u>Prod</u>				
Biode	egradability		Major constitue	cted to be not readily biodegradable. nts are expected to be inherently biodegrada s components that may persist in the environ
Bioa	ccumulative potentia	I		
Prod	<u>uct:</u>			
Bioac	cumulation		Remarks: Conta cumulate.	ains components with the potential to bioac-
	ion coefficient: n- ol/water	-	Pow: > 6 Remarks: (base	ed on information on similar products)
Mobi	lity in soil			
<u>Prod</u>	uct:			
Mobil	ity			d under most environmental conditions. t will adsorb to soil particles and will not be
			Remarks: Float	s on water.
Othe	r adverse effects			
Prod	uct:			
Addit matic	ional ecological infor- n		expected to be Not expected to	cture of non-volatile components, which are r released to air in any significant quantities. have ozone depletion potential, photochemi ion potential or global warming potential.
			Poorly soluble r May cause phys	nixture. sical fouling of aquatic organisms.
				t expected to cause any chronic effects to ms at concentrations less than 1 mg/l.

Disposal methods	
Waste from residues	: Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or na	Version 1.0	Revision Date: 2016-09-14	SDS Number: 800010027858	Print Date: 2016-09-15 Date of last issue: - Date of first issue: 14.09.2016
 Contaminated packaging Dispose in accordance with prevailing regulations, preferabl to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand Disposal should be in accordance with applicable regional, national, and local laws and regulations. 	Conta	aminated packaging	tional requireme : Dispose in accorto a recognized the collector or Disposal should	ordance with prevailing regulations, preferably collector or contractor. The competence of contractor should be established beforehand. d be in accordance with applicable regional,

SECTION 14. TRANSPORT INFORMATION

National Regulations

TDG Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category Ship type Product name Special precautions	 Not applicable Not applicable Not applicable Not applicable
Special precautions for user	
Remarks	: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
Additional Information	: MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

The components	of this product are reported in the following inventorie	s:
EINECS	: Not established.	
TSCA	: All components listed.	
DSL	: Not established.	
13 / 14		800010027858
		CA

Version Revision Date: 1.0 2016-09-14

SDS Number: 800010027858

Print Date: 2016-09-15 Date of last issue: -Date of first issue: 14.09.2016

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version. Revision Date : 2016-09-14

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN