According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version Revision Date: SDS Number: Print Date: 2023-10-26

3.0 2023-03-21 800001006645 Date of last issue: 24.04.2021

Date of first issue: 03.03.2011

SECTION 1. IDENTIFICATION

Product name : Shell Gadus S2 V100 2

Product code : 001D8463

Manufacturer or supplier's details

Manufacturer/Supplier : Shell Canada Products

4000-500 Centre Street SE Calgary AB T2G 1A6

Canada

Telephone : (+1) 8006611600 Telefax : (+1) 4033848345

Emergency telephone num-

ber

: CHEMTREC (24 hr): 1 (703) 527-3887 or 1 (800) 424-9300

(US)

Recommended use of the chemical and restrictions on use

Recommended use : Automotive and industrial grease.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

H361f Suspected of damaging fertility. ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

 Version
 Revision Date:
 SDS Number:
 Print Date: 2023-10-26

 3.0
 2023-03-21
 800001006645
 Date of last issue: 24.04.2021

 Date of first issue: 03.03.2011

Precautionary statements : **Prevention**:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention. Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Hazardous components which must be listed on the label:

Contains alkaryl amine.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used grease may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis.

Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Substance name : Shell Gadus S2 V100 2

Chemical nature : A lubricating grease containing highly-refined mineral oils and

additives.

The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346.

Classification based on DMSO extract content < 3% (Regula-

tion (EC) 1272/2008, Annex VI, Part 3, Note L).

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Zinc naphthenate	12001-85-3	0.1 - 0.9
Alkaryl amine	68411-46-1	0.1 - 0.9
Alkyl thiadiazole	13539-13-4	0.01 - 0.09
Triazole derivative	91273-04-0	0.01 - 0.09

SECTION 4. FIRST-AID MEASURES

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version Revision Date: 3.0 2023-03-21

SDS Number: 800001006645

Print Date: 2023-10-26 Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

In case of skin contact

: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait

for symptoms to develop.

Obtain medical attention even in the absence of apparent

wounds.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Most important symptoms and effects, both acute and

delayed

 Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.
 Ingestion may result in nausea, vomiting and/or diarrhoea.
 Local necrosis is evidenced by delayed onset of pain and

tissue damage a few hours following injection.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Notes to physician : Treat symptomatically.

High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue dam-

age and loss of function.

Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthet-

ics, and wide exploration is essential.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon diox-

ide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

: Do not use water in a jet.

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version 3.0

Revision Date: 2023-03-21

SDS Number: 800001006645 Print Date: 2023-10-26 Date of last issue: 24.04.2021

Date of first issue: 03.03.2011

Specific hazards during fire-

fighting

Hazardous combustion products may include:

A complex mixture of airborne solid and liquid particulates and

gases (smoke).

Carbon monoxide may be evolved if incomplete combustion

occurs.

Unidentified organic and inorganic compounds.

Specific extinguishing meth-

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Special protective equipment

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: Avoid contact with skin and eyes.

tive equipment and emer-

gency procedures

Environmental precautions : Use appropriate containment to avoid environmental contami-

> nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Methods and materials for

containment and cleaning up

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Section 13 of

this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Advice on safe handling Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate-

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version Revision Date: SDS Number: Print Date: 2023-10-26

3.0 2023-03-21 800001006645 Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

rials in order to prevent fires.

Avoidance of contact : Strong oxidising agents.

Storage

Other data : Keep container tightly closed and in a cool, well-ventilated

place.

Use properly labeled and closable containers.

Store at ambient temperature.

Packaging material : Suitable material: For containers or container linings, use mild

steel or high density polyethylene.

Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high tem-

peratures because of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-		
		late matter)		

Biological occupational exposure limits

Biological Limit Values (BLV) have not been established for this material.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version 3.0

Revision Date: 2023-03-21

SDS Number: 800001006645 Print Date: 2023-10-26 Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or mainte-

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

Personal protective equipment

Respiratory protection

: No respiratory protection is ordinarily required under normal conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point

>65°C (149°F)].

6/15 800001006645

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version 3.0 Revision Date: 2023-03-21

SDS Number: 800001006645

Print Date: 2023-10-26

Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

Hand protection Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

doponanty on the giove make and meder

: If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Thermal hazards : Not applicable

Protective measures : Personal protective equipment (PPE) should meet recom-

mended national standards. Check with PPE suppliers.

Environmental exposure controls

General advice

Eve protection

Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version 3.0

Revision Date: 2023-03-21

SDS Number: 800001006645

Print Date: 2023-10-26

Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

vapour.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Semi-solid at room temperature.

Colour : light brown

Odour : Slight hydrocarbon

Odour Threshold : Data not available

pH : Not applicable

Dropping point : 180 °C / 356 °F

Method: IP 396

Melting / freezing point Not applicable

Initial boiling point and boiling

range

: Data not available

Flash point : Not applicable

Evaporation rate : Data not available

Flammability

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Not classified as flammable but will burn.

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : Typical 10 %(V)

Lower explosion limit : Typical 1 %(V)

Vapour pressure : $< 0.5 \text{ Pa } (20 \,^{\circ}\text{C} / 68 \,^{\circ}\text{F})$

estimated value(s)

Relative vapour density : > 1

estimated value(s)

Relative density : $0.900 (15 \,^{\circ}\text{C} / 59 \,^{\circ}\text{F})$

Density : 900 kg/m3 (15.0 °C / 59.0 °F)Method: Unspecified

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n- : log Pow: > 6

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version Revision Date: SDS Number: Print Date: 2023-10-26

3.0 2023-03-21 800001006645 Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

octanol/water (based on information on similar products)

Auto-ignition temperature : > 320 °C / 608 °F

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 11 mm2/s (100 °C / 212 °F)

Method: ASTM D445

100 mm2/s (40.0 °C / 104.0 °F)

Method: ASTM D445

Explosive properties : Classification Code: Not classified

Oxidizing properties : Data not available

Surface tension : Data not available

Conductivity : This material is not expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product does not pose any further reactivity hazards in

addition to those listed in the following sub-paragraph.

Chemical stability : Stable.

Possibility of hazardous reac-

tions

: Reacts with strong oxidising agents.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidising agents.

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment : Information given is based on data on the components and

the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a

whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

9 / 15 CA

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version Revision Date: SDS Number: Print Date: 2023-10-26

3.0 2023-03-21 800001006645 Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

Acute toxicity

Product:

Acute oral toxicity : LD50 (rat): > 5,000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Low toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin result-

ing in disorders such as oil acne/folliculitis.

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye.

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Non mutagenic

Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen.

Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies.

Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

10 / 15 800001006645

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version Revision Date: SDS Number: Print Date: 2023-10-26

3.0 2023-03-21 800001006645 Date of last issue: 24.04.2021

Date of first issue: 03.03.2011

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Product:

Effects on fertility

Remarks: Suspected of damaging fertility.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version 3.0

Revision Date: 2023-03-21

SDS Number: 800001006645 Print Date: 2023-10-26 Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

for this product.

Information given is based on a knowledge of the components

and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

Ecotoxicity

Product:

Toxicity to fish (Acute toxici-

Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to crustacean (Acute

toxicity)

Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to algae/aquatic

plants (Acute toxicity)

Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic tox-

icity)

Remarks: Based on available data, the classification criteria

are not met.

Toxicity to crustacean (Chronic toxicity)

: Remarks: Based on available data, the classification criteria

are not met.

Toxicity to microorganisms

(Acute toxicity)

: Remarks: Based on available data, the classification criteria

are not met.

Persistence and degradability

Product:

Biodegradability Remarks: Not readily biodegradable.

Major constituents are inherently biodegradable, but contains

components that may persist in the environment.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains components with the potential to bioac-

cumulate.

Partition coefficient: n-

octanol/water

: log Pow: > 6

Remarks: (based on information on similar products)

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version 3.0

Revision Date: 2023-03-21

SDS Number: 800001006645 Print Date: 2023-10-26 Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

Mobility in soil

Product:

Mobility Remarks: Semi-solid under most environmental conditions.

If it enters soil, it will adsorb to soil particles and will not be

mobile.

Remarks: Floats on water.

Other adverse effects

Product:

Additional ecological infor-

mation

: Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential.

Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal

conditions of use.

Poorly soluble mixture.

Causes physical fouling of aquatic organisms.

Mineral oil does not cause chronic toxicity to aquatic organ-

isms at concentrations less than 1 mg/l.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water

Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech-

nical aspects at controlling pollutions from ships.

Contaminated packaging

: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of

800001006645 13 / 15

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version Revision Date: SDS Number: Print Date: 2023-10-26

3.0 2023-03-21 800001006645 Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local legislation

Remarks : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

TDG

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mix-

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

The components of this product are reported in the following inventories:

TSCA : All components listed.

DSL : All components listed.

According to the Hazardous Products Regulations

Shell Gadus S2 V100 2

Version 3.0 Revision Date: 2023-03-21

SDS Number: 800001006645

Print Date: 2023-10-26 Date of last issue: 24.04.2021 Date of first issue: 03.03.2011

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version. There has been an increase in the Health Hazard classification of this product in section 2. Ensure that the related sections (particularly sections 4, 8 & 11) are carefully studied. Revision Date : 2023-03-21

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN