Version 1.1	Revision Date: 2016-03-09		DS Number: 0001004622	Print Date: 2016-04-25 Date of last issue: 02.02.2016 Date of first issue: 02.02.2016		
SECTION	1. IDENTIFICATION					
Produ	ct name	:	: Shell Transmission Oil MA 75W-90			
Product code		:	901L3454			
Manufacturer or supplier's details						
Manu	facturer/Supplier	:	Shell Canada Pro 400 - 4th Avenue Calgary AB T2P Canada	S.W		
Telep Telefa		:	(+1) 8006611600 (+1) 4033848345			
Emerg ber	gency telephone num-	:	UTEC (226-8832)	): (+1) 613-996-6666; Toll Free: 1-888-CAN- ) hr): 1 (703) 527-3887 or 1 (800) 424-9300		

### Recommended use of the chemical and restrictions on use

Recommended use	: Transmission oil.	

## **SECTION 2. HAZARDS IDENTIFICATION**

GHS Classification Chronic aquatic toxicity	: Category 3
GHS label elements	
Hazard pictograms	: No symbol
Signal word	: No signal word
Hazard statements	<ul> <li>PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: H412 Harmful to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	<ul> <li>Prevention:</li> <li>P273 Avoid release to the environment.</li> <li>Response:</li> <li>No precautionary phrases.</li> </ul>
/ 14	800001004622

Version	Revision Date:	SDS Number:	Print Date: 2016-04-25
1.1	2016-03-09	800001004622	Date of last issue: 02.02.2016 Date of first issue: 02.02.2016

### Storage:

No precautionary phrases. **Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name	: Shell Transmission Oil MA 75W-90
Chemical nature	<ul> <li>Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains &lt;3% (w/w) DMSO- extract, according to IP346. The highly refined mineral oil is only present as additive dilu- ent.</li> </ul>
	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-

9.

### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Alkyl dithiophosphate	Not Assigned	0.25 - 2.4
Alkyl phosphonate	Not Assigned	0.25 - 2.4
Alkyl amine	68955-53-3	0.1 - 0.99
Alkyl thiadiazole	73984-93-7	0.1 - 0.99
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	0 - 90

# **SECTION 4. FIRST-AID MEASURES**

	ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of skin contact	If symptoms persist, obtain medical advice. : Remove contaminated clothing. Flush exposed area with wa-
If inhaled	: No treatment necessary under normal conditions of use.
General advice	: Not expected to be a health hazard when used under normal conditions.

Version 1.1	Revision Date: 2016-03-09	SDS Number: 800001004622	Print Date: 2016-04-25 Date of last issue: 02.02.2016 Date of first issue: 02.02.2016	
		If persistent ir	ritation occurs, obtain medical attention.	
If swallowed		: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.		
Most important symptoms and effects, both acute and delayed		of black pustu	ulitis signs and symptoms may include formation les and spots on the skin of exposed areas. result in nausea, vomiting and/or diarrhoea.	
Protection of first-aiders		appropriate pe	stering first aid, ensure that you are wearing the ersonal protective equipment according to the y and surroundings.	
Note	s to physician	: Treat symptor	natically.	

# **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	: Avoid contact with skin and eyes.
Environmental precautions	: Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
	Local authorities should be advised if significant spillages
14	800001004622

Version 1.1	Revision Date: 2016-03-09	SDS Number: 800001004622	Print Date: 2016-04-25 Date of last issue: 02.02.2016 Date of first issue: 02.02.2016
		cannot be conta	ined.
	ds and materials for nment and cleaning up	Prevent from sp or other contain Reclaim liquid di Soak up residue	pilt. Avoid accidents, clean up immediately. reading by making a barrier with sand, earth ment material. irectly or in an absorbent. with an absorbent such as clay, sand or other and dispose of properly.
Additio	onal advice	see Chapter 8 o	selection of personal protective equipment f this Safety Data Sheet. disposal of spilled material see Chapter 13 of Sheet.

# SECTION 7. HANDLING AND STORAGE

General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
Storage		
Other data	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

Version	Revision Date:	SDS Number:	Print Date: 2016-04-25
1.1	2016-03-09	800001004622	Date of last issue: 02.02.2016
			Date of first issue: 02.02.2016

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhal- able frac- tion))	5 mg/m3	US. ACGIH Threshold Limit Values

### **Biological occupational exposure limits**

No biological limit allocated.

### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	<ul> <li>The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.</li> </ul>
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of
4.4	equipment used to control exposure, e.g. personal protective

Version 1.1	Revision Date: 2016-03-09	SDS Number: 800001004622	Print Date: 2016-04-25 Date of last issue: 02.02.2016 Date of first issue: 02.02.2016
		Drain down sys nance. Retain drain do subsequent rec Always observe washing hands drinking, and/or protective equip	good personal hygiene measures, such as after handling the material and before eating, smoking. Routinely wash work clothing and ment to remove contaminants. Discard con- ing and footwear that cannot be cleaned.
	onal protective equipr iratory protection	: No respiratory p conditions of us In accordance w tions should be If engineering c tions to a level w select respirato cific conditions Check with resp Where air-filteri priate combinat Select a filter su	protection is ordinarily required under normal te. with good industrial hygiene practices, precau- taken to avoid breathing of material. ontrols do not maintain airborne concentra- which is adequate to protect worker health, ry protection equipment suitable for the spe- of use and meeting relevant legislation. biratory protective equipment suppliers. ng respirators are suitable, select an appro- ion of mask and filter. uitable for the combination of organic gases type A/Type P boiling point >65°C (149°F)].
	l protection marks	gloves approve US: F739) mad suitable chemic gloves Suitabilit usage, e.g. freq sistance of glov glove suppliers. Personal hygier Gloves must on gloves, hands s cation of a non- For continuous through time of 480 minutes wh short-term/splas recognize that s may not be ava time maybe acc and replacemer a good predicto dependent on th Glove thickness	ntact with the product may occur the use of d to relevant standards (e.g. Europe: EN374, e from the following materials may provide al protection. PVC, neoprene or nitrile rubber by and durability of a glove is dependent on uency and duration of contact, chemical re- e material, dexterity. Always seek advice from Contaminated gloves should be replaced. he is a key element of effective hand care. ly be worn on clean hands. After using should be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- more than 240 minutes with preference for > here suitable gloves can be identified. For sh protection we recommend the same, but suitable gloves offering this level of protection ilable and in this case a lower breakthrough the petable so long as appropriate maintenance in regimes are followed. Glove thickness is not r of glove resistance to a chemical as it is ne exact composition of the glove material. a should be typically greater than 0.35 mm and glove make and model.

Version 1.1	Revision Date: 2016-03-09	SDS Number: 800001004622	Print Date: 2016-04-25 Date of last issue: 02.02.2016 Date of first issue: 02.02.2016	
Eye p	protection		andled such that it could be splashed into eyes, wear is recommended.	
Skin a	and body protection	work clothes.	Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.	
Therr	nal hazards	: Not applicable	Not applicable	
Prote	ctive measures		Personal protective equipment (PPE) should meet recom- mended national standards. Check with PPE suppliers.	
Envir	onmental exposure c	ontrols		
Gene	ral advice	vant environm of the environ necessary, pro charged to wa municipal or in discharge to s Local guidelin	<ul> <li>Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.</li> <li>Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containin</li> </ul>	

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid at room temperature.
Colour	: amber
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рН	: Not applicable
pour point	: -42 °C / -44 °F Method: ISO 3016
Initial boiling point and boiling range	: > 280 °C / 536 °F estimated value(s)
Flash point	: 215 °C / 419 °F
	Method: ISO 2592
Evaporation rate	: Data not available

Vers 1.1	sion	Revision Date: 2016-03-09		S Number: 0001004622	Print Date: 2016-04-25 Date of last issue: 02.02.2016 Date of first issue: 02.02.2016		
	Flammability (solid, gas)		:	Data not availabl	e		
	Upper e	explosion limit	:	Typical 10 %(V)			
	Lower e	explosion limit	:	Typical 1 %(V)			
	Vapour pressure		:		< 0.5 Pa (20 °C / 68 °F) estimated value(s)		
	Relative vapour density		:	> 1 estimated value(s)			
	Relative	e density	:	0.847 (15 °C / 59	°F)		
	Density	,	:	847 kg/m3 (15.0	°C / 59.0 °F)Method: ASTM D1298		
	Solubili Wate	ty(ies) er solubility	:	negligible			
	Solul	bility in other solvents	:	Data not availabl	e		
	Partition coefficient: n- octanol/water		:	Pow: > 6 (based on information on similar products)			
	Auto-ignition temperature		:	> 320 °C / 608 °F	-		
	Viscosi Visco	ty osity, dynamic	:	Data not availabl	e		
	Visco	osity, kinematic	:	96 mm2/s (40.0 ° Method: ASTM D			
				14.6 mm2/s (100 Method: ASTM D			
	Explosi	ve properties	:	Not classified			
	Oxidizir	ng properties	:	: Data not available			
	Conductivity : This material is not expected to be a static accumula		ot expected to be a static accumulator.				
	Decom	position temperature	:	Data not availabl	e		

# SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.	I
Chemical stability	: Stable.	
Possibility of hazardous reac-	: Reacts with strong oxidising agents.	
14	800001004	622

Version 1.1	Revision Date: 2016-03-09	SDS Number: 800001004622	Print Date: 2016-04-25 Date of last issue: 02.02.2016 Date of first issue: 02.02.2016	
tior	IS			
Conditions to avoid		: Extremes of temperature and direct sunlight.		
Inc	ompatible materials	: Strong oxidising	: Strong oxidising agents.	
Hazardous decomposition products			: Hazardous decomposition products are not expected to form during normal storage.	

### SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on data on the components and
	the toxicology of similar products. Unless indicated otherwise,
	the data presented is representative of the product as a
	whole, rather than for individual component(s).

#### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

### Acute toxicity

#### Product:

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	:	Remarks: Not considered to be an inhalation hazard under normal conditions of use.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Expected to be of low toxicity:

#### Skin corrosion/irritation

# Product:

Remarks: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

#### Serious eye damage/eye irritation

## Product:

Remarks: Expected to be slightly irritating.

### Respiratory or skin sensitisation

### Product:

Remarks: Not expected to be a skin sensitiser.

#### Components:

Version	Revision Date:	SDS Number:	Print Date: 2016-04-25
1.1	2016-03-09	800001004622	Date of last issue: 02.02.2016
			Date of first issue: 02.02.2016

### Alkyl amine:

Remarks: May cause an allergic skin reaction in sensitive individuals.

#### Alkyl thiadiazole:

Remarks: May cause an allergic skin reaction in sensitive individuals.

:

#### Germ cell mutagenicity

#### Product:

Genotoxicity in vivo

: Remarks: Not considered a mutagenic hazard.

### Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

### **Reproductive toxicity**

### Product:

Effects on fertility

Remarks: Not expected to impair fertility. Not expected to be a developmental toxicant.

### STOT - single exposure

#### Product:

Remarks: Not expected to be a hazard.

### STOT - repeated exposure

#### Product:

Remarks: Not expected to be a hazard.

### Aspiration toxicity

### Product:

Not considered an aspiration hazard.

### **Further information**

### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.

ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

Version	Revision Date:	SDS Number:	Print Date: 2016-04-25
1.1	2016-03-09	800001004622	Date of last issue: 02.02.2016
			Date of first issue: 02.02.2016

### **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity		
Product:		
Toxicity to fish (Acute toxici- ty)	:	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l
Toxicity to crustacean (Acute toxicity)	:	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l
Toxicity to algae/aquatic plants (Acute toxicity)	:	Remarks: Expected to be harmful: LL/EL/IL50 10-100 mg/l
Toxicity to fish (Chronic tox- icity)	:	Remarks: Data not available
Toxicity to crustacean	:	Remarks: Data not available
(Chronic toxicity) Toxicity to microorganisms (Acute toxicity)	:	Remarks: Data not available
Components: Alkyl dithiophosphate: M-Factor (Acute aquatic tox- icity)	:	1
Persistence and degradabilit	ty	
Product:		
Biodegradability	:	Remarks: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegrada- ble, but contains components that may persist in the environ- ment.
Bioaccumulative potential		
Product:		
Bioaccumulation		Remarks: Contains components with the potential to bioac-

Version 1.1	Revision Date: 2016-03-09	SDS Number: 800001004622	Print Date: 2016-04-25 Date of last issue: 02.02.2016 Date of first issue: 02.02.2016		
Partiti	on coefficient: n-	cumulate. : Pow: > 6			
	ol/water		Remarks: (based on information on similar products)		
Mobil	ity in soil				
<u>Product:</u> Mobility		If it enters soil, i mobile.	<ul> <li>Remarks: Liquid under most environmental conditions.</li> <li>If it enters soil, it will adsorb to soil particles and will not be mobile.</li> <li>Remarks: Floats on water.</li> </ul>		
Other	adverse effects	remarks. Float			
Product: Additional ecological infor- mation		expected to be Not expected to cal ozone creat Poorly soluble r	<ul> <li>Product is a mixture of non-volatile components, which are n expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemi- cal ozone creation potential or global warming potential.</li> <li>Poorly soluble mixture. May cause physical fouling of aquatic organisms.</li> </ul>		

# SECTION 13. DISPOSAL CONSIDERATIONS

<b>Disposal methods</b> Waste from residues	: Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.	
	Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or na- tional requirements and must be complied with.	
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.	

# SECTION 14. TRANSPORT INFORMATION

## **National Regulations**

**TDG** Not regulated as a dangerous good

Version 1.1	Revision Date: 2016-03-09	SDS Number: 800001004622	Print Date: 2016-04-25 Date of last issue: 02.02.2016 Date of first issue: 02.02.2016	
Internatio	onal Regulation			
	A-DGR regulated as a dangero	ous good		
	IMDG-Code Not regulated as a dangerous good			
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code				
Pollution category Ship type Product name Special precautions		<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>	<ul><li>Not applicable</li><li>Not applicable</li></ul>	
Special p	precautions for user			
Rem	arks	for special prec	: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.	
Add	itional Information	: MARPOL Anne	ex 1 rules apply for bulk shipments by sea.	
SECTION 15. REGULATORY INFORMATION				

# Safety, health and environmental regulations/legislation specific for the substance or mix-

#### ture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

The components of this product are reported in the following inventories:			
EINECS	: All components listed or polymer exempt.		
TSCA	: All components listed.		
DSL	: All components listed.		

# **SECTION 16. OTHER INFORMATION**

### Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization;

Version	Revision Date:	SDS Number:	Print Date: 2016-04-25
1.1	2016-03-09	800001004622	Date of last issue: 02.02.2016
			Date of first issue: 02.02.2016

IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization: ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS -Workplace Hazardous Materials Information System

A vertical bar (|) in the left margin indicates an amendment from the previous version. Revision Date : 2016-03-09

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN