

SAFETY DATA SHEET

SECTION 1) IDENTIFICATION

Product Name: COOLCUT® SYN GRIND

Synonym: C-06

Product Code: 58-A 707, 58-A 708

Revision Date: Jun 21, 2022 Date Printed: Jul 08, 2022

Version: 1.0 Supersedes Date: N.A.

Manufacturer's Name: United States - Walter Surface Technologies Inc.

Address: 810 Day Hill Road Windsor, CT, US, 06095

Emergency Phone: INFOTRAC® 1-800-535-5053. International call collect: 1-352-323-3500 24 hours/day, 7 days/week.

Information Phone Number: +1 (866) 592-5837

Fax:

Product/Recommended Uses: Metal working fluid, cutting lubricant and coolant.

SECTION 2) HAZARDS IDENTIFICATION

Type of product

Liquid

Classification

Acute aquatic toxicity - Category 3

Chronic aquatic toxicity - Category 3

Corrosive to metals - Category 1

Flammable Liquids - Category 4

Serious Eye Damage - Category 1

Skin Irritation - Category 2

Pictograms



Signal Word

Danger

Hazardous Statements - Health

H318 - Causes serious eye damage

H315 - Causes skin irritation

Hazardous Statements - Physical

H290 - May be corrosive to metals

H227 - Combustible Liquid

Hazardous Statements - Environmental

H412 - Harmful to aquatic life with long lasting effects

58-A 707, 58-A 708 www.walter.com Page 1 of 10

Precautionary Statements - General

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.

Precautionary Statements - Prevention

- P273 Avoid release to the environment.
- P234 Keep only in original packaging.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P280 Wear protective gloves, protective clothing, eye protection/face protection.
- P264 Wash thoroughly after handling.

Precautionary Statements - Response

- P390 Absorb spillage to prevent material damage.
- P370 + P378 In case of fire: Use carbon-di oxide, alcohol foam, water spray or dry chemical to extinguish.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER or doctor.
- P302 + P352 IF ON SKIN: Wash with plenty of water.
- P321 Specific treatment (see First-Aid on this label).
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P362 + P364 Take off contaminated clothing. And wash it before reuse.

Precautionary Statements - Storage

- P406 Store in a corrosive resistant container with a resistant inner liner.
- P403 Store in a well-ventilated place.

Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local/national/international regulations.

Hazards Not Otherwise Classified (HNOC) (Physical & Health)

no data available

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Mixture

The product is a mixture.

CAS	Chemical Name	GHS Classifications	% By Weight
0000102-71-6	TRIETHANOLAMINE	Acute Tox. Oral 5, H303; Eye Irr. 2A, H319; Skin Irr. 3, H316	10.00% - 25.00%
0000141-43-5	ETHANOLAMINE	Acute Tox. Derm. 4, H312; Acute Tox. Inh. 4, H332; Acute Tox. Oral 4, H302; Aquatic Acute 3, H402; Eye Dam. 1, H318; Flam. Liq. 4, H227; Met. Corr. 1, H290; Skin Corr. 1B, H314	3.00% - 5.00%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor. Eliminate all ignition sources if safe to do so.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 30 minutes or until medical aid is available. Take care not to rinse contaminated

58-A 707, 58-A 708 www.walter.com Page 2 of 10

water into the unaffected eye or onto the face. Immediately call a POISON CENTER or doctor.

Skin Contact

Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Rinse skin with lukewarm, gently flowing water/shower for a duration of 30 minutes or until medical aid is available. Immediately call a POISON CENTER or doctor. Store contaminated clothing under water and wash before re-use or discard.

Ingestion

If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Never give anything by mouth to an unconscious person. Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

Most important symptoms/effects, acute and delayed

Eye contact

Causes serious eye damage.

Inhalation

No known significant effects or critical hazards.

Skin contact

Causes skin irritation.

Ingestion

No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact (OE)

Adverse symptoms may include the following: pain or irritation watering redness

Inhalation (OE)

No known significant effects or critical hazards.

Skin contact (OE)

Adverse symptoms may include the following: pain or irritation redness blistering may occur

Ingestion (OE)

Adverse symptoms may include the following: stomach pains

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire: Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire: Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

None. Do not use straight stream of water.

Specific Hazards in Case of Fire

This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In case of fire, hazardous decomposition products may include carbon oxides. Runoff may pollute waterways Fire will produce irritating and corrosive gases. Containers may explode in fire. Most vapors are

58-A 707, 58-A 708 www.walter.com Page 3 of 10

heavier than air. Vapors may form explosive mixtures with air Vapors will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to source of ignition and flash back. Many liquids are lighter than water. May form an ignitable vapor/air mixture in closed tanks or containers.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Stay uphill and/or upstream. Ventilate closed spaces before entering. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Evacuate and isolate hazard area and keep unauthorized personnel away. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. A vapor-suppressing foam may be used to reduce vapors.

Recommended Equipment

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA).

Personal Precautions

Avoid breathing vapor or mist. Do not get on skin, eyes or clothing.

Environmental Precautions

Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Dike far ahead of liquid spill for later disposal.

Methods and Materials for Containment and Cleaning up

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Contaminated absorbent material may pose the same hazard as the spilled product. If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated. Ventilate area after clean-up is complete. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean, non-sparking tools to collect absorbed material.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use. Avoid breathing vapor or mist. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. All containers must be properly labelled. Eyewash stations and showers should be available in areas where this material is used and stored ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not get in eyes, on skin, or on clothing.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

Storage Room Requirements

Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous. Store in approved containers and protect against physical damage. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and strong oxidizers. Take precautionary measures against electrostatic discharge. To avoid fire or explosion, dissipate static electricity during transfer by ground and bonding containers and equipment before transferring material. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear safety glasses complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid

58-A 707, 58-A 708 www.walter.com Page 4 of 10

exposure to liquid splashes, mists, gases or dusts. Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

If vapor or mist is generated when material is heated or handled, provide adequate ventilation to keep the airborne concentrations of vapors below their respective threshold limit value. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (mg/m3)
ETHANOLAMI NE		3		6		Eye & skin irr		6
TRIETHANOLA MINE	5					Eye & skin irr		

Chemical Name	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Tables (Z1, Z2, Z3)	OSHA Skin designation	CAN_ONtmg	CAN_ONtppm
ETHANOLAMI NE	3				1			
TRIETHANOLA MINE							3.1	0.5

Chemical Name	CAN_ONsmg	CAN_ONsppm
ETHANOLAMI NE		
TRIETHANOLA MINE		

irr - Irritation

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical and Chemical Properties

Type of product : liquid.

 Density
 9.43 lb/gal

 Specific Gravity
 1.13

 % VOC
 0.00%

 Density VOC
 0.00 lb/gal

Appearance colorless liquid

Odor Threshold N/A

Odor Description Characteristic

pH 9.50

Water Solubility Fully miscible in water.

Flammability

Flash Point Symbol N/A

58-A 707, 58-A 708 www.walter.com Page 5 of 10

Flash Point N/A

Viscosity Kinematic (20oC (68oF)): 0.06 cm2 /s (6 cSt)

Lower Explosion Level N/A Upper Explosion Level N/A Vapor Density N/A Freezing Point N/A Melting Point N/A Low Boiling Point N/A High Boiling Point N/A Auto Ignition Temp N/A **Evaporation Rate** N/A Coefficient Water/Oil N/A

SECTION 10) STABILITY AND REACTIVITY

Stability

Stable under normal storage and handling conditions.

Conditions To Avoid

Avoid all possible sources of ignition, heat, sparks, flame, build up of static electricity and contact with incompatible materials.

Hazardous Reactions/Polymerization

Will not occur.

Incompatible Materials

Strong bases, acids, and oxidizing agents. Corrosive in contact with metals.

Hazardous Decomposition Products

Oxides of carbon.

SECTION 11) TOXICOLOGICAL INFORMATION

Acute Toxicity

Based on available data, the classification criteria are not met.

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

Aspiration Hazard

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

0000102-71-6 TRIETHANOLAMINE

Not carcinogenic

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

0000102-71-6 TRIETHANOLAMINE

Not genotoxic

Reproductive Toxicity

Based on available data, the classification criteria are not met.

0000102-71-6 TRIETHANOLAMINE

58-A 707, 58-A 708 www.walter.com Page 6 of 10

Not toxic to development or the reproductive system.

Respiratory/Skin Sensitization

Based on available data, the classification criteria are not met.

Serious Eye Damage/Irritation

Causes serious eye damage

0000141-43-5 ETHANOLAMINE

Corrosive to the eye.

Skin Corrosion/Irritation

Causes skin irritation

0000102-71-6 TRIETHANOLAMINE

Mild skin irritation following repeated exposures using the dermal route.

0000141-43-5 ETHANOLAMINE

Corrosive to the skin.

Specific Target Organ Toxicity - Repeated Exposure

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Based on available data, the classification criteria are not met.

0000102-71-6 TRIETHANOLAMINE

Triethanolamine is of low toxicity following single exposures.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

0000141-43-5 ETHANOLAMINE

The substance can be absorbed into the body by inhalation, by ingestion and through the skin.

Miscellaneous Health Effects

0000141-43-5 ETHANOLAMINE

The substance is corrosive to the respiratory tract, skin and eyes. Corrosive on ingestion. The vapour is irritating to the eyes, skin and respiratory tract. The substance may cause effects on the central nervous system. Exposure could cause lowering of consciousness. Repeated or prolonged contact may cause skin sensitization.

0000102-71-6 TRIETHANOLAMINE

LD50 (oral, rat): 5000-9110 mg/kg (2,8,17,18)

LD50 (oral, mouse): 7400 mg/kg (18)

LD50 (oral, rabbit): 2200 mg/kg (18) (reported but cannot be confirmed)

LD50 (oral, guinea pig): 8000 mg/kg (8,17); 2200 mg/kg (18) (reported but cannot be confirmed)

0000141-43-5 ETHANOLAMINE

LD50 (oral, rat): 1720 mg/kg (10); 2100 mg/kg (3); 2740 mg/kg (3,8)

LD50 (oral, mouse): 700 mg/kg (10) LD50 (oral, guinea pig): 620 mg/kg (10) LD50 (oral, rabbit): 1000 mg/kg (10)

LD50 (dermal, rabbit): 1018 mg/kg (cited as 1 mL/kg) (10)

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Harmful to aquatic life

Harmful to aquatic life with long lasting effects

0000102-71-6 TRIETHANOLAMINE

Triethanolamine is a basic compound, thus if it is released to water in large quantities, effects on the pH of the receiving water might be expected.

Persistence and Degradability

58-A 707, 58-A 708 www.walter.com Page 7 of 10

0000141-43-5 ETHANOLAMINE

Readily biodegradable

Bioaccumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000141-43-5 ETHANOLAMINE

The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION

	IATA Information	IMDG Information	U.S. DOT Information	Canada TDG Information
UN number:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Proper shipping name:	N/A	N/A	N/A	N/A
Hazard class:				Not Applicable
Hazard class:	Not Applicable	Not Applicable	Not Applicable	
Packaging group:	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Hazardous substance (RQ):			No Data Available	
Marine Pollutant:	NA	No Data Available	No Data Available	No Data Available
Note / Special Provision:	No Data Available	No Data Available	No Data Available	No Data Available
Toxic-Inhalation Hazard:	NA	NA	No Data Available	No Data Available

SECTION 15) REGULATORY INFORMATION

U.S. Federal regulations

United States inventory (TSCA 8b): All components are listed or exempted.

TSCA 4(a) proposed test rules: Benzotriazole

Commerce control list precursor: 2,2',2"-Nitrilotriethanol

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)

None of the components are listed.

Clean Air Act Section 602 Class I Substances

None of the components are listed.

Clean Air Act Section 602 Class II Substances

58-A 707, 58-A 708 www.walter.com Page 8 of 10

None of the components are listed.

DEA List I Chemicals (Precursor Chemicals)

None of the components are listed.

DEA List II Chemicals (Essential Chemicals)

None of the components are listed.

SARA 302/304

None of the components are listed.

SARA 313

None of the components are listed.

SARA 311/312

SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1

States regulations

Massachusetts: The following components are listed: 2,2',2"-Nitrilotriethanol; 1-Aminopropan-2-ol; New Jersey: The following components are listed: 2,2',2"-Nitrilotriethanol; 1-Aminopropan-2-ol Pennsylvania: The following components are listed: 2,2',2"-Nitrilotriethanol; 1-Aminopropan-2-ol

New Jersey: None of the components are listed.

Canada

Canadian NPRI: None of the components are listed.

CEPA toxic substance : None of the components are listed.

Canada inventory (DSL NDSL): All components are listed or exempted.

International lists

China: All components are listed or exempted.

New Zealand: All components are listed or exempted.

Philippines: All components are listed or exempted.

Taiwan: All components are listed or exempted.

Australia: All components are listed or exempted.

Europe: All components are listed or exempted.

Turkey: All components are listed or exempted.

Republic of Korea: All components are listed or exempted.

California Proposition 65

Prop 65: No products found

CAS	Chemical Name	% By Weight	Regulation List
0000102-71-6	TRIETHANOLAMINE	10.00% - 25.00%	DSL,TSCA
0000141-43-5	ETHANOLAMINE	3.00% - 5.00%	DSL,TSCA

The information in this Section does not list non-hazardous components that might have relevant DSL, TSCA regulatory values, if they are present at less than 5%. Please contact manufacturer for more information.

Product does not contain any chemicals listed under California Proposition 65

SECTION 16) OTHER INFORMATION

Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDGCanadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center(US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of

58-A 707, 58-A 708 www.walter.com Page 9 of 10

Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System. ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

Version 1.0:

Revision Date: Jun 21, 2022

First Edition.

Full text of H-Statements referred to under Section 3

H316 Causes mild skin irritation H318 Causes serious eye damage H319 Causes serious eye irritation H314 Causes severe skin burns and eye damage Combustible Liquid H227 H332 Harmful if inhaled H302 Harmful if swallowed H312 Harmful in contact with skin H402 Harmful to aquatic life H290 May be corrosive to metals H303 May be harmful if swallowed

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

58-A 707, 58-A 708 www.walter.com Page 10 of 10